

Machine Tools prys

Machine Tools Price

E-mail: eva@mzgtool.cn



Skandeer, Kontak ons

Scanning , Contact Us

- | | | | |
|--|---|---|---|
| P01. Carbide Milling Cutter
Carbide Milling Cutter |  | P16. Eksterne Cilindriese / Inner Gat Grooving Turning Tool
External Cylindrical/Inner Hole Grooving Turning Tool |  |
| P02. Gesementeerde Carbide Cutter
Cemented Carbide Cutter |  | P17. Grooving / Cut-Off Turning Tool
Grooving/Cut-Off Turning Tool |  |
| P03. Ekstrusie Skroef Tap
Extrusion Screw Tap |  | P18. End Face / Inner Hole Grooving Turning Tool
End Face/Inner Hole Grooving Turning Tool |  |
| P04. Apex Tap
Apex Tap |  | P19. CNC Draai Gereedskap
CNC Turning Tool |  |
| P05. Spiraal Gekruiste Kraan
Spiral Grooved Tap |  | P20. CNC draai gereedskap dele
CNC Turning Tool Parts |  |
| P06. Hand Tap / Circular Die
Hand Tap/Circular Die |  | P21. BAP reghoekige freesmaaier
BAP reghoekige freesmaaier |  |
| P07. CCMT.. CNMG.. |  | P22. Machine-Clamped Ronde Neus Milling Snyder
Machine-Clamped Round Nose Milling Cutter |  |
| P08. DCMT.. DNMG.. |  | P23. KM12.. SEHT.. T2139.. P3200.. |  |
| P09. SCMT.. SNMG.. |  | P24. Sluittand Tipe snyer
Locking Tooth Type Cutter |  |
| P10. TPGT.. TNMG.. |  | P25. Boring Tool
Boring Tool |  |
| P11. VBMT.. VNMG.. |  | P26. Boor Tool Holder
Boring Tool Holder |  |
| P12. WNMG.. WNMG.. |  | P27. ER.. FMA/B.. |  |
| P13. Draaddraaitoerusting
Thread Turning Tool |  | P28. GSK.. ADS.. APU.. |  |
| P14. Cut-Off / Grooving / Terug Draai Van Klein Onderdele
Cut-Off/Grooving/Back Turning Of Small Parts |  | P29. CNC Tool Holder Toebehore
CNC Tool Holder Accessories |  |
| P15. Eksterne Cilindriese Grooving Turning Tool
External Silindriese Grooving Turning Tool |  | P30. Draaibank Toebehore
Lathe Chuck Accessories |  |


Professionele draai-, frees-, gordel- en boorgatverwerkingsgereedskapskonfigurasie.

Professional Turning, Milling, Threading and Boring Hole Processing Tool Configuration.

MaiFix®

MZG®

MOSASK®



Die L1-lengte van die freesmaaiër met verskillende hardheid kan anders wees.

The L1 Length Of Milling Cutter With Different Hardness May Be Different.

Right-Angle Milling Cutter D1xL1xDxL	Ball End Milling Cutter R1xDxL
---	-----------------------------------

		Swart bedekkings kan sny Staal onder 45HRC Black Coatings Can Cut Steel Below 45 HRC		Koperbedekkings kan sny Staal onder 55HRC Copper Coatings Can Cut Steel Below 55 HRC		Nano Black Coatings kan sny Staal onder 58HRC Nano Black Coatings Can Cut Steel Below 58 HRC		Nano Koper Coatings kan sny Staal onder 60HRC Nano Copper Coatings Can Cut Steel Below 60 HRC		Nano Blue Coatings Kan Sny staal onder 65HRC Nano Blue Coatings Can Cut Steel Below 65 HRC	
1. 0x3xD4x50	R0. 5x2xD4x50	2.0	2.6	2.7	3.1	4.6	5.1	5.1	5.1	5.7	5.7
1. 5x4xD4x50	R0. 75x3xD4x50	2.0	2.6	2.7	3.1	4.6	5.1	5.1	5.1	5.7	5.7
2. 0x6xD4x50	R1. 0x4xD4x50	2.0	2.6	2.7	3.1	4.6	5.1	5.1	5.1	5.7	5.7
2. 5x8xD4x50	R1. 25x5xD4x50	2.0	2.6	2.7	3.1	4.6	5.1	5.1	5.1	5.7	5.7
3. 0x8xD3x50	R1. 5x6xD3x50	2.0	2.6	2.7	3.1	4.6	5.1	5.1	5.1	5.7	5.7
3. 0x12xD3x75	R1. 5x6xD3x75	3.1	3.9	4.4	5.1	7.1	7.1	7.1	7.1	7.7	7.7
3. 0x15xD3x100	R1. 5x6xD3x100	3.6	4.4	5.0	5.6	8.7	8.7	8.7	8.7	8.7	8.7
3. 0x8xD4x50	R1. 5x6xD4x50	2.0	2.6	2.7	3.1	4.6	5.1	5.1	5.1	5.7	5.7
3. 5x10xD4x50	R1. 75x7xD4x50	2.0	2.6	2.7	3.1	4.6	5.1	5.1	5.1	5.7	5.7
4. 0x10xD4x50	R2. 0x8xD4x50	1.7	2.6	2.7	3.1	4.6	6.0	6.1	6.1	5.7	5.7
4. 0x20xD4x75	R2. 0x8xD4x75	2.9	3.6	4.4	5.1	7.1	7.9	8.1	8.1	7.7	7.7
4. 0x25xD4x100	R2. 0x8xD4x100	3.3	4.1	5.0	5.4	7.6	9.0	9.1	9.1	8.7	8.7
5. 0x13xD5x50	R2. 5x10xD5x50	3.7	4.7	4.7	5.6	8.1	9.3	9.5	11.6	10.7	10.7
5. 0x13xD5x75	R2. 5x10xD5x75	5.3	6.1	7.4	8.1	11.3	13.5	11.4	13.6	13.0	13.0
5. 0x13xD5x100	R2. 5x10xD5x100	6.6	7.6	8.9	9.6	13.0	15.7	11.4	13.6	13.0	13.0
5. 0x13xD6x50	R2. 5x10xD6x50	3.7	4.3	4.7	5.7	8.1	9.3	9.5	11.6	10.7	10.7
6. 0x15xD6x50	R3. 0x12xD6x50	3.1	4.3	4.7	5.7	8.1	9.3	9.5	11.6	10.7	10.7
6. 0x20xD6x75	R3. 0x12xD6x75	4.9	5.6	7.1	7.4	11.1	12.4	11.4	13.6	13.0	13.0
6. 0x30xD6x100	R3. 0x12xD6x100	6.0	7.0	8.9	9.6	13.6	15.0	13.4	16.3	15.3	15.3
6. 0x30xD6x150	R3. 0x12xD6x150	12.3	14.3	18.7	19.9	27.6	32.4	26.5	26.6	26.3	26.3
8. 0x20xD8x60	R4. 0x16xD8x60	5.9	7.6	10.8	10.0	13.9	15.2	15.3	18.4	17.6	17.6
8. 0x25xD8x75	R4. 0x16xD8x75	8.1	9.4	11.6	12.4	17.6	19.3	17.7	21.1	20.0	20.0
8. 0x35xD8x100	R4. 0x16xD8x100	9.6	11.1	14.0	15.4	21.4	23.8	22.1	26.6	25.0	25.0
8. 0x40xD8x150	R4. 0x16xD8x150	19.0	22.1	29.0	25.9	35.4	40.0	37.1	47.3	41.0	41.0
10x25xD10x75	R5. 0x20xD10x75	9.6	12.7	16.6	15.1	23.3	25.7	24.7	30.3	27.7	27.7
10x40xD10x100	R5. 0x20xD10x100	14.6	16.9	21.0	20.3	30.3	33.1	31.3	37.4	31.7	31.7
10x45xD10x150	R5. 0x20xD10x150	28.1	32.9	41.7	39.4	56.1	63.0	54.4	64.0	54.7	54.7
12x30xD12x75	R6. 0x24xD12x75	14.9	17.4	22.0	21.1	28.3	33.1	32.6	39.4	37.0	37.0
12x45xD12x100	R6. 0x24xD12x100	19.4	22.6	28.1	27.7	40.4	44.5	43.5	47.3	47.0	47.0
12x50xD12x150	R6. 0x24xD12x150	34.3	40.0	50.7	49.3	72.9	82.3	70.7	85.6	77.6	77.6
14x35xD14x80	R7. 0x28xD14x80	25.6	29.7	32.3	34.1	49.3	52.9	54.4	61.0	61.0	61.0
14x40xD14x100	R7. 0x28xD14x100	27.1	31.7	34.6	38.0	52.9	59.4	54.4	61.0	61.0	61.0
14x60xD14x150	R7. 0x28xD14x150	49.6	57.9	64.6	68.3	95.4	105.5	91.2	105.5	100.6	100.6
16x40xD16x100	R8. 0x32xD16x100	35.7	38.9	51.0	53.0	74.0	77.4	72.8	77.9	78.7	78.7
16x65xD16x150	R8. 0x32xD16x150	63.3	73.9	86.0	91.0	129.0	142.0	116.3	127.6	127.6	127.6
18x40xD18x100	R9. 0x36xD18x100	43.3	50.4	59.1	65.1	89.7	93.5	88.4	96.7	96.7	96.7
18x65xD18x150	R9. 0x36xD18x150	74.9	86.7	101.3	101.3	148.1	153.1	153.1	153.1	153.1	153.1
20x40xD20x100	R10x40xD20x100	52.7	57.6	73.1	75.9	106.7	107.9	105.5	105.5	115.7	115.7
20x65xD20x150	R10x40xD20x150	86.3	100.7	126.1	126.1	168.3	180.3	180.3	180.3	196.3	196.3


55° Desimale Punt Nie-Standard Flat-Einde Myl Snyder
55° Decimal Point Non-Standard Flat-End Milling Cutter


55° Desimale Punt Nie-Standard Ball-Einde Myl Snyder
55° Decimal Point Non-Standard Ball-End Milling Cutter

Klein Diameter Long Neck Flat-Einde Myl Snyder
Klein Diameter Long Neck Flat-End Milling Cutter

Klein Diameter Long Neck Ball-Einde Myl Snyder
Klein Diameter Long Neck Ball-End Milling Cutter


Spesifikasie RxDxL	prys
D1. 1-D3. 9xD4x50	4.3
D4. 1-D5. 9xD6x50	6.9
D6. 1-D7. 9xD8x60	12.4
D8. 1-D9. 9xD10x75	20.4
D10. 1-D11. 9xD12x75	29.0
Elke spesifikasie interval hierbo 0.1mm	
D1. 0-D3. 0xD4x75	6.0
D1. 0-D3. 0xD4x100	6.4
D1. 0-D4. 0xD6x50	6.4
D1. 0-D5. 0xD6x75	9.6
D1. 0-D5. 0xD6x100	11.9
Elke spesifikasie interval hierbo 0.5mm	
D2x2x50	4.7
D4x15xD4x50	4.0
D6x20xD6x50	6.9
D8x30xD8x60	12.4
D8x40xD8x120	20.7
D8x200	43.6
D10x30xD10x75	20.4
D10x35xD10x75	20.4
D10x50xD10x100	26.1
D10x45xD10x120	32.4
D10x200	64.3
D12x35xD12x75	27.4
D12x50xD12x100	34.7
D12x45xD12x120	42.9
D12x200	86.9
D13x14xD100	54.7
D15xD16x100	66.7
D16x50xD16x100	63.1
D16x200	154.7
D20x200	222.9

Spesifikasie	RxDxL	prys
R0. 6-R1. 9xD4x50		4. 7
Elke spesifikasie interval hierbo R0. 1mm		
R0. 5-R1. 5xD4x75		6. 9
R0. 5-R1. 5xD4x100		7. 6
R0. 5-R2. 0xD6x50		7. 6
R0. 5-R2. 5xD6x75		10. 7
R0. 5-R2. 5xD6x100		12. 6
Elke spesifikasie interval hierbo R0. 25mm		
R4x120		20. 7
R4x200		43. 6
R5x120		32. 4
R5x200		40. 3
R6x120		42. 6
R6x200		86. 9
R8x200		154. 7
R10x200		222. 9
Mikro-Diameter Flat-End Milling Snyder kan sny Staal onder 60HRC Micro-Diameter Flat-End Milling Cutter Can Steel Below 60 HRC		
		
Spesifikasie	D1xDxL	AL
0. 3xD4x50		4. 6
0. 4xD4x50		4. 6
0. 5xD4x50		4. 6
0. 6xD6x50		4. 6
0. 7xD6x50		4. 6
0. 8xD8x50		4. 6
0. 9xD8x50		4. 6




D1	L1	AL	Coatings
0.3	2/3/4	4.6	5.3
0.4	2/3/4/5/6	4.6	5.3
0.5	2/3/4/6/8	4.6	5.3
0.6	2/3/4/6/8	4.6	5.3
0.7	3/4/6/8/10	4.6	5.3
0.8	3/4/6/8/10	4.6	5.3
0.9	3/4/6/8/10	4.6	5.3
1.0	6/8/10/12/15/20	3.9	4.6
1.5	6/8/10/12/15/20	3.9	4.6
2.0	8/10/12/15/20	3.9	4.6
2.5	10/12/15/20	3.9	4.6

Mikro-diameter bal-end frees snyer kan sny
Staal onder 60HRC
Micro-Diameter Ball-End Milling Cutter Can Cut
Steel Below 60 HRC




Spesifikasie RxDxL	AL	Coatings
R0. 15xD4x50	5.3	5.4
R0. 2xD4x50	5.3	5.4
R0. 25xD4x50	5.3	5.4
R0. 3xD6x50	5.3	5.4
R0. 35xD6x50	5.3	5.4
R0. 4xD8x50	5.3	5.4
R0. 45xD8x50	5.3	5.4



D1	L1	AL	Coatings
0.3	2/3/4	4.6	5.3
0.4	2/3/4/5/6	4.6	5.3
0.5	2/3/4/6/8	4.6	5.3
0.6	2/3/4/6/8	4.6	5.3
0.7	3/4/6/8/10	4.6	5.3
0.8	3/4/6/8/10	4.6	5.3
0.9	3/4/6/8/10	4.6	5.3
1.0	6/8/10/12/15/20	4.6	5.3
1.5	6/8/10/12/15/20	4.6	5.3
2.0	8/10/12/15/20	4.6	5.3
2.5	10/12/15/20	4.6	5.3

Klein Diameter Lang Nek Ronde Nuis Flat-Einde Mael Snyder
Small Diameter Long Neck Round Nose Flat-End Milling Cutter



D1xR	L1	Coatings
D1R0. 1	4/6/8/10	10.3
D1R0. 2	4/6/8/10	10.3
D1. 5R0. 1	6/8/10/12	10.3
D1. 5R0. 2	6/8/10/12	10.3
D2R0. 1	8/10/12/16	10.3
D2R0. 2	8/10/12/16	10.3
D3R0. 2	12/16/20	19.3
D3R0. 5	12/16/20	19.3
D3R0. 5	26/30	24.6
D4R0. 2	16/20	19.3
D4R0. 5	16/20	19.3
D4R0. 5	26/30	24.6

Bogenoemde prys sluit vraag, belasting en fooi in.

Binnelandse USD Dollar Transaksieprys In China.

As jy enige vrae het, stuur asb. E-pos: eva@mzgtool.cn

<http://www.mzg.tw>

Enkel-Edge Akriel / Aluminium Freesmaaiër Single-Edge Acrylic / Aluminium Milling Cutter



dimensies D1xL1xDxL	General	poleer	AL -poleer
D2x6xD3. 175x50	2.0		
D2x8xD3. 175x50	2.0		
D2x10xD3. 175x50	2.0		
D2x12xD3. 175x50	2.0		
D2x22xD3. 175x50	2.0		
D2. 5x8xD3. 175x50	2.0		
D2. 5x15xD3. 175x50	2.0		
D2. 5x22xD3. 175x50	2.0		
D3. 175x12xD3. 175x50	2.0	4.0	4.3
D3. 175x15xD3. 175x50	2.0	4.0	4.3
D3. 175x17xD3. 175x50	2.0	4.0	4.3
D3. 175x22xD3. 175x50	3.1	4.3	4.7
D3. 175x25xD3. 175x50	3.4	4.3	4.7
D3. 175x28xD3. 175x50	3.9	5.7	6.1
D3. 175x32xD3. 175x50	4.0	6.4	6.9
D3. 175x42xD3. 175x60	7.9	9.3	9.7
D3. 175x52xD3. 175x70	10.3	12.1	12.6
D4x12xD4x50	4.7	5.4	6.1
D4x15xD4x50	4.7	5.4	6.1
D4x17xD4x50	4.7	5.4	6.1
D4x22xD4x50	4.7	5.4	6.1
D4x25xD4x50	5.3	5.7	6.4
D4x28xD4x50	6.0	7.1	7.9
D4x32xD4x50	6.4	8.6	9.3
D4x42xD4x60	10.3	12.1	12.9
D4x52xD4x70	13.3	17.1	17.9
D6x12xD6x50	9.3	10.0	11.4
D6x15xD6x50	9.3	10.0	11.4
D6x17xD6x50	9.3	10.0	11.4
D6x22xD6x50	9.3	10.0	11.4
D6x25xD6x50	9.3	10.0	11.4
D6x28xD6x50	11.1	12.1	13.6
D6x32xD6x50	11.1	12.9	14.3
D6x42xD6x60	15.7	17.7	19.3
D6x52xD6x70	20.3	22.3	25.7
D6x62xD6x80	25.0	32.1	33.6
D6x72xD6x90	31.4	39.3	40.7
D8x20xD8x50	19.7	33.3	42.6
D8x32xD8x50	19.7	33.3	42.6
D10x20xD10x50	35.3	35.7	49.3
D10x32xD10x50	35.3	35.7	49.3
D12x20xD12x50	46.9	50.0	53.6
D12x32xD12x50	46.9	50.0	53.6

3-Randige Taper Milling Snyder Vir Tungsten Staal kan staal onder 55 HRC sny

3-Edged Taper Milling Cutter For Tungsten
Staal kan staal onder 55 HRC sny




dimensies D1xα°xL1xD2xDxLx3F	prys USD
D1x0. 5°x4LxD1. 07xD4x50Lx3F	6.9
D1x1°x4LxD1. 14xD4x50Lx3F	6.9
D1x1. 5°x4LxD1. 21xD4x50Lx3F	6.9
D1x2°x4LxD1. 28xD4x50Lx3F	6.9
D1x3°x4LxD1. 42xD4x50Lx3F	6.9
D1x5°x4LxD1. 7xD4x50Lx3F	6.9
D1. 5x0. 5°x5LxD1. 59xD4x50Lx3F	6.9
D1. 5x1°x5LxD1. 67xD4x50Lx3F	6.9
D1. 5x1. 5°x5LxD1. 76xD4x50Lx3F	6.9
D1. 5x2°x5LxD1. 85xD4x50Lx3F	6.9
D1. 5x3°x5LxD1. 02xD4x50Lx3F	6.9
D1. 5x5°x5LxD1. 37xD4x50Lx3F	6.9
D2x0. 5°x6LxD2. 1xD4x50Lx3F	6.9
D2x1°x6LxD2. 21xD4x50Lx3F	6.9
D2x1. 5°x6LxD2. 31xD4x50Lx3F	6.9
D2x2°x6LxD2. 41xD4x50Lx3F	6.9
D2x3°x6LxD2. 62xD4x50Lx3F	6.9
D2x5°x6LxD2. 05xD4x50Lx3F	6.9
D3x0. 5°x10LxD3. 17xD4x50Lx3F	6.9
D3x1°x10LxD3. 35xD4x50Lx3F	6.9
D3x1. 5°x10LxD3. 52xD4x50Lx3F	6.9
D3x2°x10LxD3. 69xD4x50Lx3F	6.9
D3x3°x9. 5LxD4x50Lx3F	6.9
D3x5°x10LxD4. 75xD6x50Lx3F	11.9
D3x10°x10LxD6. 53xD8x60Lx3F	18.1
D3x15°x13. 06LxD10x10x75Lx3F	29.0

Tungsten Steel Inner R Milling Cutter
Kan staal onder 55HRC sny
Tungsten Steel Inner R Milling Cutter
Can Cut Steel Below 55 HRC



dimensies D1RxDxL	prys USD
D4R0. 5xD4x50	6.7
D4R0. 75xD4x50	6.7
D4R1. 0xD4x50	6.7
D6R1. 0xD6x50	11.9
D6R1. 5xD6x50	11.9
D6R2. 0xD6x50	20.0
D8R2. 0xD8x50	20.0
D8R2. 5xD8x50	20.0
D8R3. 0xD8x50	29.1
D10R4. 0xD10x60	40.1
D12R5. 0xD12x60	

Tungsten Steel Dovetail Groove Milling
Snyder kan staal onder 60HRC sny
Tungsten Steel Dovetail Groove Milling
Cutter Can Cut Steel Below 60 HRC



dimensies D1xα°xL1xD2xDxL	prys USD
D4x90°x1. 5x6xD4x50	6.4
D6x90°x2. 5x8xD6x50	10.4
D8x90°x3x6xD8x50	16.9
D10x90°x4x10xD10x60	24.6
D12x90°x5x12xD12x60	31.9

Spesiale Maas Snyder vir Tungsten
Staal Inverted Cone Die Frame
Kan staal onder 55HRC sny


Special Milling Cutter for Tungsten
Steel Inverted Cone Die Frame
Can Cut Steel Below 55 HRC



dimensies D1xL1xDxL	prys USD
D4x15xD4x50	4.0
D6x30xD6x100	11.1
D8x30xD8x60	12.1
D10x30xD10x75	20.4
D10x45xD10x100	26.1
D12x35xD12x75	27.1
D12x50xD12x100	34.7
D16x50xD16x100	57.9

Bubble Kop Tungsten Staal Vastpunt
Boor Bubble Gebruik Van Vastpunt En
Chamfer kan staal onder 55HRC sny

Double Head Tungsten Steel Fixed-point
Drill Dual Use Of Fixed Point And
Chamfer Can Cut Steel Below 58 HRC



dimensies DxL	AL	Coatings
D3x100L-DB	7.4	8.1
D4x100L-DB	7.4	8.1
D5x100L-DB	14.3	15.0
D6x100L-DB	14.3	15.0

Tungsten Steel T-Groove Side Milling Snyder kan staal onder 55HRC sny

Tungsten Steel T-Groove Side Milling
Cutter Can Cut Steel Below 55 HRC



dimensies D1RxDxL	prys USD
D4x0. 5HxD1. 5xD6x50	6.4
D4x1HxD1. 5xD6x50	6.4
D4x1. 5HxD1. 5xD6x50	6.4
D4x2HxD1. 5xD6x50	6.4
D4x3HxD1. 5xD6x50	6.4
D6x0. 5HxD2. 5xD8x50	10.4
D6x1HxD2. 5xD8x50	10.4
D6x1. 5HxD2. 5xD8x50	10.4
D6x2HxD2. 5xD8x50	10.4
D6x3HxD2. 5xD8x50	10.4
D8x0. 5HxD3. 5xD8x60	16.9
D8x1HxD3. 5xD8x60	16.9
D8x1. 5HxD3. 5xD8x60	16.9
D8x2HxD3. 5xD8x60	16.9
D8x3HxD3. 5xD8x60	16.9
D10x0. 5HxD4xD10x75	24.6
D10x1HxD4xD10x75	24.6
D10x1. 5HxD4xD10x75	24.6
D10x2HxD4xD10x75	24.6
D10x3HxD4xD10x75	24.6
D12x0. 5HxD5xD12x75	31.9
D12x1HxD5xD12x75	31.9
D12x1. 5HxD5xD12x75	31.9
D12x2HxD5xD12x75	31.9
D12x3HxD5xD12x75	31.9

Tungsten Staal Reguit Groove
Chamfer Snyder kan staal sny
Onder 58HRC (60°/90°/120°)

Tungsten Steel Straight Groove
Chamfer Cutter Can Cut Steel
Below 58 HRC(60°/90°/120°)



dimensies DxL	AL	Coatings
D1xD4x50L	4.6	5.0
D2xD4x50L	4.6	5.0
D3x50L	4.6	5.0
D4x50L	4.6	5.0
D5x50L	8.6	9.3
D6x50L	8.6	9.3
D8x60L	13.6	14.3
D10x75L	20.0	21.1
D12x75L	26.9	27.9

Tungsten Staal Vastpunt Drill Dual
Gebruik van vaste punt en chamfer kan sny
Staal onder 58HRC


Tungsten Steel Fixed-point Drill Dual
Use Of Fixed Point And Chamfer Can Cut
Steel Below 58 HRC



dimensies DxL	AL	Coatings
D1xD4x50L	3.3	3.9
D1. 5xD4x50L	3.3	3.9
D2xD4x50L	3.3	3.9
D3xD4x50L	3.3	3.9
D3x100L	6.1	6.9
D4x50L	3.3	3.9
D4x100L	6.1	6.9
D5x50L	6.0	6.4
D5x100L	12.1	12.9
D6x50L	6.0	6.4
D6x100L	12.1	12.9
D8x60L	11.1	12.1
D8x100L	19.0	20.0
D10x75L	18.9	19.3
D10x100L	27.1	28.3
D12x75L	25.4	27.1
D12x100L	37.9	38.9
D14x100L	51.4	52.6
D16x100L	64.0	65.7
D20x100L	94.6	96.9

Spiral-Edged Tungsten Steel Reamer Kan staal onder 55HRC sny

Spiral-Edged Tungsten Steel Reamer
Can Cut Steel Below 55 HRC



dimensies D1xL1xDxLxT	prys USD
D3x50xD3x100Lx4T	7.6
D4x50xD4x100Lx4T	8.1
D5x50xD5x100Lx6T	11.1
D6x50xD6x100Lx6T	13.3
D8x50xD8x100Lx6T	21.1
D10x50xD10x100Lx6T	30.7
D12x50xD12x100Lx6T	40.7

Reguit-Edged Tungsten Steel Reamer Kan staal onder 55HRC sny

Straight-Edged Tungsten Steel Reamer
Can Cut Steel Below 55 HRC



dimensies D1xL1xDxLxT	prys USD
D3x50xD3x100Lx4T	6.0
D4x50xD4x100Lx4T	6.4
D5x50xD5x100Lx6T	8.9
D6x50xD6x100Lx6T	9.6
D8x50xD8x100Lx6T	14.6
D10x50xD10x100Lx6T	22.1
D12x50xD12x100Lx6T	30.0

Tungsten Steel Drills

Tungsten Steel Drills



dimensies	prys USD
D1. 0-D1. 5	1.9
D1. 6-D2. 0	2.4
D2. 1-D2. 5	2.6
D2. 6-D3. 0	3.3
D3. 1-D3. 5	4.0
D3. 6-D4. 0	4.7
D4. 1-D4. 5	5.4
D4. 6-D5. 0	6.9
D5. 1-D5. 5	7.9
D5. 6-D6. 0	9.6
D6. 1-D6. 5	11.1
D6. 6-D7. 0	12.9
D7. 1-D7. 5	16.9
D7. 6-D8. 0	18.9
D8. 1-D8. 5	22.4
D8. 6-D9. 0	24.7
D9. 1-D9. 5	28.3
D9. 6-D10. 0	30.7
D10. 1-D10. 5	35.7
D10. 6-D11. 0	37.4
D11. 1-D11. 5	46.0
D11. 6-D12. 0	50.0

Tungsten Steel Bar

Tungsten Steel Bar



dimensies DxL	55° USD	60° USD
D3x100L	2.4	3.6
D4x100L	3.9	6.0
D5x100L	6.1	7.4
D6x100L	7.4	8.6
D8x100L	14.3	21.1
D10x100L	21.4	32.4
D12x100L	31.1	46.9

Ekstrusie Skroef Tap

Extrusion Screw Tap



Draad x Pitch x Lengte (/ Omgekeerde Tande)	presisie	vorm	wit	Tin
M0. 5x0. 125	RH2	B	11.0	11.9
M0. 6x0. 15	RH2	B	9.3	10.0
M0. 7x0. 175	RH3	B	9.3	10.0
M0. 8x0. 2	RH4	B	6.7	7.4
M0. 9x0. 25	RH4	B	6.7	7.4
M1. 0x0. 25	RH4	P	5.3	6.0
	RH4	B	5.3	6.0
	RH5	P	5.3	6.0
	RH5	B	5.3	6.0
M1. 1x0. 25	RH4	P	7.1	7.9
	RH4	B	7.1	7.9
M1. 2x0. 25	RH4	P	5.3	6.0
	RH4	B	5.3	6.0
	RH5	P	5.3	6.0
	RH5	B	5.3	6.0
M1. 4x0. 2	RH4	P	7.1	7.9
M1. 4x0. 3	RH4	P	5.3	6.0
	RH4	B	5.3	6.0
	RH5	P	5.3	6.0
	RH5	B	5.3	6.0
M1. 4x0. 3-80L			9.7	10.4
M1. 5x0. 3	RH4	P	7.1	7.9
	RH4	B	7.1	7.9
M1. 6x0. 2	RH4	P	7.1	7.9
	RH4	B	7.1	7.9
M1. 6x0. 35	RH4	P	5.3	6.0
	RH4	B	5.3	6.0
	RH5	P	5.3	6.0
	RH5	B	5.3	6.0
M1. 6x0. 35-80L			9.7	10.4
M1. 7x0. 2	RH4	B	7.1	7.9
M1. 7x0. 35	RH4	P	5.3	6.0
	RH4	B	5.3	6.0
	RH5	P	5.3	6.0
	RH5	B	5.3	6.0
M1. 8x0. 2	RH4	B	7.1	7.9
M1. 8x0. 35	RH4	P	5.7	6.7
	RH4	B	5.7	6.7
M2. 0x0. 25	RH4	P	7.1	7.9
	RH4	B	7.1	7.9
M2. 0x0. 4	RH4	P	4.7	5.4
	RH4	B	4.7	5.4
	RH5	P	4.7	5.4
	RH5	B	4.7	5.4
	RH6	P	4.7	5.4
	RH6	B	4.7	5.4
	RH7	P	4.7	5.4
	RH7	B	4.7	5.4
	RH8	B	4.7	5.4
M2. 0x0. 4-80L			8.9	9.7
M2. 0x0. 4-100L			9.7	10.4
M2. 0x0. 4L Omgekeerde Tande	RH6	B	7.1	7.9
M2. 2x0. 45	RH4	P	5.3	6.0
	RH4	B	5.3	6.0
M2. 3x0. 4	RH5	P	4.7	5.4
	RH5	B	4.7	5.4
M2. 3x0. 4L Omgekeerde Tande	RH6	B	7.1	7.9
M2. 5x0. 25	RH6	B	7.1	7.9
M2. 5x0. 35	RH4	P	4.7	5.4
M2. 5x0. 45	RH4	P	4.7	5.4
	RH5	P	4.7	5.4
	RH5	B	4.7	5.4
	RH6	P	4.7	5.4
	RH6	B	4.7	5.4
	RH7	P	4.7	5.4
	RH7	B	4.7	5.4
	RH8	B	4.7	5.4
M2. 5x0. 45-80L			8.9	9.7
M2. 5x0. 45-100L			9.7	10.4
M2. 5x0. 45L Omgekeerde Tande	RH6	B	7.1	7.9
M2. 6x0. 45	RH5	P	4.7	5.4
	RH5	B	4.7	5.4
	RH6	P	4.7	5.4
	RH6	B	4.7	5.4
	RH7	B	4.7	5.4
M2. 6x0. 45-100L			9.7	10.4

Draad x Pitch x Lengte (/ Omgekeerde Tande)	presisie	vorm	wit	Tin
M3. 0x0. 35	RH6	B	7.1	7.9
M3. 0x0. 5	RH4	P	4.7	5.4
	RH4	B	4.7	5.4
	RH5	P	4.7	5.4
	RH5	B	4.7	5.4
	RH6	P	4.7	5.4
	RH6	B	4.7	5.4
	RH7	P	4.7	5.4
	RH7	B	4.7	5.4
	RH8	B	4.7	5.4
	RH9	B	4.7	5.4
M3. 0x0. 5-80L			8.9	
M3. 0x0. 5-100L			9.7	10.4
M3. 0x0. 5-150L			17.6	18.3
M3. 0x0. 5L Omgekeerde Tande	RH6	B	6.7	7.4
M3. 5x0. 6-100L			9.7	10.4
M3. 5x0. 6L Omgekeerde Tande	RH6	B	6.7	7.4
M4. 0x0. 35	RH6	B	7.1	7.9
M4. 0x0. 5	RH6	B	7.1	7.9
M4. 0x0. 7	RH5	P	4.7	5.4
	RH5	B	4.7	5.4
	RH6	P	4.7	5.4
	RH6	B	4.7	5.4
	RH7	P	4.7	5.4
	RH7	B	4.7	5.4
	RH8	P	4.7	5.4
	RH8	B	4.7	5.4
	RH9	B	4.7	5.4
M4. 0x0. 7-80L			8.9	9.7
M4. 0x0. 7-100L			9.7	10.4
M4. 0x0. 7-150L			17.6	18.3
M4. 0x0. 7L Omgekeerde Tande	RH6	B	6.7	7.4
M4. 5x0. 5	RH7	B	7.4	8.3
M4. 5x0. 75	RH7	B	5.7	6.9
M5. 0x0. 35	RH6	B	7.4	8.3
M5. 0x0. 5	RH6	P	5.3	6.1
M5. 0x0. 8	RH6	P	5.3	6.1
	RH7	P	5.3	6.1
	RH7	B	5.3	6.1
	RH8	B	5.3	6.1
M5. 0x0. 8-80L			9.3	10.3
M5. 0x0. 8-100L			10.0	11.0
M5. 0x0. 8-150L			18.3	19.3
M5. 0x0. 8L Omgekeerde Tande	RH6	B	7.1	8.1
M6. 0x0. 5	RH7	B	7.4	8.3
M6. 0x0. 75	RH7	B	7.4	8.3
M6. 0x1. 0	RH6	P	5.3	6.1
	RH6	B	5.3	6.1
	RH7	P	5.3	6.1
	RH7	B	5.3	6.1
	RH8	B	5.3	6.1
M6. 0x1. 0-80L			9.3	10.3
M6. 0x1. 0-100L			10.0	11.0
M6. 0x1. 0-150L			18.3	19.3
M6. 0x1. 0L Omgekeerde Tande	RH6	B	7.1	8.1
M7. 0x0. 5	RH7	B	9.3	10.4
M7. 0x0. 75	RH7	B	9.3	10.4
M7. 0x1. 0	RH7	B	9.3	10.4
M8. 0x0. 5	RH7	B	9.3	10.4
M8. 0x0. 75	RH7	B	9.3	10.4
M8. 0x1. 0	RH7	B	9.3	10.4
M8. 0x1. 25	RH7	B	9.3	10.4
	RH9	B	9.3	10.4
M8. 0x1. 25-100L			13.1	14.6
M8. 0x1. 25-150L			18.9	20.3
M8. 0x1. 25L Omgekeerde Tande	RH7	B	11.0	12.4
M9. 0x0. 5	RH7	B	10.4	12.1
M9. 0x0. 75	RH7	B	10.4	12.1
M9. 0x1. 0	RH7	B	10.4	12.1
M9. 0x1. 25	RH7	B	10.4	12.1
M10x0. 5	RH7	B	10.4	12.1
M10x0. 75	RH7	B	10.4	12.1
M10x1. 0	RH7	B	10.4	12.1
M10x1. 25	RH7	B	10.4	12.1
M10x1. 5	RH7	B	10.4	12.1
	RH9	B	10.4	12.1
M10x1. 5-100L			15.3	16.7
M10x1. 5-150L			20.3	21.7
M10x1. 5L Omgekeerde Tande	RH7	B	12.6	14.0
M11x1. 0	RH7	B	11.9	13.9
M12x0. 5	RH7	B	11.9	13.9
M12x0. 75	RH7	B	11.9	13.9
M12x1. 0	RH7	B	11.9	13.9
M12x1. 25	RH7	B	11.9	13.9
M12x1. 5	RH7	B	11.9	13.9
M12x1. 75	RH7	B	11.9	13.9
	RH8	B	11.9	13.9
M12x1. 75-100L			19.7	21.7
M12x1. 75-150L			22.9	25.0
M12x1. 75L Omgekeerde Tande	RH7	B	14.0	16.1

Draad x Pitch x Lengte (/ Omgekeerde Tande)	presisie	vorm	wit	Tin
M14x1. 0	RH8	B	26.1	28.9
M14x1. 25	RH8	B	26.1	28.9
M14x1. 5	RH8	B	26.1	28.9
M14x2. 0	RH8	B	26.1	28.9
M16x1. 0	RH8	B	34.0	37.1
M16x1. 25	RH8	B	34.0	37.1
M16x1. 5	RH8	B	34.0	37.1
M16x2. 0	RH8	B	34.0	37.1
UNF0-80	RH4	P	5.7	6.1
	RH4	B	5.7	6.1
UNC1-64	RH4	B	5.7	6.1
UNF1-72	RH4	B	7.4	7.9
UNC2-56	RH4	P	5.7	6.1
	RH4	B	5.7	6.1
	RH5	P	5.7	6.1
	RH5	B	5.7	6.1
UNC2-56-100L			10.0	10.7
UNF2-64	RH5	B	6.7	7.9
UNC3-48	RH5	B	5.7	6.1
UNF3-56	RH5	B	7.4	7.9
UNC4-40	RH5	P	4.7	5.4
	RH5	B	4.7	5.4
	RH6	P	4.7	5.4
	RH6	B	4.7	5.4
	RH7	B	4.7	5.4
UNC4-40-100L			10.0	10.7
UNF4-48	RH5	P	7.4	7.9
	RH5	B	7.4	7.9
UNC5-40	RH5	P	5.3	6.0
	RH5	B	5.3	6.0
UNC5-40-100L			10.0	10.7
UNF5-44	RH6	B	7.4	7.9
UNC6-32	RH5	P	4.7	5.4
	RH5	B	4.7	5.4
	RH6	P	4.7	5.4
	RH6	B	4.7	5.4
	RH7	B	4.7	5.4
UNC6-32-100L			10.0	10.7
UNF6-40	RH6	P	6.7	7.4
	RH6	B	6.7	7.4
UNC8-32	RH6	P	5.0	5.7
	RH6	B	5.0	5.7
	RH7	P	5.0	5.7
	RH7	B	5.0	5.7
UNC8-32-100L			10.0	10.7
UNF8-36	RH7	B	7.4	8.1
UNS8-40	RH6	B	7.4	8.1
UNC10-24	RH6	P	5.3	6.0
	RH7	B	5.3	6.0
UNC10-24-100L			10.0	11.0
UNC10-24L Omgekeerde Tande	RH7	B	7.1	8.1
UNF10-32	RH7	P	6.7	7.4
	RH7	B	6.7	7.4
UNF10-32-100L			10.0	11.0
UNF10-32L Omgekeerde Tande	RH7	B	7.1	8.1
UNF12-24	RH7	B	5.4	6.7
UNF12-28	RH7	B	6.7	7.6
UNS12-32	RH7	B	6.7	7.6
UNC1/4-20	RH7	P	5.4	6.7
	RH7	B	5.4	6.7
UNC1/4-20-100L			10.0	11.0
UNC1/4-20L Omgekeerde Tande	RH7	B	7.1	8.1
UNF1/4-28	RH7	P	6.7	7.6
	RH7	B	6.7	7.6
UNF1/4-28L Omgekeerde Tande	RH7	B	7.1	8.1
UNEF1/4-32	RH7	B	6.7	7.6
UNS1/4-36	RH7	B	6.7	7.6
UNC5/16-18	RH7	B	9.3	10.4
UNC5/16-18L Omgekeerde Tande	RH7	B	11.1	12.6
UNC5/16-18-100L			13.6	15.0
UNF5/16-24	RH7	B	10.0	11.1
UNC3/8-16	RH7	B	11.0	13.1
UNC3/8-16-100L			15.3	16.7
UNC3/8-16L Omgekeerde Tande	RH7	B	13.1	14.7
UNC3/8-24	RH7	B	11.9	13.9
UNC7/16-14	RH7	B	14.6	16.4
UNF7/16-20	RH7	B	15.7	17.9
UNC1/2-12	RH7	B	17.1	19.7
UNF1/2-20	RH7	B	17.1	19.7
W1/8-40	RH6	P	5.3	6.0
	RH6	B	5.3	6.0
W5/32-32	RH7	B	5.3	6.0
W3/16-24	RH7	B	5.3	6.0
W1/4-20	RH7	B	5.4	6.7
W5/16-18	RH7	B	9.3	10.4
W3/8-16	RH7	B	11.9	13.9
W7/16-14	RH7	B	14.6	16.4
W1/2-12	RH7	B	17.1	19.7

Bogenoemde prys sluit vraag, belasting en fooi in.

Binnelandse USD Dollar Transaksieprys In China.

As jy enige vrae het, stuur asb. E-pos: eva@mzgtool.cn

<http://www.mzg.tw>

Apex Tap

Apex Tap



wit

Tin

Draad x Pitch x Lengte (/ Omgekeerde Tande)	presisie	vorm	wit	Tin
M1. 0x0. 25	P1		5. 3	6. 0
M1. 0x0. 25 Carbide	P2			27. 6
M1. 2x0. 25	P1		5. 3	6. 0
M1. 2x0. 25 Carbide	P2			25. 0
M1. 4x0. 2	P1		6. 7	7. 4
M1. 4x0. 3	P1		5. 3	6. 0
	P2		5. 3	6. 0
M1. 4x0. 3-80L			9. 3	
M1. 4x0. 3 Carbide	P2			22. 4
M1. 5x0. 3	P2		5. 7	6. 7
M1. 6x0. 2	P2		6. 7	7. 4
M1. 6x0. 35	P2		5. 3	6. 0
M1. 6x0. 35-80L			9. 3	
M1. 6x0. 35 Carbide	P2		0. 0	21. 0
M1. 7x0. 35	P2		5. 3	6. 0
M1. 7x0. 35 Carbide	P2			21. 0
M1. 8x0. 2	P2		6. 7	7. 4
M1. 8x0. 35	P2		5. 7	6. 7
M2. 0x0. 25	P2		6. 7	7. 4
M2. 0x0. 4	P2		4. 7	5. 4
	P3		4. 7	5. 4
	P4		4. 7	5. 4
M2. 0x0. 4-80L			8. 3	
M2. 0x0. 4-100L			9. 3	
M2. 0x0. 4 Carbide	P3			19. 7
M2. 2x0. 25	P2		6. 7	7. 4
M2. 2x0. 45	P2		4. 7	5. 4
M2. 3x0. 4	P2		4. 7	5. 4
M2. 5x0. 35	P2		6. 7	7. 4
M2. 5x0. 45	P2		4. 7	5. 4
	P3		4. 7	5. 4
	P4		4. 7	5. 4
M2. 5x0. 45-80L			8. 3	
M2. 5x0. 45-100L			9. 3	
M2. 5x0. 45 Carbide	P3			19. 7
M2. 6x0. 35	P2		6. 7	7. 4
M2. 6x0. 45	P2		4. 7	5. 4
M2. 6x0. 45-100L			9. 3	
M3. 0x0. 35	P2		4. 7	5. 4
M3. 0x0. 5	P2		4. 0	4. 7
	P3		4. 0	4. 7
	P4		4. 0	4. 7
	+0. 1		4. 7	5. 4
M3. 0x0. 5-80L			8. 3	
M3. 0x0. 5-100L			9. 3	
M3. 0x0. 5-150L			17. 1	
M3. 0x0. 5 Carbide	P3			19. 7
M3. 5x0. 6-100L			9. 3	
M4. 0x0. 35	P2		6. 7	7. 4
M4. 0x0. 5	P2		4. 7	5. 4
M4. 0x0. 7	P2		4. 0	4. 7
	P3		4. 0	4. 7
	P4		4. 0	4. 7
	+0. 1		4. 7	5. 4
M4. 0x0. 7-80L			8. 3	
M4. 0x0. 7-100L			9. 3	
M4. 0x0. 7-150L			17. 1	
M4. 0x0. 7 Carbide	P3			19. 7
M5. 0x0. 5	P2		4. 7	5. 7
M5. 0x0. 8	P2		4. 0	5. 0
	P3		4. 0	5. 0
	P4		4. 0	5. 0
	+0. 1		4. 7	5. 7
M5. 0x0. 8-80L			8. 6	
M5. 0x0. 8-100L			9. 6	
M5. 0x0. 8-150L			17. 9	
M5. 0x0. 8 Carbide	P3			21. 0
M6. 0x0. 5	P2		4. 7	5. 7
M6. 0x0. 75	P2		4. 7	5. 7
M6. 0x1. 0	P2		4. 0	5. 0
	P3		4. 0	5. 0
	P4		4. 0	5. 0
	+0. 1		4. 7	5. 7
M6. 0x1. 0-80L			8. 6	
M6. 0x1. 0-100L			9. 6	
M6. 0x1. 0-150L			17. 9	
M6. 0x1. 0 Carbide	P3			22. 4

Draad x Pitch x Lengte (/ Omgekeerde Tande)	presisie	vorm	wit	Tin
M7. 0x0. 5	P2		6. 7	7. 9
M7. 0x0. 75	P2		6. 7	7. 9
M7. 0x1. 0	P2		6. 0	7. 4
M8. 0x0. 5	P2		6. 7	7. 9
M8. 0x0. 75	P3		6. 7	7. 9
M8. 0x1. 0	P3		6. 7	7. 9
M8. 0x1. 25	P3		6. 0	7. 4
	P4		6. 0	7. 4
M8. 0x1. 25-100L			12. 6	
M8. 0x1. 25-150L			18. 3	
M8. 0x1. 25 Carbide	P4			43. 3
M9. 0x0. 5	P2		8. 3	10
M9. 0x0. 75	P3		8. 3	10
M9. 0x1. 0	P3		8. 3	10
M9. 0x1. 25	P3		7. 9	9. 6
M10x0. 5	P2		8. 3	10
M10x0. 75	P3		8. 3	10
M10x1. 0	P3		8. 3	10
M10x1. 25	P3		8. 3	10
M10x1. 5	P4		7. 9	9. 6
			7. 9	9. 6
M10x1. 5-100L			14. 6	
M10x1. 5-150L			19. 7	
M10x1. 5 Carbide	P4			51. 1
M11x1. 0	P3		10. 4	12. 6
M12x0. 5	P2		11. 0	13. 1
M12x0. 75	P3		11. 0	13. 1
M12x1. 0	P4		11. 0	13. 1
M12x1. 25	P4		11. 0	13. 1
M12x1. 5	P3		11. 0	13. 1
M12x1. 75	P4		10. 4	12. 6
M12x1. 75-100L			18. 9	
M12x1. 75-150L			22. 4	
M12x1. 75 Carbide	P4			62. 9
M14x1. 0	P3		17. 1	19. 7
M14x1. 25	P3		17. 1	19. 7
M14x1. 5	P3		17. 1	19. 7
M14x2. 0	P2		15. 7	18. 3
M16x1. 0	P3		19. 7	22. 4
M16x1. 25	P3		19. 7	22. 4
M16x1. 5	P3		19. 7	22. 4
M16x2. 0	P4		18. 3	21
UNF0-80	P1		5. 3	6
UNC1-64	P1		5. 3	6
UNF1-72	P1		6. 7	7. 4
UNC2-56	P2		5. 3	6
	P4		5. 3	6
UNC2-56-100L			9. 6	
UNF2-64	P2		6. 7	7. 4
UNC3-48	P2		5. 3	6
UNF3-56	P2		6. 7	7. 4
UNC4-40	P2		4. 7	5. 4
	P3		4. 7	5. 4
	P4		4. 7	5. 4
UNC4-40-100L			9. 6	
UNF4-48	P2		6. 7	7. 4
UNC5-40	P2		4. 7	5. 4
UNC5-40-100L			9. 6	
UNC6-32	P2		4. 7	5. 4
	P3		4. 7	5. 4
	P4		4. 7	5. 4
UNC6-32-100L			9. 6	
UNF6-40	P2		6. 7	7. 4
UNC8-32	P2		4. 7	5. 4
	P3		4. 7	5. 4
	P4		4. 7	5. 4
UNC8-32-100L			9. 6	
UNF8-36	P2		6. 7	7. 4
UNC10-24	P2		4. 7	5. 7
UNC10-24-100L			9. 6	
UNF10-32	P2		4. 7	5. 7
UNF10-32-100L			9. 6	
UNC12-24	P2		4. 7	5. 7
UNF12-28	P2		6. 7	7. 6
UNC1/4-20	P2		4. 7	5. 7
	P3		4. 7	5. 7
	P4		4. 7	5. 7
UNC1/4-20-100L			9. 6	
UNC1/4-28	P2		6. 7	7. 6
UNS1/4-32	P2		6. 7	7. 6
UNEF1/4-36	P2		6. 7	7. 6
UNC5/16-18	P3		6. 0	7. 4
UNC5/16-18-100L			13. 1	
UNF5/16-24	P2		7. 4	8. 6
UNC3/8-16	P3		7. 9	9. 6
UNC3/8-16-100L			14. 7	
UNF3/8-24	P2		9. 3	10. 7
UNC7/16-14	P3		11. 9	13. 9
UNF7/16-20	P3		12. 6	14. 7

Draad x Pitch x Lengte (/ Omgekeerde Tande)	presisie	vorm	wit	Tin
UNC1/2-12	P3		13. 1	15. 3
UNF1/2-20	P3		14. 6	16. 4
W1/8-40	P1		4. 7	5. 4
W5/32-32	P2		4. 7	5. 4
W3/16-24	P2		4. 7	5. 4
W7/32-24	P2		4. 7	5. 7
W1/4-20	P2		4. 7	5. 7
W5/16-18	P2		6. 0	7. 4
W3/8-16	P2		7. 9	9. 6
W7/16-14	P3		11. 9	13. 9
W1/2-12	P2		13. 1	15. 3
PS1/8-28 Carbide	P4			56. 4
PS1/4-19 Carbide	P4			91. 7
PT1/8-28 Carbide	P4			62. 9
PT1/4-19 Carbide	P4			95. 7
NPS1/8-27 Carbide	P4			56. 4
NPS1/4-18 Carbide	P4			91. 7
NPT1/8-27 Carbide	P4			62. 9
NPT1/4-18 Carbide	P4			95. 7

Spiraal Gekruiste Kraan
Spiral Grooved Tap



wit



Tin

Draad x Pitch x Lengte (/ Omgekeerde Tande)	presisie	wit	T in
M1. 0x0. 25	P1	5.3	6.0
	P2	5.3	6.0
	P3	5.3	6.0
	P4	5.3	6.0
M1. 2x0. 25	P1	5.3	6.0
	P2	5.3	6.0
	P3	5.3	6.0
	P4	5.3	6.0
M1. 4x0. 2 M1. 4x0. 3	P1	6.7	7.4
	P1	5.3	6.0
	P2	5.3	6.0
	P3	5.3	6.0
M1. 5x0. 3	P4	5.3	6.0
	P1	6.7	7.4
	P1	6.7	7.4
	P1	6.7	7.4
M1. 6x0. 2 M1. 6x0. 35	P1	5.3	6.0
	P2	5.3	6.0
	P3	5.3	6.0
	P4	5.3	6.0
M1. 6x0. 35-HT skede	1B	5.3	6.9
	P1	6.7	7.4
M1. 7x0. 2 M1. 7x0. 35	P1	5.3	6.0
	P2	5.3	6.0
	P3	5.3	6.0
	P4	5.3	6.0
M1. 8x0. 2 M1. 8x0. 35	P1	6.7	7.4
	P1	5.7	6.7
	P1	6.7	7.4
	P1	5.3	6.0
M2. 0x0. 25 M2. 0x0. 4	P2	4.7	5.4
	P1	4.7	5.4
	P2	4.7	5.4
	P3	4.7	5.4
M2. 0x0. 4-100L M2. 0x0. 4-AL M2. 0x0. 4-HT skede	P4	4.7	5.4
	9.3		
	P1	4.7	4.7
	1B	5.4	6.7
M2. 2x0. 25 M2. 2x0. 45	P1	5.7	6.7
	P1	6.7	7.4
	P1	4.7	5.4
	P1	4.7	5.4
M2. 3x0. 4 M2. 3x0. 4L Omgekeerde Tande	P1	6.7	7.4
	P1	4.7	5.4
	P1	5.7	6.7
	P1	6.7	7.4
M2. 5x0. 35 M2. 5x0. 45	P1	5.3	6.0
	+0. 1	4.7	5.4
	P1	4.7	5.4
	P2	4.7	5.4
M2. 5x0. 45-100L M2. 5x0. 45-AL M2. 5x0. 45-HT skede	P4	4.7	5.4
	9.3		
	P1	4.7	4.7
	1B	5.4	6.7
M2. 5x0. 45L Omgekeerde Tande	P1	5.7	6.7
	P1	6.7	7.4
	P1	4.7	5.4
	P2	4.7	5.4
M2. 6x0. 35 M2. 6x0. 45	P3	4.7	5.4
	P4	4.7	5.4
	P1	6.7	7.4
	P1	4.7	5.4
M2. 6x0. 45-100L M2. 6x0. 45L Omgekeerde Tande	P2	4.7	5.4
	P3	4.7	5.4
	P4	4.7	5.4
	P1	5.7	6.7
M3. 0x0. 35	P1	4.7	5.4
	P2	4.7	5.4
	P3	4.7	5.4
	P4	4.7	5.4
M3. 0x0. 35L Omgekeerde Tande	P2	5.7	6.7
	P1	4.7	5.4
	+0. 1	4.7	5.4
	P1	4	4.7
M3. 0x0. 5 M3. 0x0. 5-AL	P2	4	4.7
	P1	4	4.7
	P3	4	4.7
	P4	4	4.7
M3. 0x0. 5-100L M3. 0x0. 5-150L M3. 0x0. 5-AL	9.3		
	17.1		
	P2	4	4.0
	1B	4.7	6.1
M3. 0x0. 5-HT skede M3. 0x0. 5L Omgekeerde Tande	P2	4.7	5.4
	P2	4.7	5.4
	P2	4.7	5.4
	P2	4.7	5.4
M3. 5x0. 6-100L	9.3		
	P2	5.7	6.7
M4. 0x0. 35 M4. 0x0. 5	P2	4.7	5.4
	P2	4.7	5.4
	P3	4.7	5.4
	P4	4.7	5.4
M4. 0x0. 5L Omgekeerde Tande	P2	4.7	5.4
	P2	5.7	6.7

Draad x Pitch x Lengte (/ Omgekeerde Tande)	presisie	wit	T in
M4. 0x0. 7	+0. 1 P2 P3 P4	4. 7 4 4 4	5. 4 4. 7 4. 7 4. 7
M4. 0x0. 7-100L		9. 3	
M4. 0x0. 7-150L		17. 1	
M4. 0x0. 7-AL			
M4. 0x0. 7-HT <i>skede</i>	1B	4. 7	6. 1
M4. 0x0. 7LOmgekeerde Tande	P2	4. 7	5. 7
M5. 0x0. 5	P2 P3 P4	4. 7 4. 7 4. 7	5. 4 5. 4 5. 4
M5. 0x0. 5LOmgekeerde Tande	P2	5. 7	6. 9
M5. 0x0. 8	+0. 1 P2 P3 P4	4. 7 4 4 4	5. 7 4. 7 4. 7 4. 7
M5. 0x0. 8-100L		9. 6	
M5. 0x0. 8-150L		17. 9	
M5. 0x0. 8-AL	P2	4	4
M5. 0x0. 8-HT <i>skede</i>	1B	4. 7	6. 1
M5. 0x0. 8LOmgekeerde Tande	P2	4. 7	5. 7
M6. 0x0. 5			
	P2 P3 P4	4. 7 4. 7 4. 7	5. 4 5. 7 5. 7
M6. 0x0. 5LOmgekeerde Tande	P2	5. 7	6. 9
M6. 0x0. 75	P2 P3 P4	4. 7 4. 7 4. 7	5. 7 5. 7 5. 7
M6. 0x0. 75LOmgekeerde Tande	P2	5. 7	6. 9
M6. 0x1. 0	+0. 1 P2 P3 P4	4. 7 4 4 4	5 5 5 5
M6. 0x1. 0-100L		9. 6	
M6. 0x1. 0-150L		17. 9	
M6. 0x1. 0-AL	P2	4	4
M6. 0x1. 0-HT <i>skede</i>	1B	4. 7	6. 1
M6. 0x1. 0LOmgekeerde Tande	P2	4. 7	5. 7
M7. 0x0. 5	P2 P4	6. 7 6. 7	7. 9 7. 9
M7. 0x0. 75	P2 P4	6. 7 6. 7	7. 9 7. 9
M7. 0x0. 75LOmgekeerde Tande	P2	7. 9	9. 3
M7. 0x1. 0	P2 P4	6 6	7. 4 7. 4
M7. 0x1. 0LOmgekeerde Tande	P2	7. 4	8. 6
M8. 0x0. 5	P2 P4	6. 7 6. 7	7. 9 7. 9
M8. 0x0. 75	P2 P4	6. 7 6. 7	7. 9 7. 9
M8. 0x0. 75LOmgekeerde Tande	P2	7. 9	9. 3
M8. 0x1. 0	P2 P4	6. 7 6. 7	7. 9 7. 9
M8. 0x1. 0LOmgekeerde Tande	P2	7. 9	9. 3
M8. 0x1. 25	+0. 1 P2 P3 P4	6 6 6 6	7. 9 7. 4 7. 4 7. 4
M8. 0x1. 25-100L		12. 6	
M8. 0x1. 25-150L		18. 3	
M8. 0x1. 25-AL	P2		6
M8. 0x1. 25-HT <i>skede</i>	1B	7. 4	7. 9
M8. 0x1. 25LOmgekeerde Tande	P2	7. 4	8. 6
M9. 0x0. 5			
	P2 P4	7. 9 7. 9	9. 6 9. 6
M9. 0x0. 75	P2	7. 9	9. 6
M9. 0x1. 0	P2	7. 9	9. 6
M9. 0x1. 0LOmgekeerde Tande	P2	10	11. 4
M9. 0x1. 25	P2	7. 9	9. 6
M10x0. 5	P2	8. 3	10
M10x0. 75	P2 P4	8. 3 8. 3	10 10
M10x0. 75LOmgekeerde Tande	P2	10	11. 4
M10x1. 0	P2 P4	8. 3 8. 3	10 10
M10x1. 0LOmgekeerde Tande	P2	10	11. 4
M10x1. 25	P2 P4	8. 3 8. 3	10 10
M10x1. 25LOmgekeerde Tande	P2	10	11. 4
M10x1. 5	+0. 1 P2 P3 P4	8. 3 7. 9 7. 9 7. 9	10 9. 6 9. 6 9. 6
M10x1. 5-100L		14. 6	
M10x1. 5-150L		19. 7	
M10x1. 5-AL	P2		7. 9
M10x1. 5-HT <i>skede</i>	1B	9. 3	10
M10x1. 5LOmgekeerde Tande	P2	11	11
M11x0. 5	P2	11	13. 1
M11x0. 75	P2	11	13. 1
M11x1. 0	P2	11	13. 1
M11x1. 5	P2	10. 4	12. 1

draad x pitch x lengte (/ omgekeerde tande)	presisie	wit	T in
M12x0.5	P2	11.0	13.1
M12x0.75	P2	11.0	13.1
M12x1.0	P2	11.0	13.1
	P4	11.0	13.1
M12x1.0L _{Omgekeerde Tande}	P2	12.6	14.7
M12x1.25	P2	11.0	13.1
	P4	11.0	13.1
M12x1.25L _{Omgekeerde Tande}	P2	12.6	14.7
M12x1.5	P2	11.0	13.1
	P4	11.0	13.1
M12x1.5L _{Omgekeerde Tande}	P2	12.6	14.7
M12x1.75	+0.1	11.0	13.1
	P2	12.0	12.6
	P3	10.4	12.6
	P4	10.4	12.6
M12x1.75-100L		18.9	
M12x1.75-150L		22.4	
M12x1.75-AL	P2		10.4
M12x1.75-HT _{skede}	1B	11.9	12.6
M12x1.75L _{Omgekeerde Tande}	P2	12.1	14.7
M14x1.0	P2	17.1	19.7
M14x1.25	P2	17.1	19.7
M14x1.5	P2	17.1	19.7
M14x2.0	P2	15.7	18.3
M16x1.0	P2	19.7	22.9
M16x1.25	P2	19.7	22.9
M16x1.5	P2	19.7	22.9
M16x2.0	P2	18.3	21.4
UNF0-80	P1	5.3	6
UNC1-64	P1	5.3	6
UNF1-72	P1	6.7	7.4
UNC2-56	P1	5.3	6
	P2	5.3	6
	P3	5.3	6
	P4	5.3	6
UNC2-56-100L		9.6	
UNC2-56-HT _{skede}	1B	6.1	6.9
UNF2-64	P1	6.7	7.4
UNC3-48	P1	5.3	6
UNF3-56	P1	6.7	7.4
UNC4-40	P1	4.7	5.4
	P2	4.7	5.4
	P3	4.7	5.4
	P4	4.7	5.4
UNC4-40-100L		9.6	
UNC4-40-AL	P2	4.7	
UNC4-40-HT _{skede}	1B	5.4	6.7
UNF4-48	P1	6.7	7.4
UNC5-40	P2	4.7	5.4
UNC5-40-100L		9.6	
UNF5-44	P2	6.7	7.4
UNC6-32	P2	4.7	5.4
	P3	4.7	5.4
	P4	4.7	5.4
UNC6-32-100L		9.6	
UNC6-32-AL	P2	4.7	
UNC6-32-HT _{skede}	1B	5.4	6.7
UNC6-32L _{Omgekeerde Tande}	P2	5.7	6.7
UNF6-40	P2	6.7	7.4
UNC8-32	P2	4.7	5.4
	P3	4.7	5.4
	P4	4.7	5.4
UNC8-32-100L		9.6	
UNC8-32-AL	P2	4.7	
UNC8-32-HT _{skede}	1B	5.4	6.7
UNC8-32L _{Omgekeerde Tande}	P2	5.7	6.7
UNF8-36	P2	6.7	7.4
UNC10-24	P2	4.7	5.7
	P3	4.7	5.7
	P4	4.7	5.7
UNC10-24-100L		9.6	
UNC10-24-AL	P2	4.7	
UNC10-24-HT _{skede}	1B	5.4	6.7
UNC10-24L _{Omgekeerde Tande}	P2	5.7	6.7
UNF10-32	P2	4.7	5.7
	P3	4.7	5.7
	P4	4.7	5.7
UNF10-32-100L		9.6	
UNF10-32-HT _{skede}	1B		7.4
UNF10-32L _{Omgekeerde Tande}	P2	7.4	8.3
UNC12-24	P2	4.7	5.7
UNF12-28	P2	6.7	7.6
UNEF12-32	P2	6.7	7.6
UNS12-36	P2	6.7	7.6
UNC1/4-20	P2	4.7	5.7
	P3	4.7	5.7
	P4	4.7	5.7
UNC1/4-20		9.6	
UNC1/4-20-100L		9.6	
UNC1/4-20-AL	P2	4.7	
UNC1/4-20-HT _{skede}	1B	5.4	6.7
UNC1/4-20L _{Omgekeerde Tande}	P2	5.7	6.7

draad x pitch x lengte (/ omgekeerde tande)	presisie	wit	tin
UNF1/4-28	P2	6.7	7.6
	P4	6.7	7.6
UNF1/4-28-HT skade	1B		7.4
UNF1/4-28L omgekeerde tande	P2	7.4	8.3
UNEF1/4-32	P2	6.7	7.6
UNS1/4-36	P2	6.7	7.6
UNC5/16-18	P2	6.0	7.4
	P3	6.0	7.4
	P4	6.0	7.4
UNC5/16-18-100L		13.1	
UNC5/16-18-AL	P2	6.7	
UNC5/16-18-HT skade	1B	7.9	8.3
UNC5/16-18L omgekeerde tande	P2	7.4	8.6
UNF5/16-24	P2	7.4	8.6
	P4	7.4	8.6
UNF5/16-24-HT skade	1B		10.0
UNF5/16-24L omgekeerde tande	P2	9.3	10.4
UNC3/8-16	P2	7.9	9.6
	P3	7.9	9.6
	P4	7.9	9.6
UNC3/8-16-100L		14.7	
UNC3/8-16-AL	P2	8.3	
UNC3/8-16-HT skade	1B	9.6	10.4
UNC3/8-16L omgekeerde tande	P2	9.6	11.0
UNF3/8-24	P2	9.3	10.7
	P4	9.3	10.7
UNF3/8-24-HT skade	1B		12.1
UNF3/8-24L omgekeerde tande	P2	11.0	12.6
UNS3/8-32	P2	9.3	10.7
UNC7/16-14	P2	11.9	13.9
UNF7/16-20	P2	12.6	14.7
UNC1/2-12	P2	13.1	15.3
UNF1/2-20	P2	14.6	16.4
W1/8-40	P1	4.7	5.4
W5/32-32	P2	4.7	5.4
W3/16-24	P2	4.7	5.4
W7/32-24	P2	4.7	5.7
W1/4-20	P2	4.7	5.7
W5/16-18	P2	6.0	7.4
W3/8-16	P2	7.9	9.6
W7/16-14	P2	11.9	13.9
W1/2-12	P2	13.1	15.3
PS1/8-28 Britse standaard		7.9	
PS1/4-14 Amerikaanse standaard		22.4	
PS1/4-18 Amerikaanse standaard		7.9	
PS1/4-19 Britse standaard		9.3	
PS3/8-18 Amerikaanse standaard		13.1	
PS3/8-19 Britse standaard		14.6	
PS1/2-14 Amerikaanse standaard		17.1	
PS1/2-14 Britse standaard		19.7	
PS3/4-14 Britse standaard		25.0	
PS1-11 Britse standaard		41.9	
PS1-11. 1-2 Amerikaanse standaard		41.9	
PT1/16-28 Britse standaard		7.9	
PT1/8-28 Britse standaard		7.9	
PT1/4-19 Britse standaard		10.4	
PT3/8-19 Britse standaard		15.7	
PT1/2-14 Britse standaard		19.7	
PT3/4-14 Britse standaard		27.6	
PT1-11 Britse standaard		46.0	
NPT1/8-27 Amerikaanse standaard		7.9	
NPT1/4-18 Amerikaanse standaard		10.4	
NPT3/8-18 Amerikaanse standaard		15.7	
NPT1/2-14 Amerikaanse standaard		19.7	
NPT1/4-14 Amerikaanse standaard		27.6	
NPT1-11. 1-2 Amerikaanse standaard		46.0	


Hand Tap / Circular Die

Hand Tap/Circular Die

MaiFix®

HT Straight Wire Tap

HT Straight Wire Tap



Draad x Pitch x Lengte (/ Omgekeerde Tande)	presisie	wit
M1. 0x0. 25	P1	4. 3
M1. 2x0. 25	P1	4. 3
M1. 6x0. 35	P1	4. 3
M1. 7x0. 35	P1	4. 3
M1. 8x0. 35	P1	4. 3
M2. 0x0. 25	P1	4. 7
M2. 0x0. 4	P2	4. 0
	P3	4. 0
	P4	4. 0
M2. 2x0. 25	P1	4. 7
M2. 2x0. 45	P2	4. 0
M2. 3x0. 25	P1	4. 7
M2. 3x0. 4	P2	4. 0
M2. 5x0. 35	P1	4. 7
M2. 5x0. 45	P2	4. 0
	P3	4. 0
	P4	4. 0
M2. 6x0. 35	P2	4. 7
M2. 6x0. 45	P2	4. 0
	P3	4. 0
	P4	4. 0
M3. 0x0. 35	P2	4. 7
M3. 0x0. 5	P2	3. 3
	P3	3. 3
	P4	3. 3
M3. 5x0. 35	P2	4. 7
M3. 5x0. 6	P2	3. 3
	P3	3. 3
	P4	3. 3
M4. 0x0. 35	P2	4. 7
M4. 0x0. 5	P2	4. 7
M4. 0x0. 7	P2	3. 3
	P3	3. 3
	P4	3. 3
M4. 0x0. 75	P2	4. 7
M4. 5x0. 5	P2	4. 7
M4. 5x0. 75	P2	3. 6
M5. 0x0. 35	P2	4. 7
M5. 0x0. 5	P2	4. 7
M5. 0x0. 8	P2	3. 6
	P3	3. 6
	P4	3. 6
M6. 0x0. 35	P2	5. 3
M6. 0x0. 5	P2	4. 7
M6. 0x0. 75	P2	4. 7
M6. 0x1. 0	P2	3. 6
	P3	3. 6
	P4	3. 6
M7. 0x0. 5	P2	6. 1
M7. 0x0. 75	P2	6. 1
M7. 0x1. 0	P2	5. 3
M8. 0x0. 35	P2	7. 4
M8. 0x0. 5	P2	6. 1
M8. 0x0. 75	P2	6. 1
M8. 0x1. 0	P2	6. 1
M8. 0x1. 25	P2	5. 3
	P3	5. 3
M9. 0x0. 5	P3	8. 1
M9. 0x0. 75	P3	8. 1
M9. 0x1. 0	P3	8. 1
M9. 0x1. 25	P3	6. 9
M10x0. 5	P3	8. 1
M10x0. 75	P3	8. 1
M10x1. 0	P3	8. 1
M10x1. 25	P3	8. 1
M10x1. 5	P3	6. 9
	P4	6. 9
M11x0. 5	P3	10. 4
M11x0. 75	P3	10. 4
M11x1. 0	P3	10. 4
M11x1. 5	P3	9. 3
M12x0. 5	P3	10. 4
M12x0. 75	P3	10. 4
M12x1. 0	P3	10. 4
M12x1. 25	P3	10. 4
M12x1. 5	P3	10. 4
M12x1. 75	P3	9. 3
	P4	9. 3
M14x2. 0	P3	10. 4
M16x2. 0	P3	13. 1

Draad x Pitch x Lengte (/ Omgekeerde Tande)	presisie	wit
UNF0-80	P1	4. 3
UNC1-64	P1	4. 3
UNF1-72	P1	5. 0
UNC2-56	P1	4. 3
UNF2-64	P1	5. 0
UNC3-48	P1	4. 3
UNF3-56	P1	5. 0
UNC4-40	P2	4. 0
	P3	4. 0
	P4	4. 7
UNF4-48	P2	4. 0
UNC5-40	P2	4. 0
UNF5-44	P2	4. 7
UNC6-32	P2	4. 0
	P3	4. 0
	P4	4. 7
UNF6-40	P2	4. 0
UNC8-32	P2	4. 0
	P3	4. 0
	P4	4. 7
UNF8-36	P2	4. 0
UNC10-24	P2	4. 0
UNF10-32	P2	4. 7
UNC12-24	P2	4. 0
UNF12-28	P2	4. 7
UNC1/4-20	P2	4. 0
UNF1/4-28	P2	4. 7
UNF1/4-32	P2	4. 7
UNC5/16-18	P3	5. 3
UNF5/16-24	P3	6. 1
UNF5/16-32	P3	6. 7
UNC3/8-16	P3	6. 9
UNF3/8-24	P3	8. 1
UNF3/8-32	P3	8. 1
UNC7/16-14	P3	9. 3
UNF7/16-20	P3	10. 4
UNC1/2-13	P3	9. 3
UNF1/2-20	P3	10. 4
Tube Tapping		
PS1/16-28 Britse Standard		6. 7
PS1/8-27 Amerikaanse Standaard		6. 7
PS1/8-28 Britse Standard		6. 7
PS1/4-14 Amerikaanse Standaard		22. 4
PS1/4-18 Amerikaanse Standaard		7. 9
PS1/4-19 Britse Standard		7. 9
PS3/8-18 Amerikaanse Standaard		13. 1
PS3/8-19 Britse Standard		13. 1
PS1/2-14 Amerikaanse Standaard		17. 1
PS1/2-14 Britse Standard		17. 1
PS3/4-14 Britse Standard		22. 4
PS1-11 Britse Standard		38. 1
PS1-11. 1-2 American Standard		38. 1
PT1/16-28 Britse Standard		6. 7
PT1/8-28 Britse Standard		6. 7
PT1/4-19 Britse Standard		8. 6
PT3/8-19 Britse Standard		14. 6
PT1/2-14 Britse Standard		18. 3
PT3/4-14 Britse Standard		25. 0
PT1-11 Britse Standard		41. 9
NPT1/8-27 Amerikaanse Standaard		6. 7
NPT1/4-18 Amerikaanse Standaard		8. 6
NPT3/8-18 Amerikaanse Standaard		14. 6
NPT1/2-14 Amerikaanse Standaard		18. 3
NPT1/4-14 Amerikaanse Standaard		25. 0
NPT1-11. 1-2 American Standard		41. 9

AR-D Verstelbare Omsendbrief

AR-D Adjustable Circular Die









Draad x Pitch x Lengte (/ Omgekeerde Tande)	External Diameter	wit
M1. 0x0. 25	20	33. 1
M1. 2x0. 25	20	13. 1
M1. 4x0. 3	20	13. 1
M1. 5x0. 3	20	13. 1
M1. 6x0. 35	20	13. 1
M1. 7x0. 35	20	13. 1
M1. 8x0. 35	20	13. 1
M2. 0x0. 25	20	11. 9
M2. 0x0. 4	20	10. 4
M2. 0x0. 4L Omgekeerde Tande	20	11. 9
M2. 2x0. 25	20	11. 9
M2. 2x0. 45	20	10. 4
M2. 3x0. 4	20	10. 4
M2. 5x0. 35	20	11. 9
M2. 5x0. 45	20	10. 4
M2. 5x0. 45L Omgekeerde Tande	20	11. 9
M2. 6x0. 35	20	11. 9
M2. 6x0. 45	20	10. 4
M3. 0x0. 35	20	11. 9
M3. 0x0. 5	20	10. 4
M3. 0x0. 5L Omgekeerde Tande	20	11. 9
M4. 0x0. 35	20	11. 9
M4. 0x0. 5	20	11. 9
M4. 0x0. 7	20	10. 4
M4. 0x0. 7L Omgekeerde Tande	20	11. 9
M4. 5x0. 5	20	11. 9
M4. 5x0. 75	20	10. 4
M5. 0x0. 35	20	11. 9
M5. 0x0. 5	20	11. 9
M5. 0x0. 8	20	10. 4
M5. 0x0. 8L Omgekeerde Tande	20	11. 9
M6. 0x0. 5	20	11. 9
M6. 0x0. 75	20	11. 9
M6. 0x1. 0	20	10. 4
M6. 0x1. 0L Omgekeerde Tande	20	11. 9
M7. 0x0. 5	25	13. 1
M7. 0x0. 75	25	13. 1
M7. 0x1. 0	25	11. 9
M8. 0x0. 5	25	13. 1
M8. 0x0. 75	25	13. 1
M8. 0x1. 0	25	13. 1
M8. 0x1. 25	25	11. 9
M8. 0x1. 25L Omgekeerde Tande	25	13. 1
M9. 0x0. 5	25	13. 1
M9. 0x0. 75	25	13. 1
M9. 0x1. 0	25	13. 1
M9. 0x1. 25	25	11. 9
M10x0. 5	25	13. 1
M10x0. 75	25	13. 1
M10x1. 0	25	13. 1
M10x1. 25	25	13. 1
M10x1. 5	25	11. 9
M10x1. 5L Omgekeerde Tande	25	13. 1
M11x1. 0	25	11. 9
M12x0. 5	25	13. 1
M12x0. 75	25	13. 1
M12x1. 0	25	13. 1
M12x1. 25	25	13. 1
M12x1. 5	25	13. 1
M12x1. 75	25	11. 9
M12x1. 75L Omgekeerde Tande	25	13. 1
M14x1. 0	38	25. 0
M14x1. 25	38	25. 0
M14x1. 5	38	25. 0
M14x2. 0	38	23. 6
M16x1. 0	38	25. 0
M16x1. 25	38	25. 0
M16x1. 5	38	25. 0
M16x2. 0	38	23. 6

Draad x Pitch x Lengte (/ Omgekeerde Tande)	External Diameter	wit
UNF0-80	20	11. 9
UNC1-64	20	10. 4
UNF1-72	20	11. 9
UNC2-56	20	10. 4
UNC3-48	20	10. 4
UNF3-56	20	11. 9
UNC4-40	20	10. 4
UNF4-48	20	11. 9
UNC5-40	20	10. 4
UNC6-32	20	10. 4
UNF6-40	20	11. 9
UNC8-32	20	10. 4
UNF8-36	20	11. 9
UNC10-24	20	10. 4
UNF10-32	20	11. 9
UNC12-24	20	10. 4
UNF12-28	20	11. 9
UNC1/4-20	20	10. 4
UNF1/4-28	20	11. 9
UNF1/4-32	20	11. 9
UNF5/16-18	25	11. 9
UNF5/16-24	25	13. 1
UNC3/8-16	25	11. 9
UNF3/8-24	25	13. 1
UNC7/16-14	25	11. 9
UNF7/16-20	25	13. 1
UNC1/2-12	25	11. 9
UNF1/2-20	25	13. 1
W1/8-40	20	10. 4
W5/32-32	20	10. 4
W3/16-24	20	10. 4
W1/4-20	20	10. 4
W5/16-18	25	11. 9
W3/8-16	25	11. 9
W7/16-14	25	11. 9
W1/2-12	25	11. 9

Bogenoemde prys sluit vraag, belasting en fooi in.
Binnelandse USD Dollar Transaksieprys In China.
As jy enige vrae het, stuur asb. E-pos: eva@mzgtool.cn





<http://www.mzg.tw>




Produkprente	Spesifikasie	R	USD
	CCGT060202 CBN1 CCGT060204 CBN1 CCGT060208 CBN1 CCGT09T302 CBN1 CCGT09T304 CBN1 CCGT09T308 CBN1 CCGT120402 CBN1 CCGT120404 CBN1 CCGT120408 CBN1	0.2 0.4 0.8 0.2 0.4 0.8 0.2 0.4 0.8	6.9 6.9 6.9 6.9 6.9 6.9 6.9 6.9 6.9
	CCGT060202 PCD1 CCGT060204 PCD1 CCGT09T302 PCD1 CCGT09T304 PCD1 CCGT09T308 PCD1 CCGT120402 PCD1 CCGT120404 PCD1 CCGT120408 PCD1	0.2 0.4 0.2 0.4 0.8 0.2 0.4 0.8	6.9 6.9 6.9 6.9 6.9 6.9 6.9 6.9
	CCGT060202-AL ZK01 CCGT060204-AL ZK01 CCGT060208-AL ZK01 CCGT09T302-AL ZK01 CCGT09T304-AL ZK01 CCGT09T308-AL ZK01 CCGT120402-AL ZK01 CCGT120404-AL ZK01 CCGT120408-AL ZK01	0.2 0.4 0.8 0.2 0.4 0.8 0.2 0.4 0.8	1.1 1.1 1.1 1.4 1.4 1.4 2.3 2.3 2.3
	CCMT060204 ZM30 CCMT060208 ZM30 CCMT09T304 ZM30 CCMT09T308 ZM30 CCMT120404 ZM30 CCMT120408 ZM30	0.4 0.8 0.4 0.8 0.4 0.8	1.6 1.6 1.7 1.7 2.4 2.4
	CCMT060204-FG ZN60 CCMT09T304-FG ZN60 CCMT09T308-FG ZN60	0.4 0.4 0.8	1.7 1.9 1.9
	CCMT060202-HQ ZN60 CCMT060204-HQ ZN60 CCMT09T302-HQ ZN60 CCMT09T304-HQ ZN60	0.2 0.4 0.2 0.4	1.7 1.7 1.9 1.9
	CCMT060204-MT ZN60 CCMT09T304-MT ZN60 CCMT09T308-MT ZN60	0.4 0.8 0.8	1.7 1.9 1.9
	CCGT060202EL-U ZN90 CCGT060204EL-U ZN90 CCGT09T302EL-U ZN90 CCGT09T304EL-U ZN90	0.2 0.4 0.2 0.4	4.0 4.0 4.0 4.0
	CCGT060202ER-U ZN90 CCGT060204ER-U ZN90 CCGT09T302ER-U ZN90 CCGT09T304ER-U ZN90	0.2 0.4 0.2 0.4	4.0 4.0 4.0 4.0



Produkprente	Spesifikasie	R	USD
	CNMG120402 CBN1 CNMG120404 CBN1 CNMG120408 CBN1	0.2 0.4 0.8	6.9 6.9 6.9
	CNMG120402 PCD1 CNMG120404 PCD1 CNMG120408 PCD1	0.2 0.4 0.8	6.9 6.9 6.9
	CNMG120404-TM ZC25 CNMG120408-TM ZC25 CNMG120412-TM ZC25	0.4 0.8 1.2	2.6 2.6 2.6
	CNMG120408R-X ZC25 CNMG120408L-X ZC25	0.8 0.8	2.6 2.6
	CNMG120404-TM ZC35 CNMG120408-TM ZC35	0.4 0.8	2.6 2.6
	CNMG120404-HA ZK01 CNMG120408-HA ZK01	0.4 0.8	2.0 2.0
	CNMA120404 ZK50 CNMA120408 ZK50	0.4 0.8	2.6 2.6
	CNMG120404 ZK50 CNMG120408 ZK50	0.4 0.8	2.6 2.6
	CNMG120408-HS ZM30	0.8	2.6
	CNMG120404-MA ZM30 CNMG120408-MA ZM30	0.4 0.8	2.6 2.6
	CNMG120404-MS ZM30 CNMG120408-MS ZM30	0.4 0.8	2.6 2.6
	CNMG120404-HQ ZN60 CNMG120408-HQ ZN60	0.4 0.8	2.3 2.3
	CNMG120404-TS ZN60 CNMG120408-TS ZN60	0.4 0.8	2.3 2.3







Bogenoemde prys sluit vrag, belasting en fooi in.
Binnelandse USD Dollar Transaksieprys In China.
As jy enige vrae het, stuur asb. E-pos: eva@mzgtool.cn

<http://www.mzg.tw>







Produkprente	Spesifikasie	R	USD
	DCGT070202 CBN1 DCGT070204 CBN1 DCGT070208 CBN1 DCGT11T301 CBN1 DCGT11T302 CBN1 DCGT11T304 CBN1 DCGT11T308 CBN1 DCGW11T308 CBN1	0.2 0.4 0.8 0.1 0.2 0.4 0.8 0.8	6.9 6.9 6.9 6.9 6.9 6.9 6.9 6.9
	DCGT070201 PCD1 DCGT070202 PCD1 DCGT070204 PCD1 DCGT070208 PCD1 DCGT11T301 PCD1 DCGT11T302 PCD1 DCGT11T304 PCD1 DCGT11T308 PCD1	0.1 0.2 0.4 0.8 0.1 0.2 0.4 0.8	6.9 6.9 6.9 6.9 6.9 6.9 6.9 6.9
	DCGT070202-AL ZK01 DCGT070204-AL ZK01 DCGT11T302-AL ZK01 DCGT11T304-AL ZK01 DCGT11T308-AL ZK01	0.2 0.4 0.2 0.4 0.8	1.4 1.4 1.6 1.6 1.6
	DCMT070204-MV ZM30 DCMT11T304-MV ZM30	0.4 0.4	1.6 1.7
	DCMT11T304 ZM30 DCMT11T308 ZM30	0.4 0.8	1.7 1.7
	DCMT070204-FG ZN60 DCMT11T302-FA ZN60 DCMT11T304-FG ZN60	0.4 0.2 0.4	1.7 1.9 1.9
	DCMT070202-HQ ZN60 DCMT070204-HQ ZN60 DCMT11T302-HQ ZN60 DCMT11T304-HQ ZN60	0.2 0.4 0.2 0.4	1.7 1.7 1.9 1.9
	DCGT11T302FL-U ZN90 DCGT11T304FL-U ZN90	0.2 0.4	4.0 4.0
	DCGT11T302FR-U ZN90 DCGT11T304FR-U ZN90	0.2 0.4	4.0 4.0




Produkprente	Spesifikasie	R	USD
	DNMA150404 CBN1 DNMA150408 CBN1	0.4 0.8	6.9 6.9
	DNMA150404 PCD1 DNMA150408 PCD1	0.4 0.8	6.9 6.9
	DNMG150404-HA ZK01 DNMG150408-HA ZK01 DNMG150604-HA ZK01 DNMG150608-HA ZK01	0.4 0.8 0.4 0.8	4.3 4.3 4.9 4.9
	DNMG110404-FG ZN60	0.4	2.6
	DNMG150404-HQ ZN60 DNMG150408-HQ ZN60	0.4 0.8	2.6 2.6
	DNMG150404L-VF ZN60	0.4	2.6
	DNMG150404R-VF ZN60	0.4	2.6

Produkprente	Spesifikasie	R	USD
 Gietyster En Hardened Materiaal voltooi bewerking	SNMG120404 CBN1 SNMG120408 CBN1	0.4 0.8	6.9 6.9
 Koper En Aluminium Voltooi bewerking	SNMG120404 PCD1 SNMG120408 PCD1	0.4 0.8	6.9 6.9
 Ruwe verwerking van staal	SNMG120408L-S ZC25	0.8	2.6
 Ruwe verwerking van harde staal	SNMG120408L-S ZC35	0.8	2.6
 Ruwe verwerking van staal	SNMG120408R-S ZC25	0.8	2.6
 Ruwe verwerking van harde staal	SNMG120408R-S ZC35	0.8	2.6
 Medium afwerking bewerking van staal	SNMG120408-TM ZC25	0.8	2.6
 Koper En Aluminium Medium Voltooi bewerking	SNMG120404-HA ZK01 SNMG120408-HA ZK01	0.4 0.8	2.0 2.0
 Vleklose staal Processing	SNMG120408-MA ZM30	0.8	2.6
 Vleklose staal Processing	SNMG120404-MS ZM30	0.4	2.6
 Vleklose staal Processing	SNMG120404-HQ ZN60 SNMG120404-HQ ZN60	0.4 0.8	2.3 2.3
 Cermet Medium En Fyn Staal Onderdele het goeie afwerking	SCMT09T304-MT ZN60	0.4	1.9
 Koper En Aluminium Medium Voltooi bewerking	SCGT09T304-AL ZK01 SCGT09T308-AL ZK01 SCGT120404-AL ZK01 SCGT120408-AL ZK01	0.4 0.8 0.4 0.8	1.4 1.4 1.9 1.9

Produkprente	Spesifikasie	R	USD
 Gietyster En Hardened Materiaal voltooi bewerking	TBGT060102 CBN1 TCGT110302 CBN1 TCGT16T302 CBN1 TCGT16T304 CBN1 TCGT16T308 CBN1 TPGT080202 CBN1 TPGT080204 CBN1 TPGT090202 CBN1 TPGT090204 CBN1 TPGT110202 CBN1 TPGT110204 CBN1 TPGT110302 CBN1 TPGT110304 CBN1 TPGT110308 CBN1	0.2 0.2 0.2 0.4 0.8 0.2 0.4 0.2 0.4 0.2 0.4 0.2 0.4 0.8	6.9 6.9 6.9 6.9 6.9 6.9 6.9 6.9 6.9 6.9 6.9 6.9 6.9 6.9
 Koper En Aluminium Voltooi bewerking	TBGT060102 PCD1 TCGT110202 PCD1 TCGT110204 PCD1 TCGT110304 PCD1 TCGT16T302 PCD1 TCGT16T304 PCD1 TCGT16T308 PCD1 TPGT080202 PCD1 TPGT080204 PCD1 TPGT090202 PCD1 TPGT090204 PCD1 TPGT110204 PCD1 TPGT110302 PCD1 TPGT110304 PCD1	0.2 0.2 0.4 0.4 0.2 0.4 0.8 0.2 0.4 0.2 0.4 0.4 0.2 0.4	6.9 6.9 6.9 6.9 6.9 6.9 6.9 6.9 6.9 6.9 6.9 6.9 6.9 6.9
 Cermet Medium En Fyn Staal Onderdele het goeie afwerking	TBGT060102L ZN90 TBGT060104L ZN90 TCGT110202L ZN90 TCGT110204L ZN90 TPGH080202L ZN90 TPGH080204L ZN90 TPGH090202L ZN90 TPGH090204L ZN90 TPGH110302L ZN90 TPGH110304L ZN90	0.2 0.4 0.2 0.4 0.2 0.4 0.2 0.4 0.2 0.4	3.4 3.4 3.4 3.4 3.4 3.4 3.4 3.4 3.4 3.4
 Cermet Medium En Fyn Staal Onderdele het goeie afwerking	TBGT060102L-W ZN90 TBGT060104L-W ZN90 TPGT080202L-W ZN90 TPGT080204L-W ZN90 TPGT090202L-W ZN90 TPGT090204L-W ZN90 TPGT110302L-W ZN90 TPGT110304L-W ZN90	0.2 0.4 0.2 0.4 0.2 0.4 0.2 0.4	3.4 3.4 3.4 3.4 3.4 3.4 3.4 3.4
 Cermet Medium En Fyn Staal Onderdele het goeie afwerking	TCMT090202-HQ ZN60 TCMT090204-HQ ZN60 TCMT110202-HQ ZN60 TCMT110204-HQ ZN60 TCMT110208-HQ ZN60 TCMT16T304-HQ ZN60	0.2 0.4 0.2 0.4 0.8 0.4	1.7 1.7 1.7 1.7 1.7 2.4
 Koper En Aluminium Medium Voltooi bewerking	TPMT110304-HQ ZN60 TPMT110308-HQ ZN60	0.4 0.8	1.7 1.7
 Vleklose staal Processing	TCGT090202-AL ZK01 TCGT090204-AL ZK01 TCGT110202-AL ZK01 TCGT110204-AL ZK01 TCGT110302-AL ZK01 TCGT110304-AL ZK01 TCGT16T302-AL ZK01 TCGT16T304-AL ZK01 TCGT16T308-AL ZK01	0.2 0.4 0.2 0.4 0.2 0.4 0.2 0.4 0.8	1.4 1.4 1.4 1.4 1.6 1.6 1.7 1.7 1.7
 Vleklose staal Processing	TCMT110204 ZM30 TCMT110208 ZM30 TCMT16T304 ZM30 TCMT16T308 ZM30	0.4 0.8 0.4 0.8	1.6 1.6 2.3 2.3

Bogenoemde prys sluit vraag, belasting en fooi in.
Binnelandse USD Dollar Transaksieprys In China.
As jy enige vrae het, stuur asb. E-pos: eva@mzgtool.cn

Produkprente	Spesifikasie	R	USD
	TNMA160402 CBN1 TNMA160404 CBN1 TNMA160408 CBN1	0.2 0.4 0.8	6.9 6.9 6.9
	TNMA160402 PCD1 TNMA160404 PCD1 TNMA160408 PCD1	0.2 0.4 0.8	6.9 6.9 6.9
	TNMG160404-CQ ZC25 TNMG160408-CQ ZC25 TNMG160404-HQ ZC25 TNMG160408-HQ ZC25	0.4 0.8 0.4 0.8	2.3 2.3 2.3 2.3
	TNMG160404L-S ZC25 TNMG160408L-S ZC25 TNMG160404R-S ZC25 TNMG160408R-S ZC25	0.4 0.8 0.4 0.8	2.3 2.3 2.3 2.3
	TNMG160404L-S ZC35 TNMG160408L-S ZC35 TNMG160404R-S ZC35 TNMG160408R-S ZC35	0.4 0.8 0.4 0.8	2.3 2.3 2.3 2.3
	TNMG160404-TM ZC25 TNMG160408-TM ZC25 TNMG160412-TM ZC25	0.4 0.8 1.2	2.3 2.3 2.3
	TNMG160404-TM ZC35 TNMG160408-TM ZC35	0.4 0.8	2.3 2.3
	TNMG160402-HA ZK01 TNMG160404-HA ZK01 TNMG160408-HA ZK01	0.2 0.4 0.8	1.9 1.9 1.9
	TNMA160404 ZK50 TNMA160408 ZK50 TNMG160404 ZK50 TNMG160408 ZK50	0.4 0.8 0.4 0.8	2.3 2.3 2.3 2.3
	TNMG160404-HA ZM30 TNMG160408-HA ZM30 TNMG160404-MA ZM30 TNMG160408-MA ZM30	0.4 0.8 0.4 0.8	2.3 2.3 2.3 2.3
	TNMG160404-MQ ZM30 TNMG160408-MQ ZM30	0.4 0.8	2.3 2.3
	TNMG160404-MS ZM30 TNMG160408-MS ZM30	0.4 0.8	2.3 2.3






Produkprente	Spesifikasie	R	USD
	TNMG160404L-C ZN60 TNMG160408L-C ZN60 TNMG160404R-C ZN60 TNMG160408R-C ZN60	0.4 0.8 0.4 0.8	1.9 1.9 1.9 1.9
	TNMG160404L-S ZN60 TNMG160408L-S ZN60 TNMG160404R-S ZN60 TNMG160408R-S ZN60	0.4 0.8 0.4 0.8	1.9 1.9 1.9 1.9
	TNMG160404L-VF ZN60 TNMG160408L-VF ZN60 TNMG160404R-VF ZN60 TNMG160408R-VF ZN60	0.4 0.8 0.4 0.8	1.9 1.9 1.9 1.9
	TNMG160404L-FS ZN60 TNMG160408L-FS ZN60 TNMG160404R-FS ZN60 TNMG160408R-FS ZN60	0.4 0.8 0.4 0.8	1.9 1.9 1.9 1.9
	TNMG160404-HQ ZN60 TNMG160408-HQ ZN60	0.4 0.8	1.9 1.9
	TNMG160404-MT ZN60 TNMG160408-MT ZN60	0.4 0.8	1.9 1.9
	TNMG160404-TS ZN60 TNMG160408-TS ZN60	0.4 0.8	1.9 1.9
	TNGG160402L-P ZN90 TNGG160404L-P ZN90 TNGG160402R-P ZN90 TNGG160404R-P ZN90	0.2 0.4 0.2 0.4	3.6 3.6 3.6 3.6
	TNGG160402L-S ZN90 TNGG160404L-S ZN90 TNGG160402R-S ZN90 TNGG160404R-S ZN90	0.2 0.4 0.2 0.4	3.6 3.6 3.6 3.6



Bogenoemde prys sluit vraag, belasting en fooi in.
Binnelandse USD Dollar Transaksieprys In China.
As jy enige vrae het, stuur asb. E-pos: eva@mzgtool.cn

<http://www.mzg.tw>


Produkprente	Spesifikasie	R	USD
	VBMT110302 CBN1	0.2	6.9
	VBMT110304 CBN1	0.4	6.9
	VBMT160402 CBN1	0.2	6.9
	VBMT160404 CBN1	0.4	6.9
	VBMT160408 CBN1	0.8	6.9
	VCGT110302 CBN1	0.2	6.9
	VCGT110304 CBN1	0.4	6.9
	VCGT110308 CBN1	0.8	6.9
	VCGT160402 CBN1	0.2	6.9
	VCGT160404 CBN1	0.4	6.9
	VCGT160408 CBN1	0.8	6.9
	VCGT160412 CBN1	1.2	6.9
	VBGT110301 PCD1	0.1	6.9
	VBGT110302 PCD1	0.2	6.9
	VBGT110304 PCD1	0.4	6.9
	VBGT110308 PCD1	0.8	6.9
	VBGT160402 PCD1	0.2	6.9
	VBGT160404 PCD1	0.4	6.9
	VBGT160408 PCD1	0.8	6.9
	VCGT110301 PCD1	0.1	6.9
	VCGT110302 PCD1	0.2	6.9
	VCGT110304 PCD1	0.4	6.9
	VCGT110308 PCD1	0.8	6.9
	VCGT160401 PCD1	0.1	6.9
	VCGT160402 PCD1	0.2	6.9
	VCGT160404 PCD1	0.4	6.9
	VCGT160408 PCD1	0.8	6.9
	VCGT160412 PCD1	1.2	6.9
	VBGT110302-AL ZK01	0.2	1.1
	VBGT110304-AL ZK01	0.4	1.1
	VBGT160402-AL ZK01	0.2	2.0
	VBGT160404-AL ZK01	0.4	2.0
	VBGT160408-AL ZK01	0.8	2.0
	VCGT110302-AL ZK01	0.2	1.1
	VCGT110304-AL ZK01	0.4	1.1
	VCGT160402-AL ZK01	0.2	2.0
	VCGT160404-AL ZK01	0.4	2.0
	VCGT160408-AL ZK01	0.8	2.0
	VBMT160404-MV ZM30	0.4	3.7
	VBMT160408-MV ZM30	0.8	3.7
	VCGT110302-AL ZK01	0.2	1.1
	VCGT110304-AL ZK01	0.4	1.1
	VCGT160402-AL ZK01	0.2	2.0
	VCGT160404-AL ZK01	0.4	2.0
	VCGT160408-AL ZK01	0.8	2.0
	VBMT110304-HQ ZN60	0.4	2.7
	VBMT160404-HQ ZN60	0.4	3.4
	VBMT160404-MT ZN60	0.4	3.6
	VBGT110302L ZN90	0.2	4.7
	VBGT110304L ZN90	0.4	4.7
	VBGT110302R-Y ZN90	0.2	4.7
	VBGT110304R-Y ZN90	0.4	4.7
	VBGT110302R-Y ZN90	0.2	4.7
	VBGT110304R-Y ZN90	0.4	4.7
	VBGT110302R-Y ZN90	0.2	4.7
	VBGT110304R-Y ZN90	0.4	4.7
	VBGT110302R-Y ZN90	0.2	4.7
	VBGT110304R-Y ZN90	0.4	4.7
	VBGT110302R-Y ZN90	0.2	4.7
	VBGT110304R-Y ZN90	0.4	4.7





Produkprente	Spesifikasie	R	USD
	VNMG160404 CBN1	0.4	6.9
	VNMG160408 CBN1	0.8	6.9
	VNMG160402 PCD1	0.2	6.9
	VNMG160404 PCD1	0.4	6.9
	VNMG160408 PCD1	0.8	6.9
	VNMG160404-TM ZC25	0.4	2.7
	VNMG160408-TM ZC25	0.8	2.7
	VNMG160404-TM ZC35	0.4	2.7
	VNMG160408-TM ZC35	0.8	2.7
	VNMG160404-AL ZK01	0.4	2.3
	VNMG160408-AL ZK01	0.8	2.3
	VNMG160404 ZM30	0.4	2.7
	VNMG160408 ZM30	0.8	2.7
	VNMG160404-HS ZM30	0.4	2.7
	VNMG160408-HS ZM30	0.8	2.7
	VNMG160404-MT ZN60	0.4	2.3
	VNMG160408-MT ZN60	0.8	2.3
	VNMG160404-MT ZN60	0.4	2.3
	VNMG160408-MT ZN60	0.8	2.3
	VNMG160404-MT ZN60	0.4	2.3
	VNMG160408-MT ZN60	0.8	2.3
	VNMG160404-MT ZN60	0.4	2.3
	VNMG160408-MT ZN60	0.8	2.3
	VNMG160404-MT ZN60	0.4	2.3
	VNMG160408-MT ZN60	0.8	2.3
	VNMG160404-MT ZN60	0.4	2.3
	VNMG160408-MT ZN60	0.8	2.3
	VNMG160404-MT ZN60	0.4	2.3
	VNMG160408-MT ZN60	0.8	2.3
	VNMG160404-MT ZN60	0.4	2.3

Produkprente	Spesifikasie	R	USD
	WNMG080404 CBN1 WNMG080408 CBN1 WNMG080412 CBN1	0.4 0.8 1.2	6.9 6.9 6.9
	WNMA080402 PCD1 WNMA080404 PCD1 WNMA080408 PCD1	0.2 0.4 0.8	6.9 6.9 6.9
	WNMG080404-CQ ZC25 WNMG080408-CQ ZC25 WNMG080412-CQ ZC25	0.4 0.8 1.2	2.6 2.6 2.6
	WNMG080404-HQ ZC25 WNMG080408-HQ ZC25	0.4 0.8	2.6 2.6
 R-S L-S	WNMG080404L-S ZC25 WNMG080408L-S ZC25 WNMG080404R-S ZC25 WNMG080408R-S ZC25	0.4 0.8 0.4 0.8	2.6 2.6 2.6 2.6
 R-S L-S	WNMG080404L-S ZC35 WNMG080408L-S ZC35 WNMG080404R-S ZC35 WNMG080408R-S ZC35	0.4 0.8 0.4 0.8	2.6 2.6 2.6 2.6
 TM ZC25 TM ZC35	WNMG080404-TM ZC25 WNMG080408-TM ZC25 WNMG080412-TM ZC25	0.4 0.8 1.2	2.6 2.6 2.6
	WNMG080408-CM ZC25 WNMG080412-CM ZC25	0.8 1.2	2.6 2.6
	WNMG080402-HA ZK01 WNMG080404-HA ZK01 WNMG080408-HA ZK01	0.2 0.4 0.8	2.3 2.3 2.3
	WNMG080404-HA ZM30 WNMG080408-HA ZM30	0.4 0.8	2.6 2.6
	WNMA080404 ZK50 WNMA080408 ZK50	0.4 0.8	2.6 2.6
	WNMG080404 ZK50 WNMG080408 ZK50	0.4 0.8	2.6 2.6

Produkprente	Spesifikasie	R	USD
	WNMG080404-MA ZM30 WNMG080408-MA ZM30	0.4 0.8	2.6 2.6
	WNMG080404-MQ ZM30 WNMG080408-MQ ZM30	0.4 0.8	2.6 2.6
	WNMG080404-MS ZM30 WNMG080408-MS ZM30	0.4 0.8	2.6 2.6
	WNMG080404-HS ZN60 WNMG080408-HS ZN60	0.4 0.8	2.3 2.3
	WNMG080404-HQ ZN60 WNMG080408-HQ ZN60	0.4 0.8	2.3 2.3
 R-S L-S	WNMG080404L-X ZN60 WNMG080408L-X ZN60 WNMG080404R-X ZN60 WNMG080408R-X ZN60	0.4 0.8 0.4 0.8	2.3 2.3 2.3 2.3
	WNMG080404-MT ZN60 WNMG080408-MT ZN60	0.4 0.8	2.3 2.3
	WNMG080404-TS ZN60 WNMG080408-TS ZN60	0.4 0.8	2.3 2.3

Bogenoemde prys sluit vraag, belasting en fooi in.
Binnelandse USD Dollar Transaksieprys In China.
As jy enige vrae het, stuur asb. E-pos: eva@mzgtool.cn

Produkprente	Spesifikasie	TPI	USD
ZP10 General Machining 	16ER 050ISO ZP10	0.50	2.0
	16ER 075ISO ZP10	0.75	2.0
	16ER 100ISO ZP10	1.00	2.0
	16ER 125ISO ZP10	1.25	2.0
	16ER 150ISO ZP10	1.50	2.0
	16ER 175ISO ZP10	1.75	2.0
	16ER 200ISO ZP10	2.00	2.0
	16ER 250ISO ZP10	2.50	2.0
	16ER 300ISO ZP10	3.00	2.0
	16ER 350ISO ZP10	3.50	2.0
	16ER A60 ZP10	0.5-1.5	2.0
	16ER AG60 PCD1	0.5-3.0	6.9
	16ER AG60 ZP10	0.5-3.0	2.0
	16ER G60 ZP10	1.5-3.0	2.0
	22ER 350ISO ZP10	3.50	5.1
PCD1 Koper En Aluminium Voltooi bewerking  60° Metriek Ekerne Draadverwerking	22ER 400ISO ZP10	4.00	5.1
	22ER 500ISO ZP10	5.00	5.1
	22ER 600ISO ZP10	6.00	5.1
	22ER N60 ZP10	3.5-5.0	5.1
	SER1616H16	—	7.1
	SER2020K16	—	7.1
	SER2525M16	—	9.3
	SER2020K22	—	9.6
	SER2525M22	—	13.1
	SER3232P22	—	20.3
	B-SEL1212H16	—	9.6
	B-SEL1616H16	—	9.6
	B-SEL2020K16	—	9.6
	B-SEL2525M16	—	13.1
	Eksterne draad verwerking		
ZP10 General Machining 	06IR A60 ZP10	0.5-1.25	4.7
	08IR 150ISO ZP10	1.50	4.1
	08IR A60 ZP10	0.5-1.5	4.1
	11IR 150ISO ZP10	1.5	2.0
	11IR 200ISO ZP10	2.0	2.0
	11IR A60 ZP10	0.5-1.5	2.0
	16IR 050ISO ZP10	0.50	2.0
	16IR 075ISO ZP10	0.75	2.0
	16IR 100ISO ZP10	1.00	2.0
	16IR 125ISO ZP10	1.25	2.0
	16IR 150ISO ZP10	1.50	2.0
	16IR 175ISO ZP10	1.75	2.0
	16IR 200ISO ZP10	2.00	2.0
	16IR 250ISO ZP10	2.50	2.0
	16IR 300ISO ZP10	3.00	2.0
PCD1 Koper En Aluminium Voltooi bewerking  60° Metriek Interne Gat Draadverwerking	16IR 350ISO ZP10	3.50	2.0
	16IR A60 ZP10	0.5-1.5	2.0
	16IR AG60 PCD1	0.5-3.0	6.9
	16IR AG60 ZP10	0.5-3.0	2.0
	16IR G60 ZP10	1.5-3.0	2.0
	22IR 350ISO ZP10	3.50	5.1
	22IR 400ISO ZP10	4.00	5.1
	22IR 500ISO ZP10	5.00	5.1
	22IR 600ISO ZP10	6.00	5.1
	22IR N60 ZP10	3.5-5.0	5.1
	SNR0005K06-A12	—	7.1
	SNR0007J08	—	5.1
	SNR0008K08	—	5.1
	SNR0010K11	—	5.1
	SNR0012M11	—	5.4
TKFT.. TTP.. Verwerking van 60 Metriek Onderwerp Klein Onderdele 	SNR0013N16	—	6.1
	SNR0014N16	—	6.7
	SNR0016Q16	—	6.7
	SNR0020R16	—	7.1
	SNR0025S16	—	11.7
	SNR0032T16	—	20.3
	SNR0020R22	—	10.7
	SNR0025S22	—	14.3
	SNR0032T22	—	22.9
	Interne Gat Draadverwerking		
	TKFT6001 ZP15	0.5-3.0	5.9
	TTP6001 ZP15	0.5-3.0	5.9
	TTP..		
	TTPR12	—	9.3
	TTPR16	—	11.7



Produkprente	Spesifikasie	TPI	USD
 30° Trapezoidale Drade vir DIN103 Transmissie Eksterne draadverwerking	16ER 2TR ZP10	2.0	2.0
	16ER 3TR ZP10	3.0	2.0
 30° Trapezoidale Drade vir DIN103 Transmissie Interne Hole onderwerp verwerking	16IR 2TR ZP10	2.0	2.0
	16IR 3TR ZP10	3.0	2.0
ZP10 General Machining 	16ER 11W ZP10	1 1/16 11Tooth	2.0
	16ER 14W ZP10	1 1/16 14Tooth	2.0
	16ER 19W ZP10	1 1/16 19Tooth	2.0
	16ER 24W ZP10	1 1/16 24Tooth	2.0
	16ER 8W ZP10	1 1/8 8Tooth	2.0
	16ER A55 ZP10	0.5-1.5	2.0
	16ER AG55 PCD1	0.5-3.0	6.9
	16ER AG55 ZP10	0.5-3.0	2.0
	16ER G55 ZP10	1.5-3.0	2.0
	22ER N55 ZP10	3.5-5.0	5.1
	PCD1 Koper En Aluminium Voltooi bewerking 		
	55° Inch Eksterne Draadverwerking		
	ZP10 General Machining 		
	06IR A55 ZP10	0.5-1.25	4.7
	08IR A55 ZP10	0.5-1.5	4.1
PCD1 Koper En Aluminium Voltooi bewerking  55° Inch Interne Gat Draadverwerking	11IR 19W ZP10	1 1/16 19Tooth	2.0
	16IR 11W ZP10	1 1/16 11Tooth	2.0
	16IR 12W ZC01	1 1/16 12Tooth	2.0
	16IR 14W ZP10	1 1/16 14Tooth	2.0
	16IR 19W ZP10	1 1/16 19Tooth	2.0
	16IR A55 ZP10	0.5-1.5	2.0
	16IR AG55 PCD1	0.5-3.0	6.9
	16IR AG55 ZP10	0.5-3.0	2.0
	16IR G55 ZP10	1.5-3.0	2.0
	22IR N55 ZP10	3.5-5.0	5.1
	55° Inch Eksterne Draadverwerking		
	 60° Amerikaanse Eksterne Draadverwerking		
	16ER 12UN ZP10	1 1/16 12Tooth	2.0
	16ER 14UN ZP10	1 1/16 14Tooth	2.0
	16ER 16UN ZP10	1 1/16 16Tooth	2.0
 60° Amerikaanse Interne Gat Draadverwerking	16ER 18UN ZP10	1 1/16 18Tooth	2.0
	16ER 20UN ZP10	1 1/16 20Tooth	2.0
	16IR 12UN ZP10	1 1/16 12Tooth	2.0
	16IR 14UN ZP10	1 1/16 14Tooth	2.0
	16IR 16UN ZP10	1 1/16 16Tooth	2.0
	16IR 18UN ZP10	1 1/16 18Tooth	2.0
	16IR 20UN ZP10	1 1/16 20Tooth	2.0
	BSPT Britse Standard Taper Tube Onderwerp eksterne onderwerp verwerking 		
	16ER 11BSPT ZP10	1 1/16 11Tooth	2.0
	16ER 14BSPT ZP10	1 1/16 14Tooth	2.0
	16ER 19BSPT ZP10	1 1/16 19Tooth	2.0
	16ER 28BSPT ZP10	1 1/16 28Tooth	2.0
	BSPT Britse Standard Taper Tube Draa Interne Hole onderwerp verwerking 		
	16IR 11BSPT ZP10	1 1/16 11Tooth	2.0
	16IR 14BSPT ZP10	1 1/16 14Tooth	2.0
 NPT-buisdraad Eksterne draad verwerking	16ER 11.5NPT ZP10	1 1/16 11.5Tooth	2.0
	16ER 14NPT ZP10	1 1/16 14Tooth	2.0
	16ER 18NPT ZP10	1 1/16 18Tooth	2.0
	NPT-buisdraad Interne Gat Draadverwerking 		
	16IR 11.5NPT ZP10	1 1/16 11.5Tooth	2.0
	16IR 14NPT ZP10	1 1/16 14Tooth	2.0


Bogenoemde prys sluit vrag, belasting en fooi in.

Binnelandse USD Dollar Transaksieprys In China.

As jy enige vrae het, stuur asb. E-pos: eva@mzgtool.cn

<http://www.mzg.tw>

Produkprente	Spesifikasie	Width	USD
	T16E100 ZP15	1.0	3.0
	T16E150 ZP15	1.5	3.0
	T16E160 ZP15	1.6	3.0
	T16E200 ZP15	2.0	3.0
	T16E250 ZP15	2.5	3.0
	T16E300 ZP15	3.0	3.0
Inventarisgrootte breedte 0.5-3 mm en diepte 1-2.2 mm Algemene materiaal kan dwarssny gesny word			
	SER1616H16	—	7.1
	SER2020K16	—	7.1
	SER2525M16	—	9.3
	T11N100 ZP15	1.0	3.0
	T11N150 ZP15	1.5	3.0
	T11N200 ZP15	2.0	3.0
	T16N100 ZP15	1.0	3.0
	T16N150 ZP15	1.5	3.0
	T16N160 ZP15	1.6	3.0
	T16N180 ZP15	1.8	3.0
	T16N200 ZP15	2.0	3.0
	T16N230 ZP15	2.3	3.0
	T16N250 ZP15	2.5	3.0
Inventarisgrootte breedte 0.5-3 mm en diepte 1-2.2 mm Algemene materiaal kan dwarssny gesny word			
	SNR0010K11	—	5.1
	SNR0012M11	—	5.4
	SNR0013N16	—	6.1
	SNR0014N16	—	6.7
	SNR0016Q16	—	6.7
	SNR0020R16	—	7.1
	SNR0025S16	—	11.7
	CTP10FR ZP15	1.0	5.9
	CTP15FR ZP15	1.5	5.9
	CTP20FR ZP15	2.0	5.9
	CTPA10FR ZP15	1.0	6.6
	CTPA15FR ZP15	1.5	6.6
	CTPA20FR ZP15	2.0	6.6
	CTP10FRN ZP15	1.0	5.9
	CTP15FRN ZP15	1.5	5.9
	CTP20FRN ZP15	2.0	5.9
	CTPA10FRN ZP15	1.0	6.6
	CTPA15FRN ZP15	1.5	6.6
	CTPA20FRN ZP15	2.0	6.6
	CTPSL10	—	10.7
	CTPSL12	—	11.9
	CTPASL10	—	10.7
	CTPASL12	—	11.9
	CTPR08	—	11.9
	CTPR10	—	9.4
	CTPR12	—	9.4
	CTPR16	—	9.4
	CTPR20	—	10.7
	CTPAR10	—	9.4
	CTPAR12	—	9.4
	CTPAR16	—	9.4
	CTPAR20	—	10.7
	CTPAR25	—	14.3
	TTB6001 ZP15	—	5.9
	TTB6001 ZP15	—	5.9
	TBPR10	—	9.4
	TBPR12	—	9.4
	TBPAR10	—	9.4
	TBPAR12	—	9.4
	TBPAR16	—	9.4
	TBPAR16	—	9.4

Produkprente	Spesifikasie	Width	USD
	TKF12R100-S ZP15	1.0	5.9
	TKF12R150-S ZP15	1.5	5.9
	TKF12R200-S ZP15	2.0	5.9
	TKF16R100-S ZP15	1.0	6.6
	TKF16R150-S ZP15	1.5	6.6
	TKF16R200-S ZP15	2.0	6.6
Klein Onderdele Grooving /Afsnyverwerking			
	TKF12R100-S16R ZP15	1.0	5.9
	TKF12R150-S16R ZP15	1.5	5.9
	TKF12R200-S16R ZP15	2.0	5.9
	TKF16R100-S16R ZP15	1.0	6.6
	TKF16R150-S16R ZP15	1.5	6.6
	TKF16R200-S16R ZP15	2.0	6.6
Klein Onderdele Afsnyverwerking			
	TKFB6001 ZP15	—	5.9
	TKFB6001 ZP15	—	5.9
Terug Draai van Klein Onderdele			
	KTKFSL1010JX12	—	11.9
	KTKFSL1212JX12	—	11.9
	KTKFSL1212JX16	—	11.9
	KTKFSL1212JX16	—	11.9
KTKFSL..			
	KTKFR0810JX12	—	11.9
	KTKFR1010JX12	—	9.4
	KTKFR1212JX12	—	9.4
	KTKFR1616JX12	—	9.4
	KTKFR1010JX16	—	9.4
	KTKFR1212JX16	—	9.4
	KTKFR1616K16	—	9.4
	KTKFR2020JX16	—	10.7
	KTKFR2020JX16	—	10.7
	KTKFR2020JX16	—	10.7
	KTKFR2020JX16	—	10.7
	KTKFR2020JX16	—	10.7
	FVC1604R150 ZP15	1.5	4.3
	FVC1604R200 ZP15	2.0	4.3
	FV1604R300 ZP15	3.0	4.3
	FV1604R300 ZP15	3.0	4.3
End Face Grooving Machining			
	SVQCR2020K16-NJ	—	11.9
	SVQCR2020K16-NJ	—	11.9
SVQCR..			
	VC1604R250 ZP15	2.5	4.3
	VC1604R300 ZP15	3.0	4.3
End Face Grooving Machining			
	SGIVFR16Q16	—	14.3
	SGIVFR20Q16	—	14.3
	SGIVFR25R16	—	16.7
	SGIVFR25R16	—	16.7
SGIVFR..			

Produkprente	Spesifikasie	Width	USD
	TGF32R050 ZP15	0.5	2.6
	TGF32R080 ZP15	0.8	2.6
	TGF32R100 ZP15	1.0	2.6
	TGF32R110 ZP15	1.1	2.6
	TGF32R120 ZP15	1.2	2.6
	TGF32R125 ZP15	1.25	2.6
	TGF32R130 ZP15	1.3	2.6
	TGF32R140 ZP15	1.4	2.6
	TGF32R150 ZP15	1.5	2.6
	TGF32R160 ZP15	1.6	2.6
	TGF32R170 ZP15	1.7	2.6
	TGF32R180 ZP15	1.8	2.6
	TGF32R190 ZP15	1.9	2.6
	TGF32R200 ZP15	2.0	2.6
	TGF32R210 ZP15	2.1	2.6
	TGF32R220 ZP15	2.2	2.6
	TGF32R230 ZP15	2.3	2.6
	TGF32R250 ZP15	2.5	2.6
	TGF32R260 ZP15	2.6	2.6
	TGF32R270 ZP15	2.7	2.6
	TGF32R280 ZP15	2.8	2.6
	TGF32R290 ZP15	2.9	2.6
	TGF32R300 ZP15	3.0	2.6


Inventarisgrootte breedte 0.3-3.2mm
Selektiewe snydiepte 0.8-4 mm
Algemene materiaal kan word dwarsnsy gesny

Produkprente	Spesifikasie	Width	USD
	TGF32L050 ZP15	0.5	2.6
	TGF32L080 ZP15	0.8	2.6
	TGF32L100 ZP15	1.0	2.6
	TGF32L110 ZP15	1.1	2.6
	TGF32L120 ZP15	1.2	2.6
	TGF32L125 ZP15	1.25	2.6
	TGF32L130 ZP15	1.3	2.6
	TGF32L140 ZP15	1.4	2.6
	TGF32L150 ZP15	1.5	2.6
	TGF32L160 ZP15	1.6	2.6
	TGF32L170 ZP15	1.7	2.6
	TGF32L180 ZP15	1.8	2.6
	TGF32L190 ZP15	1.9	2.6
	TGF32L200 ZP15	2.0	2.6
	TGF32L210 ZP15	2.1	2.6
	TGF32L220 ZP15	2.2	2.6
	TGF32L230 ZP15	2.3	2.6
	TGF32L250 ZP15	2.5	2.6
	TGF32L260 ZP15	2.6	2.6
	TGF32L270 ZP15	2.7	2.6
	TGF32L280 ZP15	2.8	2.6
	TGF32L290 ZP15	2.9	2.6
	TGF32L300 ZP15	3.0	2.6

Inventarisgrootte breedte 0.3-3.2mm
Selektiewe snydiepte 0.8-4 mm
Algemene materiaal kan word dwarsnsy gesny


	KTGFR1010H16 KTGFR1212H16 KTGFR1616H16 KTGFR2020K16 KTGFR2525M16	— — — — —	6.9 6.9 6.9 6.9 9.0
KTGFR..			

	KTGFL1010H16 KTGFL1212H16 KTGFL1616H16 KTGFL2020K16 KTGFL2525M16	— — — — —	6.9 6.9 6.9 6.9 9.0
KTGFL..			

	KTGFR1010H16F KTGFR1212H16F KTGFR1616H16F KTGFR2020K16F	— — — —	6.7 6.7 6.7 6.7
---	--	------------------	--------------------------

	KTGFL1010H16F KTGFL1212H16F KTGFL1616H16F KTGFL2020K16F	— — — —	6.7 6.7 6.7 6.7
--	--	------------------	--------------------------

	KTGFSL1010H16 KTGFSL1212H16 KTGFSL1616H16 KTGFSL2020K16 KTGFSL2525M16	— — — — —	6.9 6.9 6.9 6.9 9.3
KTGFSL..			

	KTGFSR1010H16 KTGFSR1212H16 KTGFSR1616H16 KTGFSR2020K16 KTGFSR2525M16	— — — — —	6.9 6.9 6.9 6.9 9.3
KTGFSR..			





	S16N-KTGFL16 S20Q-KTGFL16 S25R-KTGFL16	— — —	9.3 11.0 13.1
S..-KTGFL..			




	S16N-KTGFR16 S20Q-KTGFR16 S25R-KTGFR16	— — —	9.3 11.0 13.1
S..-KTGFR..			

Eksterne Cilindriese / Inner Gat Grooving Turning Tool

External Cylindrical/Inner Hole Grooving Turning Tool

MaiFix®

Produkprente	Spesifikasie	Width	USD
	GBA43R250 ZP15 GBA43R300 ZP15 GBA43R350 ZP15 GBA43R400 ZP15 GBA43R450 ZP15	2.5 3.0 3.5 4.0 4.5	6.1 6.1 6.1 6.1 6.1
Inventarisgrootte breedte 1.0-4.8mm Selektiewe snydiepte 2.0-5.0 mm Algemene materiaal kan word dwarssny gesny			
CGBR.. 	CGBR1616H43 CGBR2020K43 CGBR2525M43	— — —	9.3 13.1 16.4
CGBSL.. 	CGBSL2020K43 CGBSL2525M43	— —	12.4 19.0
SGBR.. 	SGBR1616H43 SGBR2020K43 SGBR2525M43	— — —	6.7 6.7 9.0
SGBSL.. 	SGBSL2020K43 SGBSL2525M43	— —	10.7 14.3
	GBA43L250 ZP15 GBA43L300 ZP15 GBA43L350 ZP15 GBA43L400 ZP15 GBA43L450 ZP15	2.5 3.0 3.5 4.0 4.5	6.1 6.1 6.1 6.1 6.1
Inventarisgrootte breedte 1.0-4.8mm Selektiewe snydiepte 2.0-5.0 mm Algemene materiaal kan word dwarssny gesny			
CGBL.. 	CGBL1616H43 CGBL2020K43 CGBL2525M43	— — —	9.3 13.1 16.4
CGBSR.. 	CGBSR2020K43 CGBSR2525M43	— —	12.4 19.0
SGBL.. 	SGBL1616H43 SGBL2020K43 SGBL2525M43	— — —	6.7 6.7 9.0
SGBSR.. 	SGBSR2020K43 SGBSR2525M43	— —	10.7 14.3



Produkprente	Spesifikasie	Width	USD
	GER100-A ZP15 GER150-A ZP15	1.0 1.5	4.7 4.7
Grooving Machining			
	SIGER0606A-EH SIGER0808A-EH Lente Staal SIGER0808A-EHT	— — —	19.0 11.9 11.9
	GER100-B ZP15 GER150-B ZP15 GER200-B ZP15 GER250-B ZP15 GER300-B ZP15	1.0 1.5 2.0 2.5 3.0	4.7 4.7 4.7 4.7 4.7
Grooving Machining			
	SIGER1010B-EH SIGER1210B-EH Lente Staal SIGER1010B-EHT SIGER1210B-EHT	— — — — —	11.9 11.9 11.9 11.9 11.9
	GER100-C ZP15 GER150-C ZP15 GER200-C ZP15 GER250-C ZP15 GER300-C ZP15 GER350-C ZP15	1.0 1.5 2.0 2.5 3.0 3.5	4.7 4.7 4.7 4.7 4.7 4.7
Grooving Machining			
	SIGER1412C-EH SIGER1616C-EH Lente Staal SIGER1412C-EH	— — — —	11.9 13.3 11.9 11.9
	GER100-D ZP15 GER150-D ZP15 GER200-D ZP15 GER250-D ZP15 GER300-D ZP15 GER400-D ZP15	1.0 1.5 2.0 2.5 3.0 4.0	5.1 5.1 5.1 5.1 5.1 5.1
Grooving Machining			
	SIGER2020D-EH SIGER2525D-EH	— —	14.3 16.7
	7GR100 ZP15 7GR150 ZP15 7GR200 ZP15	1.0 1.5 2.0	2.6 2.6 2.6
	SNGR08J07 SNGR10K07 Lente Staal SNGR10K07	— — — —	8.6 8.6 9.6 9.6
Grooving Machining			
	8GR200 ZP15 8GR300 ZP15	2.0 3.0	2.9 2.9
Grooving Machining			
	SNGR10K08 SNGR12M08 Lente Staal SNGR10K08	— — — —	8.6 9.0 11.9 11.9
	9GR100 ZP15 9GR200 ZP15 9GR250 ZP15 9GR300 ZP15	1.0 2.0 2.5 3.0	3.0 3.0 3.0 3.0
Grooving Machining			
	SNGR12M09 SNGR16Q09 SNGR20R09	— — —	9.0 11.0 13.1



Bogenoemde prys sluit vrag, belasting en fooi in.

Binnelandse USD Dollar Transaksieprys In China.

As jy enige vrae het, stuur asb. E-pos: eva@mzgtool.cn

<http://www.mzg.tw>





Produkprente	Spesifikasie	Width	USD
	MGMN150 CBN1	1.5	6.9
	MGMN200 CBN1	2.0	6.9
	MGMN250 CBN1	2.5	6.9
	MGMN300 CBN1	3.0	6.9
	MGMN400 CBN1	4.0	6.9
	MGMN500 CBN1	5.0	6.9
	MGMN150 PCD1	1.5	6.9
	MGMN200 PCD1	2.0	6.9
	MGMN250 PCD1	2.5	6.9
	MGMN300 PCD1	3.0	6.9
	MGMN400 PCD1	4.0	6.9
	MGGN300 ZP15	3.0	1.6
	MGGN400 ZP15	4.0	1.7
	MGGN200-Q ZP15	2.0	1.7
	MGGN300-Q ZP15	3.0	1.7
	MGGN200 ZK01	2.0	1.7
	MGGN300 ZK01	3.0	1.9
	MGGN400 ZK01	4.0	2.3
	MGGN150 ZP30	1.5	1.7
	MGGN200 ZP30	2.0	1.7
	MGGN250 ZP30	2.5	1.7
	MGGN300 ZP30	3.0	1.7
	MGGN400 ZP30	4.0	2.0
	MGGN500 ZP30	5.0	2.7
	MGGN150R-8 ZP30	1.5	1.7
	MGGN200R-8 ZP30	2.0	1.7
	MGGN250R-8 ZP30	2.5	1.9
	MGGN300R-8 ZP30	3.0	2.0
	MGGN400R-8 ZP30	4.0	2.4
	MGGN500R-8 ZP30	5.0	3.1
	MGGN150L-8 ZP30	1.5	1.7
	MGGN200L-8 ZP30	2.0	1.7
	MGGN250L-8 ZP30	2.5	1.9
	MGGN300L-8 ZP30	3.0	2.0
	MGGN400L-8 ZP30	4.0	2.4
	MGMN150-G ZK01	1.5	1.7
	MGMN200-G ZK01	2.0	1.7
	MGMN200-M ZK01	2.0	1.7
	MGMN300-M ZK01	3.0	1.7
	MGMN400-M ZK01	4.0	2.0
	MGMN200-G ZN60	2.0	1.4
	MGMN300-M ZN60	3.0	1.7
	MGMN400-M ZN60	4.0	2.0
	MGMN500-M ZN60	5.0	2.7
	MGMN200-T ZP30	2.0	1.6
	MGMN300-T ZP30	3.0	1.6
	MGMN400-T ZP30	4.0	2.0
	MGMN300-H ZP30	3.0	1.6
	MGMN200-G ZP20	2.0	1.6
	MGMN250-G ZP20	2.5	1.6
	MGMN250-M ZP20	2.5	1.6
	MGMN300-M ZP20	3.0	1.6
	MGMN400-M ZP20	4.0	2.0
	MGMN150-G ZP30	1.5	1.6
	MGMN200-M ZP30	2.0	1.6
	MGMN200-G ZP30	2.0	1.6
	MGMN250-M ZP30	2.5	1.6
	MGMN250-G ZP30	2.5	1.6
	MGMN300-M ZP30	3.0	1.6
	MGMN400-M ZP30	4.0	2.0
	MGMN500-M ZP30	5.0	2.7

Produkprente	Spesifikasie	Width	USD
	MRMN200-G ZP30	R1.0	1.6
	MRMN200-M ZP30	R1.0	1.6
	MRMN300-M ZP30	R1.5	1.6
	MRMN400-M ZP30	R2.0	2.0
	MRMN400 CBN1	R2.0	6.9
	MGEHR1010-1.5	1.5	9.0
	MGEHR1010-2	2.0	9.0
	MGEHR1212-1.5	1.5	9.0
	MGEHR1212-2	2.0	9.0
	MGEHR1212-3	3.0	9.0
	MGEHR1616-1.5	1.5	6.7
	MGEHR1616-2	2.0	6.7
	MGEHR1616-2.5	2.5	6.7
	MGEHR1616-3	3.0	6.7
	MGEHR1616-4	4.0	6.7
	MGEHR2020-1.5	1.5	6.7
	MGEHR2020-2	2.0	6.7
	MGEHR2020-2.5	2.5	6.7
	MGEHR2020-3	3.0	6.7
	MGEHR2020-4	4.0	6.7
	MGEHR2020-5	5.0	6.7
	MGEHR2020-6	6.0	8.3
	MGEHR2525-1.5	1.5	9.0
	MGEHR2525-2	2.0	9.0
	MGEHR2525-2.5	2.5	9.0
	MGEHR2525-3	3.0	9.0
	MGEHR2525-4	4.0	9.0
	MGEHR2525-5	5.0	9.0
	MGEHR2525-6	6.0	10.7
	MGEHR3232-2	2.0	16.4
	MGEHR3232-3	3.0	16.4
	MGEHR3232-4	4.0	16.4
	MGEHR3232-5	5.0	16.4
	MGEHR3232-6	6.0	17.9
	MGEHR1010-1.5T12	1.5	10.7
	MGEHR1010-2T12	2.0	10.7
	MGEHR1212-1.5T12	1.5	9.6
	MGEHR1212-2T12	2.0	9.6
	MGEHR1616-1.5T13	1.5	9.0
	MGEHR1616-2T16	2.0	9.0
	MGEHR1616-2.5T18	2.5	9.0
	MGEHR1616-3T12	3.0	9.0
	MGEHR1616-3T20	3.0	9.0
	MGEHR1616-4T20	4.0	9.0
	MGEHR2020-1.5T13	1.5	9.6
	MGEHR2020-2T16	2.0	9.6
	MGEHR2020-3T20	3.0	9.6
	MGEHR2020-4T20	4.0	9.6
	MGEHR2525-3T20	3.0	11.0
	MGEHR2525-4T20	4.0	11.0
	MGEHL1010-1.5	1.5	9.0
	MGEHL1010-2	2.0	9.0
	MGEHL1212-1.5	1.5	9.0
	MGEHL1212-2	2.0	9.0
	MGEHL1616-1.5	1.5	6.7
	MGEHL1616-2	2.0	6.7
	MGEHL1616-2.5	2.5	6.7
	MGEHL1616-3	3.0	6.7
	MGEHL1616-4	4.0	6.7
	MGEHL2020-1.5	1.5	6.7
	MGEHL2020-2	2.0	6.7
	MGEHL2020-2.5	2.5	6.7
	MGEHL2020-3	3.0	6.7
	MGEHL2020-4	4.0	6.7
	MGEHL2020-5	5.0	6.7
	MGEHL2525-2	2.0	9.0
	MGEHL2525-2.5	2.5	9.0
	MGEHL2525-3	3.0	9.0
	MGEHL2525-4	4.0	9.0
	MGEHL2525-5	5.0	9.0
	MGEHL2525-6	6.0	10.7
	MGEHL3232-3	3.0	16.4
	MGEHL3232-4	4.0	16.4
	MGEHL3232-5	5.0	16.4
	MGEHL3232-6	6.0	17.9

End Face / Inner Hole Grooving Turning Tool

End Face/Inner Hole Grooving Turning Tool

MaiFix®



Produkprente	Spesifikasie	Width	USD
  Verwerking van omsendbrief Grooving on End Face	MGHH320R-35/48	3.0	19.0
	MGHH320R-48/66	3.0	19.0
	MGHH320R-64/100	3.0	19.0
	MGHH320R-98/160	3.0	19.0
	MGHH320R-160/400	3.0	19.0
	MGHH325R-35/48	3.0	28.6
	MGHH325R-48/60	3.0	28.6
	MGHH325R-60/75	3.0	28.6
	MGHH325R-64/100	3.0	28.6
	MGHH325R-100/140	3.0	28.6
	MGHH325R-160/400	3.0	28.6
	MGHH325R-200/800	3.0	28.6
	MGHH420R-48/60	4.0	19.0
	MGHH420R-60/75	4.0	19.0
	MGHH420R-64/100	4.0	19.0
	MGHH420R-98/160	4.0	19.0
	MGHH420R-160/400	4.0	19.0
	MGHH425R-48/66	4.0	28.6
	MGHH425R-64/100	4.0	28.6
	MGHH425R-100/140	4.0	28.6
	MGHH425R-160/400	4.0	28.6
	MGHH425R-200/800	4.0	28.6
  Verwerking van omsendbrief Grooving on End Face	MGHH320R13-30/50	3.0	21.9
	MGHH320R15-50/80	3.0	21.9
	MGHH320R17-80/160	3.0	21.9
	MGHH320R18-160/400	3.0	21.9
	MGHH325R18-160/400	3.0	23.9
	MGHH420R15-30/50	4.0	21.9
	MGHH420R18-50/80	4.0	21.9
	MGHH420R20-80/160	4.0	21.9
	MGHH425R15-30/50	4.0	23.9
	MGHH425R18-50/80	4.0	23.9
  Verwerking van omsendbrief Grooving on End Face	MFH216R08-20/140	2.0	16.7
	MFH320R10-25/140	3.0	21.4
	MFH325R10-25/140	3.0	24.6
	MFH420R12-25/140	4.0	21.4
	MFH425R08-25/140	4.0	24.6
	MFH425R10-25/140	4.0	24.6
 Silindriese Grooving	MGEVR1616-2	2.0	8.6
	MGEVR1616-2.5	2.5	8.6
	MGEVR1616-3	3.0	8.6
	MGEVR1616-4	4.0	8.6
	MGEVR2020-2	2.0	8.6
	MGEVR2020-2.5	2.5	8.6
	MGEVR2020-3	3.0	8.6
	MGEVR2020-4	4.0	8.6
 Silindriese Grooving	MGEVL1616-2	2.0	8.6
	MGEVL1616-2.5	2.5	8.6
	MGEVL1616-3	3.0	8.6
	MGEVL1616-4	4.0	8.6
	MGEVL2020-2	2.0	8.6
	MGEVL2020-2.5	2.5	8.6
	MGEVL2020-3	3.0	8.6
	MGEVL2020-4	4.0	8.6
	MGEVL2525-3	3.0	11.0





Produkprente	Spesifikasie	Width	USD
 Machining van Inner Hole Grooving	MGIVR2016-1.5	1.5	9.3
	MGIVR2016-2	2.0	9.3
	MGIVR2016-2.5	2.5	9.3
	MGIVR2016-3	3.0	9.3
	MGIVR2520-1.5	1.5	11.0
	MGIVR2520-2	2.0	11.0
	MGIVR2520-2.5	2.5	11.0
	MGIVR2520-3	3.0	11.0
	MGIVR2520-4	4.0	11.0
	MGIVR3125-1.5	1.5	13.1
	MGIVR2925-2	2.0	13.1
	MGIVR3125-3	3.0	13.1
	MGIVR3125-4	4.0	13.1
	MGIVR3125-5	5.0	13.1
	MGIVR3732-3	3.0	26.1
	MGIVR3732-4	4.0	26.1
	MGIVR3732-5	5.0	26.1
 Machining van Inner Hole Grooving	MGIVR2520-3T8	3.0	15.4
	MGIVR2520-4T8	4.0	15.4
 Machining van Inner Hole Grooving	MGIVL2016-1.5	1.5	9.3
	MGIVL2016-2	2.0	9.3
	MGIVL2016-2.5	2.5	9.3
	MGIVL2016-3	3.0	9.3
	MGIVL2316-3	3.0	9.3
	MGIVL2520-1.5	1.5	11.0
	MGIVL2520-2	2.0	11.0
	MGIVL2520-2.5	2.5	11.0
	MGIVL2520-3	3.0	11.0
	MGIVL2520-4	4.0	11.0
	MGIVL2925-2	2.0	13.1
	MGIVL3125-3	3.0	13.1
	MGIVL3125-4	4.0	13.1
	MGIVL3125-5	5.0	13.1
	MGIVL3732-3	3.0	26.1
	MGIVL3732-4	4.0	26.1
	MGIVL3732-5	5.0	26.1

Bogenoemde prys sluit vrag, belasting en fooi in.
Binnelandse USD Dollar Transaksieprys In China.
As jy enige vrae het, stuur asb. E-pos: eva@mzgtool.cn

<http://www.mzg.tw>

Produkprente	Size	USD
	1010E	5.4
	1212F	5.3
	1616H	5.4
	2020K	6.0
	2525M	8.3
	3232P	14.7
	4040R	21.9
	1616H	6.7
	2020K	6.7
	2525M	8.6
	3232P	14.7
	4040R	29.0
	1616H	6.7
	2020K	6.7
	2525M	8.6
	3232P	16.4
	4040R	32.4
	1616H	9.3
	2020K	9.3
	2525M	11.0
	3232P	14.6
	4040R	36.0
	S06K	5.4
	S07K	4.6
	S08K	4.6
	S10K	4.6
	S12M	5.0
	S14N	5.4
	S16Q	5.7
	S18Q	6.4
	S20R	6.4
	S25S	9.7
	S32T	14.6
	S40U	25.4
	Lente Staal	
	S07	5.4
	S08	5.4
	S10	5.4
	S12	6.9
	S16	8.6
	S20	9.7
	Lente Staal	
	S06	14.6
	S07	14.6
	S08	14.6
	S10	16.4
	S12	18.1
	S14	20.0
	S16	21.7
	S18	34.6
	S20	43.6
	S25	65.0
	C04G	19.0
	C05G	19.0
	C06J	19.0
	C07K	19.0
	C08K	22.6
	C10K	26.1
	C12M	33.3
	C14N	52.4
	C16Q	69.0
	C18Q	81.0
	C20R	95.3
	C25S	204.7
	C32T	452.4
	Gesementeerde Carbide	
	S16Q	8.3
	S20R	8.6
	S25S	11.0
	S32T	16.4
	S40T/U	28.9
	S50V	72.1
	S..M.. Tik Inner Hole Lathe Tool	


Produkprente	Size	USD
	1616H	6.4
	2020K	6.4
	2525M	8.9
	3232P	16.4
	ZQ.. Tik afsny-draai-instrument	
	SPB226	11.9
	SPB326	11.9
	SPB426	11.9
	SPB232	14.3
	SPB332	14.3
	SPB432	14.3
	1616	22.6
	2020	22.6
	2525	22.6
	3232	29.7
	SLTBN..	
	1010	7.1
	1212	7.1
	1616	6.4
	2020	6.4
	2525	8.9
	1010	9.6
	1212	9.6
	1616	8.9
	2020	9.6
	2525	11.0
	1616	8.6
	2020	8.6
	2525	11.0
	MGMN..	
	MGEVR/L.. Tik Afsny /Grooving Turning Tool	
	16	9.3
	20	11.0
	25	13.1
	32	25.7
	40	54.3
	1616H	9.6
	2020K	10.7
	CGWSR/L.. Tik Afsny /Grooving Turning Tool	
	WGE..	
	Lente Staal	
	1616	10.3
	2020	10.3
	2525	11.9
	GY2M..	
	GYHR/L.. Tik Afsny /Grooving Turning Tool	
	1010	10.3
	1212	10.3
	1616	9.3
	2020	11.0
	2525	12.9
	3232	20.0
	GMN.. GMG..	
	1010	10.3
	1212	10.3
	1616	9.3
	2020	11.0
	2525	12.9
	3232	20.0
	TDC.. TDJ..	
	16	14.3
	20	16.7
	25	19.0
	TTIR/L.. Type Inner Hole Grooving Turning Tool	
	TDC.. TDJ..	

Produkprente	Size	USD
	1010	6.7
	1212	6.7
	1616	6.7
	2020	6.7
	2525	9.0
	KTGFR/L.. Tik Grooving Turning Tool	
	1010	11.9
	1212	11.9
	1616	11.9
	2020	13.1
	2525	15.4
	Lente Staal	
	1010	7.1
	1212	7.1
	1616	7.1
	2020	7.1
	2525	9.3
	1616	6.7
	2020	6.7
	2525	8.9
	GBA..	
	KTGFR/L.. Tik Grooving Turning Tool	
	1616	9.0
	2020	9.0
	2525	11.9
	GBA..	
	KTGFR/L.. Tik Grooving Turning Tool	
	1616	9.3
	2020	13.1
	2525	16.4
	3232	21.9
	GBA..	
	1616	11.9
	2020	14.3
	2525	17.9
	GBA..	
	KTGFR/L.. Tik Grooving Turning Tool	
	1616H	9.3
	2020K	11.0
	2525M	12.6
	3232P	20.0
	KTGFR/L.. Tik Grooving Turning Tool	
	1616	15.3
	2020	16.9
	2525	20.4
	DGN..	
	KTGFR/L.. Tik Grooving Turning Tool	
	1616	28.6
	2020	28.6
	2525	32.4
	FMN..	
	KTGFR/L.. Tik Grooving Turning Tool	
	1616	35.7
	2020	38.1
	2525	42.9
	ZT..	
	KTGFR/L.. Tik Grooving Turning Tool	
	1616	23.9
	2020	21.9
	2525	23.9
	MGMN..	
	KTGFR/L.. Tik Grooving Turning Tool	

Produkprente	Size	USD
	MC0903 MC1204 MC1604 MC1904	0.4 0.6 1.1 1.6
C-Tik Shim		
	MD1103 MD1504 MD1506	0.4 1.0 1.1
D-Tik Shim		
	MS0903 MS1204 MS1504 MS1904	0.6 0.6 1.1 1.6
S-Tik Shim		
	MT1603 MT1604 MT2204	0.3 1.1 1.1
T-Tik Shim		
	MV1603	0.6
V-Tik Shim		
	MW0603 MW0804	0.4 0.6
W-Tik Shim		
	STM16R STM16L STM22R STM22L	0.3 0.3 1.0 1.0
STM-Tik Shim		
	CTM510 CTM513 CTM613 CTM617 CTM619 CTM515-T CTM618-W CTM0822 CTM0822 CTM1022 CTM1022	0.2 0.2 0.2 0.2 0.2 0.2 0.2 0.3 0.7 0.3 0.3 0.7
Middelpuntskroef		
	M2. 0X5 M2. 2X5 M2. 5X5 M2. 5X6 M2. 5X8 M3. 0X8 M3. 5X10 M3. 5X12 M4. 0X8 M4. 0X10 M4. 5X12 M5. 0X10 M5. 0X12	0.1 0.1 0.1 0.1 0.1 0.1 0.1 0.1 0.1 0.1 0.1 0.1 0.1
Plum Blossom Tool Skroef		

Produkprente	Size	USD
	HL1810 HL1814 HL1917 HL2114 HL2217 HL2217 HL2414	0.4 0.4 0.4 0.4 0.4 1.0 0.4
M-Tipe Klem		
	ML520 ML620 ML625 ML630 ML830	0.3 0.3 0.3 0.3 0.8
M-Tipe klemskroef		
	WT16 WW08	0.4 0.4
W-Tipe Klem		
	WC0525E WC0625E	0.4 0.4
W-Tipe klemskroef		
	DC12 DD15 DT16 DV16 DW08	1.0 1.0 1.0 1.0 1.0
D-Tipe Klem		
	DL525 DL625	0.7 0.7
D-Tipe klemskroef		
	DDC12 DDD15 DDT16 DDV16 DDW08	0.5 0.5 0.5 0.5 0.5
D-Tik Shim Screw		
	L1.5 L2.0 L2.5 L3.0 L4.0 L5.0	0.2 0.2 0.2 0.2 0.2 0.3
L-Tik Inner Seshoek-spanner		
	TL1.5 TL2.0 TL2.5 TL3.0 TL4.0 TL5.0	1.0 1.0 1.0 1.0 1.0 1.0
T-Tik Inner Seshoek-spanner		
	T6 T7 T8 T10 T15 T20	0.2 0.2 0.2 0.2 0.2 0.2
Vlagvormige Varkskroef		
	T6 T7 T8 T10 T15 T20	0.8 0.8 0.8 0.8 0.8 0.8
Vlagvormige Varkskroef		
	TT6 TT7 TT8 TT10 TT15 TT20	1.0 1.0 1.0 1.0 1.0 1.0
T-tipe Pruimensleutel		

Bogenoemde prys sluit vraag, belasting en fooi in.
Binnelandse USD Dollar Transaksieprys In China.
As jy enige vrae het, stuur asb. E-pos: eva@mzgtool.cn


Produkprente	Spesifikasie	R	USD
	APKT113502 CBN1 APKT113504 CBN1 APKT113508 CBN1	0.2 0.4 0.8	6.9 6.9 6.9
Afwerking van Gietyster en verharde materiale			
	APKT160402 CBN1 APKT160404 CBN1 APKT160408 CBN1	0.2 0.4 0.8	6.9 6.9 6.9
Afwerking van Gietyster en verharde materiale			
	APKT113502 PCD1 APKT113504 PCD1 APKT113508 PCD1	0.2 0.4 0.8	6.9 6.9 6.9
Afwerking van Copper and Aluminum			
	APKT160402 PCD1 APKT160404 PCD1 APKT160408 PCD1	0.2 0.4 0.8	6.9 6.9 6.9
Afwerking van Copper and Aluminum			
	APKT1135PDER-AL ZK01 APKT1604PDER-G2 ZK01	0.8 0.8	1.4 1.9
Medium Afwerking van Copper and Aluminum			
	APKT1604-AL ZK01	0.2	1.9
Afwerking van Copper and Aluminum			
	APMT1135-TG ZN60 APMT1604-TG ZN60	0.8 0.8	1.4 1.9
Cermet Medium En Fyn Staal Onderdele het goeie afwerking			
	APMT1135PDER-M2 ZP25 APMT1604PDER-M2 ZP25	0.8 0.8	1.1 1.9
Medium afwerking			
	APMT1135PDER-H2 ZP25 APMT1604PDER-H2 ZP25	0.8 0.8	1.1 1.9
Medium Rough Machining			
	APMT1135PDER-XM ZP25 APMT1604PDER-XM ZP25	0.8 0.8	1.1 1.9
Verwerking in Algemene Materiaal			
	APMT1135PDER ZM90 APMT1604PDER ZM90	0.8 0.8	2.0 2.7
Spiraal-Edged Tungsten Staal Reamer			
	APMT1135PDER ZP20 APMT1604PDER ZP20	0.8 0.8	1.6 2.3
Verwerking in Algemene Materiaal			
	APMT1135PDER ZP30 APMT1604PDER ZP30	0.8 0.8	1.6 2.3
Verwerking in Algemene Materiaal			
	APMT1135PDER ZP60 APMT1604PDER ZP60	0.8 0.8	1.4 1.7
Verwerking in Algemene Materiaal			

Vergrendelende Tand Tipe Reghoekige Einde Myl Snyder
Locking Tooth Type Right-Angle End Milling Cutter



Spesifikasie D x T x M	prys USD
BAP3-11-1T-M5	23.9
BAP3-13-1T-M6	23.9
BAP3-15-2T-M8	23.9
BAP3-16-2T-M8	28.6
BAP3-17-2T-M8	28.6
BAP3-20-2T-M10	31.0
BAP3-21-2T-M10	31.0
BAP3-25-3T-M12	33.3
BAP3-25-4T-M12	35.7
BAP3-26-2T-M12	33.3
BAP3-26-3T-M12	33.3
BAP3-26-4T-M12	35.7
BAP4-25-2T-M12	33.3
BAP4-26-2T-M12	33.3
BAP4-30-2T-M16	38.1
BAP4-30-3T-M16	40.4
BAP4-32-2T-M16	38.1
BAP4-32-3T-M16	40.4
BAP4-35-3T-M16	42.9

BAP Steel Right-Angle
Einde Myl Snyder
BAP Steel Right-Angle
End Milling Cutter



Spesifikasie D x d x T	prys USD
BAP300R 40-22-4T	11.9
BAP300R 50-22-4T	15.3
BAP300R 63-22-6T	20.4
BAP400R 40-22-3T	10.3
BAP400R 50-22-4T	10.3
BAP400R 63-22-4T	11.9
BAP400R 80-27-6T	20.4
BAP400R 100-32-6T	32.4
BAP400R 125-40-7T	51.0
BAP400R 160-40-8T	61.1
BAP400R 200-40-10T	119.0
BAP400R 250-40-12T	187.1
BAP400R 300-60-14T	238.1
BAP400R 50-25.4-4T	11.9
BAP400R 63-25.4-4T	15.3
BAP400R 80-25.4-6T	23.9
BAP400R 100-31.75-6T	35.7

AL-BAP Aluminium Reghoekige Einde Maal Snyder
AL-BAP Aluminum Right-Angle End Milling Cutter



Spesifikasie D x d x T	prys USD
AL-BAP400R 50-22-4T	16.9
AL-BAP400R 63-22-4T	22.1
AL-BAP400R 80-22-6T	30.7
AL-BAP400R 100-22-6T	54.6
AL-BAP400R 125-27-7T	85.0
AL-BAP400R 160-27-8T	95.3
AL-BAP400R 200-27-10T	204.0
AL-BAP400R 250-32-12T	272.1
AL-BAP400R 300-32-14T	340.3

Weggooide Gereedschap vir regte hoeke
Discarded Right-Angle End Milling Cutter Toolholder



Spesifikasie d x D x L	prys USD
BAP300R C10-10-120-1T	3.3
BAP300R C10-11-120-1T	3.3
BAP300R C12-12-130-1T	3.3
BAP300R C12-13-130-1T	3.3
BAP300R C14-14-130-2T	4.6
BAP300R C14-14-150-2T	4.6
BAP300R C15-15-150-2T	4.6
BAP300R C15-15-200-2T	5.4
BAP300R C15-16-150-2T	4.6
BAP300R C15-16-200-2T	5.4
BAP300R C15.6-16-150-2T	4.6
BAP300R C15.6-16-200-2T	5.4
BAP300R C16-16-120-2T	4.6
BAP300R C16-16-150-2T	4.6
BAP300R C16-16-200-2T	5.4
BAP300R C16-16-250-2T	9.6
BAP300R C16-17-120-2T	4.6
BAP300R C16-17-150-2T	4.6
BAP300R C16-17-200-2T	5.4
BAP300R C16-17-250-2T	9.6
BAP300R C16-18-150-2T	5.4
BAP300R C16-18-200-2T	6.1
BAP300R C19-20-150-2T	5.4
BAP300R C19-20-200-2T	6.1
BAP300R C20-20-120-2T	5.4
BAP300R C20-20-150-2T	5.4
BAP300R C20-20-200-2T	6.1
BAP300R C20-20-250-2T	9.6
BAP300R C20-21-120-2T	5.4
BAP300R C20-21-150-2T	5.4
BAP300R C20-21-200-2T	6.1
BAP300R C20-21-250-2T	9.6
BAP300R C24-25-150-3T	10.3
BAP300R C24-25-200-3T	11.9
BAP300R C24-25-250-3T	14.3
BAP300R C24-25-300-3T	20.4
BAP300R C25-25-150-3T	10.3
BAP300R C25-25-200-3T	11.9
BAP300R C25-25-250-3T	14.3
BAP300R C25-25-300-3T	20.4
BAP300R C25-25-150-2T	7.4
BAP300R C25-25-200-2T	8.9
BAP300R C25-25-250-2T	11.9
BAP300R C25-25-300-2T	19.0
BAP400R C24-25-150-2T	7.9
BAP400R C24-25-200-2T	9.6
BAP400R C24-25-250-2T	11.9
BAP400R C24-25-300-2T	19.0
BAP400R C25-25-150-2T	7.9
BAP400R C25-25-200-2T	9.6
BAP400R C25-25-250-2T	11.9
BAP400R C25-25-300-2T	19.0
BAP400R C25-26-150-2T	7.9
BAP400R C25-26-200-2T	9.6
BAP400R C25-26-250-2T	11.9
BAP400R C25-26-300-2T	19.0
BAP400R C25-30-150-2T	10.3
BAP400R C25-30-200-2T	11.9
BAP400R C25-30-250-2T	16.9
BAP400R C25-30-300-2T	20.4
BAP400R C32-32-150-3T	13.6
BAP400R C32-32-200-3T	15.3
BAP400R C32-32-250-3T	18.9
BAP400R C32-32-300-3T	23.9
BAP400R C32-32-350-3T	27.1
BAP400R C32-32-400-3T	35.7
BAP400R C32-35-150-3T	13.6
BAP400R C32-35-200-3T	15.3
BAP400R C32-35-250-3T	19.7
BAP400R C32-35-300-3T	23.9
BAP400R C32-35-350-3T	27.1
BAP400R C32-35-400-3T	35.7
BAP400R C32-40-150-3T	15.3
BAP400R C32-40-200-3T	17.6
BAP400R C32-40-250-3T	22.1
BAP400R C32-40-300-3T	25.4
BAP400R C32-40-350-3T	30.7
BAP400R C32-40-400-3T	39.0
BAP400R C32-50-150-4T	22.1
BAP400R C32-50-200-4T	27.1




Bogenoemde prys sluit vraag, belasting en fooi in.
Binnelandse USD Dollar Transaksieprys In China.
As jy enige vrae het, stuur asb. E-pos: eva@mzgtool.cn

<http://www.mzg.tw>

Machine-Clamped Ronde Neus Milling Snyer

Machine-Clamped Round Nose Milling Cutter

MaiFix®


Produkprente	Spesifikasie	R	prys
	RDMW1204MOT-PM ZP30	R6	1.7
Verwerking in Algemene Materiaal	RDMW1605MOT-PM ZP30	R8	2.4
	RPGT1003-AL ZK01	R5	1.9
Medium Afwerking van Copper and Aluminum			
	RPMW1003MO ZN60	R5	1.6
Cermet Medium En Fyn Staal Onderdele het goeie afwerking	RPMW1003 ZN60 Non Chamfering	R5	1.3
	RPMT1204MO ZN60	R6	1.9
	RPMT08T2-JS ZP25	R4	1.1
Verwerking in Algemene Materiaal	RPMT10T3-JS ZP25	R5	1.4
	RPMT1204MO ZM90	R6	2.0
Spiraal-Edged Tungsten Staal Reamer			
	RPMT1204MO ZP30	R6	1.7
Verwerking in Algemene Materiaal			
	RPMT1204MO ZP60	R6	1.7
Verwerking in Algemene Materiaal			
	RPMT1204-XM ZP25	R6	1.3
Verwerking in Algemene Materiaal			
	RPMW1003MO ZM90	R5	1.7
Spiraal-Edged Tungsten Staal Reamer			
	RPMW1003MO ZP20	R5	1.3
Verwerking in Algemene Materiaal			
	RPMW1003MO ZP30	R5	1.3
Verwerking in Algemene Materiaal			
	RPMW1003MO ZP60	R5	1.3
Verwerking in Algemene Materiaal			
	RPMW1003-XM ZP25	R5	1.3
Verwerking in Algemene Materiaal			

Toesluit Tipe Type Ronde Nose Einde Maal Snyer
Locking Tooth Type Round Nose End Milling Cutter



Spesifikasie D x T x M	prys USD
EMRR4-16-2T-M8	28.6
EMRR4-17-2T-M8	28.6
EMRR4-20-2T-M10	31.0
EMRR4-21-2T-M10	31.0
EMRR4-25-2T-M12	33.3
EMRR4-26-2T-M12	33.3
EMRR4-25-3T-M12	35.7
EMRR4-26-3T-M12	35.7
EMRR5-20-2T-M10	31.0
EMRR5-21-2T-M10	31.0
EMRR5-25-2T-M12	33.3
EMRR5-26-2T-M12	33.3
EMRR5-30-2T-M16	38.1
EMRR5-32-2T-M16	38.1
EMRR5-30-3T-M12	40.4
EMRR5-32-3T-M16	40.4
EMRR5-35-3T-M16	42.9
EMRR6-25-2T-M12	33.3
EMRR6-26-2T-M12	33.3
EMRR6-30-2T-M16	38.1
EMRR6-32-2T-M16	38.1
EMRR6-35-3T-M16	42.9

EMR Steel Round Nose Einde Myl Snyder
EMR Steel Round Nose End Milling Cutter



Spesifikasie D x d x T	prys USD
EMR 5R50-22-4T	10.3
EMR 5R63-22-4T	11.9
EMR 5R80-27-6T	20.4
EMR 5R100-32-6T	32.4
EMR 5R125-40-7T	51.0
EMR 5R160-40-8T	61.1
EMR 5R50-25.4-4T	11.9
EMR 5R63-25.4-4T	15.3
EMR 5R80-25.4-6T	23.9
EMR 5R100-31.75-6T	35.7
EMRW 6R50-22-4T	10.3
EMRW 6R63-22-4T	11.9
EMRW 6R80-27-6T	20.4
EMRW 6R100-32-6T	32.4
EMRW 6R125-40-7T	51.0
EMRW 6R160-40-8T	61.1
EMR 6R200-40-10T	119.0
EMR 6R250-40-12T	187.1
EMR 6R300-60-14T	238.1
EMRW 6R50-25.4-4T	11.9
EMRW 6R63-25.4-4T	15.3
EMRW 6R80-25.4-6T	23.9
EMRW 6R100-31.75-6T	35.7

The Above Spesifikasie Are RP.. Inserts,
RC.. / RD.. Inserts en hanteer, asseblief navraag!

The Above Spesifikasie Are RP.. Inserts,
RC.. / RD.. Inserts and handle, please inquire!

Weggooi Ronde Nose Einde Maal Sny Gereedskaphouer
Discarded Round Nose End Milling Cutter Toolholder













Spesifikasie D x D x L x T	prys USD
EMR C10-4R10-120-1T	3.3
EMR C12-4R12-130-1T	3.3
EMR C12-4R13-130-1T	3.3
EMR C16-4R16-150-2T	5.0
EMR C16-4R16-200-2T	6.1
EMR C16-4R17-150-2T	5.0
EMR C16-4R17-200-2T	6.1
EMR C19-4R20-150-2T	6.1
EMR C19-4R20-200-2T	6.9
EMR C20-4R20-150-2T	6.1
EMR C20-4R20-200-2T	6.9
EMR C20-4R20-250-2T	11.9
EMR C20-4R21-150-2T	6.1
EMR C20-4R21-200-2T	6.9
EMR C19-5R20-150-2T	6.1
EMR C19-5R20-200-2T	7.4
EMR C20-5R20-150-2T	6.1
EMR C20-5R20-200-2T	7.4
EMR C20-5R21-150-2T	6.1
EMR C20-5R21-200-2T	7.4
EMR C20-5R21-250-2T	11.9
EMR C20-5R25-150-2T	7.9
EMR C20-5R25-200-2T	9.6
EMR C20-5R25-250-2T	11.9
EMR C20-5R30-110-2T	7.9
EMR C24-5R25-150-2T	7.9
EMR C24-5R25-200-2T	9.6
EMR C24-5R25-250-2T	13.6
EMR C24-5R25-300-2T	19.0
EMR C25-5R25-150-2T	7.9
EMR C25-5R25-200-2T	9.6
EMR C25-5R25-250-2T	13.6
EMR C25-5R25-300-2T	19.0
EMR C25-5R26-150-2T	7.9
EMR C25-5R26-200-2T	9.6
EMR C25-5R26-250-2T	13.6
EMR C25-5R26-300-2T	19.0
EMR C25-5R30-150-2T	10.3
EMR C25-5R30-200-2T	11.9
EMR C25-5R30-250-2T	13.6
EMR C25-5R30-300-2T	19.0
EMR C32-5R35-150-3T	13.6
EMR C32-5R35-200-3T	15.3
EMR C32-5R35-250-3T	18.9
EMR C32-5R35-300-3T	23.9
EMR C32-5R35-350-3T	28.9
EMR C32-5R35-400-3T	39.0
EMR C32-5R40-150-3T	15.3
EMR C32-5R40-200-3T	18.9
EMR C32-5R40-250-3T	20.4
EMR C32-5R40-300-3T	23.9
EMR C32-5R40-350-3T	30.7
EMR C32-5R40-400-3T	39.0
EMR C32-5R50-150-4T	23.9
EMR C32-5R50-200-4T	27.1
EMRW C25-5R25-150-2T	7.9
EMRW C25-5R25-200-2T	9.6
EMRW C25-5R25-250-2T	15.3
EMRW C25-5R30-150-2T	10.3
EMRW C25-5R30-200-2T	11.9
EMRW C25-5R30-250-2T	16.9
EMRW C32-5R35-150-3T	13.6
EMRW C32-5R35-200-3T	15.3
EMRW C32-5R35-250-3T	18.9
EMRW C32-5R35-300-3T	27.1
EMRW C25-6R32-150-2T	10.3
EMRW C25-6R32-200-2T	11.9
EMRW C25-6R32-250-2T	16.9
EMRW C25-6R32-300-2T	20.4
EMRW C32-6R32-150-2T	13.6
EMRW C32-6R32-200-2T	15.3
EMRW C32-6R32-250-2T	18.9
EMRW C32-6R32-300-2T	23.9
EMRW C32-6R32-350-2T	27.1
EMRW C32-6R32-400-2T	30.7
EMRW C32-6R35-150-2T	15.3
EMRW C32-6R35-200-2T	16.9
EMRW C32-6R35-250-2T	20.4
EMRW C32-6R35-300-2T	27.1
EMRW C32-6R32-350-2T	28.9
EMRW C32-6R32-400-2T	32.4
EMRW C32-6R40-150-3T	16.9
EMRW C32-6R40-200-3T	19.7
EMRW C32-6R40-250-3T	22.1
EMRW C32-6R40-300-3T	27.1
EMRW C32-6R40-350-3T	30.7
EMRW C32-6R40-400-3T	39.0
EMRW C32-6R50-150-4T	23.9
EMRW C32-6R50-200-4T	27.1


Bogenoemde prys sluit vrag, belasting en fooi in.
Binnelandse USD Dollar Transaksieprys In China.

As jy enige vrae het, stuur asb. E-pos: eva@mzgtool.cn

<http://www.mzg.tw>

Product Pictures	Spesifikasie	USD	Product Pictures	Spesifikasie	USD	Product Pictures	Spesifikasie	USD	Product Pictures	Spesifikasie	USD
	Afwerking van Gietyster en verharde materiaal	7.1		P3200-R4 ZP10	7.4		LNMU0303ZER-MJ			800-08A	
	Afwerking van Copper and Aluminum	7.1		P3200-R5 ZP10	8.3		PNMU0905GNEN-MJ			800-08T308M-C-G	
	Medium Afwerking van Copper and Aluminum	1.7		P3200-R6 ZP10	8.3		PNMU0905XNER-GM			800-08T308M-I-G	
	Ruwe verwerking van Algemene materiaal	3.1		P3200-R8 ZP10	9.9		SNMU130508EN-GM			800-09T308H-P-G	
	Medium afwerking van algemene materiaal	3.1		P3200-R10 ZP10	11.9		WNMU080608EN-SM			R390-11T308-PM	
	Medium afwerking van algemene materiaal	3.1		P3200-R12.5 ZP10	20.3		3PKT100408R-M			SCMT09T308-MM	
				P3200-R15 ZP10	31.1		3PKT150508R-M			S-R215.44-15T364M	
				P3200-R16 ZP10	40.3		3PKT190608R-M			DGN3102C	
				Cutting Below HRC55	17.1		XJMG1204			HNGX0906-FF	
				ZPFG100 ZM55	17.1		WNMX060312ZNN-MM			WNMX09T316ZNN-MM	
				ZPFG120 ZM55	17.1		6NGU060408R-M			6NGU090508R-M	
				ZPFG160 ZM55	20.4		CNHX100508T			CNHX131108T	
				ZPFG200 ZM55	23.9		AXMT060208R-EM			BLMP0603R-M	
				ZPFG250 ZM55	32.4		BLMP0904R-ML			BLMP0904R-ML	
				ZPFG300 ZM55	51.4		BLMP1205R-M			BLMP1205R-M	
				Cutting Below HRC55	17.1		BLMP1306R-M			BLMP1306R-M	
				BNM120 ZM55	17.1		TNGX2207PNTN			TNGX2207PNTN	
				BNM160 ZM55	18.6		ZNHU080-08			ZNHU080-08	
				BNM200 ZM55	23.9		SNMX1205XTN			SNMX1205XTN	
				BNM250 ZM55	32.4		SOMT050204-DP			SOMT060204-DP	
				BNM300 ZM55	41.0		SOMT070306-DP			SOMT08T306-DP	
							SOMT09T308-DP			SOMT11T308-DP	
							AXMT123508PEERG			APKT150412-PM	
							RPHX1204M6EN-M31			SPMT120408-PM	
							XNEX080608-MD15			ONHU060408-PM	
							XOMX180608TR-M14			ONHU08T508-PM	
										KNX-Q7-3.5	

KM Steel 45° Face Milling Cutter
KM Steel 45° Face Milling Cutter



Spesifikasie DxdxT	prys USD
KM12-50-22-4T	11.9
KM12-63-22-4T	15.3
KM12-80-27-5T	25.4
KM12-100-32-5T	35.7
KM12-125-40-6T	51.0
KM12-160-40-6T	61.1
KM12-200-40-8T	136.0
KM12-250-40-10T	204.0
KM12 300-60-12T	255.0
KM12-50-25.4-4T	13.6
KM12-63-25.4-4T	16.9
KM12-80-25.4-5T	28.9
KM12-100-31.75-5T	39.0

KM Aluminum 45° Face Milling Cutter
KM Aluminum 45° Face Milling Cutter



Spesifikasie DxdxT	prys USD
AL-KM12-50-22-4T	16.9
AL-KM12-63-22-4T	22.1
AL-KM12-80-22-5T	30.7
AL-KM12-100-22-5T	54.6
AL-KM12-125-27-6T	85.0
AL-KM12-160-27-6T	95.3
AL-KM12-200-27-8T	204.0
AL-KM12-250-32-10T	272.1
AL-KM12 300-32-12T	340.3
AL-KM12-50-25.4-4T	19.0
AL-KM12-63-25.4-4T	23.1
AL-KM12-80-25.4-5T	32.4
AL-KM12-100-31.75-5T	54.6

Weggooid sferiese eindmeulwerkhouer
Discarded Spherical End Milling Toolholder



Spesifikasie dxDxLxT	prys USD
T2139 C10-4R-100-1T	8.9
T2139 C12-4R-130-1T	8.9
T2139 C16-4R-150-1T	10.7
T2139 C10-5R-120-1T	8.9
T2139 C12-5R-150-1T	8.9
T2139 C16-5R-150-1T	10.7
T2139 C12-6R-130-1T	8.9
T2139 C12-6R-150-1T	8.9
T2139 C16-6R-150-1T	10.7
T2139 C16-6R-200-1T	12.6
T2139 C16-8R-150-1T	10.0
T2139 C16-8R-200-1T	11.9
T2139 C20-8R-200-1T	16.7
T2139 C25-8R-250-1T	19.7
T2139 C20-10R-150-1T	13.9
T2139 C20-10R-200-1T	16.0
T2139 C25-10R-250-1T	19.7
T2139 C32-10R-300-1T	22.1
T2139 C25-12.5R-150-1T	16.7
T2139 C25-12.5R-200-1T	19.6
T2139 C25-12.5R-250-1T	22.1
T2139 C25-12.5R-300-1T	25.0
T2139 C32-12.5R-300-1T	27.9
T2139 C32-15R-150-1T	18.3
T2139 C32-15R-200-1T	21.0
T2139 C32-15R-250-1T	23.9
T2139 C32-15R-300-1T	26.7
T2139 C32-16R-150-1T	30.4
T2139 C32-16R-200-1T	18.3
T2139 C32-16R-250-1T	21.0
T2139 C32-16R-300-1T	23.9
T2139 C32-16R-350-1T	26.7
T2139 C32-16R-350-1T	30.4
Insert: ZPFG	
ABPF C16-8R-150	23.9
ABPF C16-8R-200	29.7
ABPF C20-10R-150	31.7
ABPF C20-10R-200	37.6
ABPF C25-12.5R-150	39.7
ABPF C25-12.5R-200	49.6
ABPF C25-12.5R-250	55.4
ABPF C32-15R-150	45.7
ABPF C32-15R-200	51.7
ABPF C32-15R-250	59.6
ABPF C32-15R-300	79.3
Insert: BNM	
BNML C12-6R-130-1T	11.9
BNML C12-6R-150-1T	11.9
BNML C16-8R-150-1T	15.0
BNML C16-8R-200-1T	17.9
BNML C20-10R-150-1T	21.0
BNML C20-10R-200-1T	23.9
BNML C25-10R-250-1T	29.7
BNML C25-12.5R-150-1T	25.0
BNML C25-12.5R-200-1T	29.7
BNML C25-12.5R-250-1T	33.3

Bogenoemde prys sluit vraag, belasting en fooi in.
Binnelandse USD Dollar Transaksieprys In China.

As jy enige vrae het, stuur asb. E-pos: eva@mzgtool.cn


<http://www.mzg.tw>

Insert Type Quick Drill

Insert Type Quick Drill

MaiFix®

Vergrendelende Tand Tipe Reghoekige Einde Myl Snyder
Locking Tooth Type Right-Angle End Milling Cutter



Spesifikasie DxTxM	prys USD
R39011-16-2T-M8	28.6
R39011-17-2T-M8	28.6
R39011-20-2T-M10	31.0
R39011-21-2T-M10	31.0
R39011-25-2T-M12	33.3
R39011-26-2T-M12	33.3
R39011-30-2T-M16	35.7
R39011-32-2T-M16	35.7
R39011-33-2T-M16	35.7
R39011-35-2T-M16	42.9

Vergrendelende Tand Tipe Steriese Einde Splyskutter
Locking Tooth Type Spherical End Milling Cutter



Spesifikasie DxRxM	prys USD
BNM-10-R5-M5	35.7
BNM-12-R6-M6	35.7
BNM-16-R8-M8	38.1
BNM-20-R10-M10	38.1
BNM-25-R12.5-M12	40.4

Vergrendelende Tand Tipe Reghoekige Einde Myl Snyder
Locking Tooth Type Right-Angle End Milling Cutter



Spesifikasie DxTxM	prys USD
JDMT07-11-2T-M5	35.7
JDMT07-12-2T-M5	35.7
JDMT07-12-2T-M6	35.7
JDMT07-13-2T-M6	35.7
JDMT07-14-2T-M6	35.7
JDMT07-16-3T-M8	42.9
JDMT07-17-3T-M8	42.9

Vergrendelende Tand Tipe Reghoekige Einde Myl Snyder
Locking Tooth Type Right-Angle End Milling Cutter



Spesifikasie DxTxM	prys USD
AXMT06-11-2T-M5	35.7
AXMT06-12-2T-M5	35.7
AXMT06-12-2T-M6	35.7
AXMT06-13-2T-M6	35.7
AXMT06-16-3T-M8	42.9
AXMT06-17-3T-M8	42.9

Locking Tooth Type Fast Einde Myl Snyder
Vergrendelende Tooth Type Fast Einde Myl Snyder



Spesifikasie DxTxM	prys USD
AJX06-16-2T-M8	31.0
AJX06-17-2T-M8	31.0
AJX08-20-2T-M10	33.3
AJX08-21-2T-M10	33.3
AJX09-25-2T-M12	35.7
AJX09-26-2T-M12	35.7
AJX09-28-2T-M12	35.7
AJX12-30-2T-M16	40.4
AJX12-32-2T-M16	40.4
AJX12-35-2T-M16	47.6

* Sluit tande tipe gereedskap voorraad Spesifikasie is voltooi.
Raadpleeg asseblief vir Spesifikasie nie gelys nie.

* Lock teeth type tool stock Specification are complete.
Please inquire for stock Specification not listed.

Produkprente	Spesifikasie	R	USD
	WCMX030208 ZP25	0.8	1.4
	WCMX040208 ZP25	0.8	1.4
	WCMX050308 ZP25	0.8	1.7
	WCMX06T308 ZP25	0.8	1.9
	WCMX080412 ZP25	1.2	2.6
	WCMX030208 ZP30	0.8	2.3
	WCMX040208 ZP30	0.8	2.3
	WCMX050308 ZP30	0.8	2.4
	WCMX06T308 ZP30	0.8	2.6
	WCMX080412 ZP30	1.2	3.7
	SPMG050204 ZP25	0.4	1.4
	SPMG060204 ZP25	0.4	1.4
	SPMG07T308 ZP25	0.8	1.7
	SPMG090408 ZP25	0.8	1.9
	SPMG110408 ZP25	0.8	2.3
	SPMG050204 ZP30	0.4	2.7
	SPMG060204 ZP30	0.4	2.9
	SPMG07T308 ZP30	0.8	2.9
	SPMG090408 ZP30	0.8	3.3
	SPMG110408 ZP30	0.8	3.6
	SPMG140408 ZP30	0.8	5.4

Wc Invoeg Type Snel Boor

WC Insert Type Quick Drill



D	d		L=2XD	L=3XD	L=4XD	L=5XD
8	12	XCMT040104	61.7	91.4	-	-
10	12	XCMT050204	57.1	85.0	-	-
12	16	XCMT060204	47.1	65.3	-	-
14-14.5	20	WCMX030208	25.3	32.9	37.6	67.1
15-20	25	WCMX030208	25.3	32.9	37.6	67.1
20.5-24.5	25	WCMX040208	35.3	42.6	50.3	72.9
25	32	WCMX050308	35.3	42.6	50.3	72.9
25.5-30	32	WCMX050308	42.6	45.3	52.9	80.0
30.5-31	32	WCMX050308	57.6	59.6	72.9	100.4
31.5-40	32	WCMX06T308	57.6	59.6	72.9	100.4
41	32	WCMX06T308	69.0	76.7	96.0	125.7
42	40	WCMX06T308	69.0	76.7	96.0	125.7
43-45	40	WCMX080412	69.0	76.7	96.0	125.7
46-50	40	WCMX080412	75.4	93.3	102.9	137.1
51-55	40	WCMX080412	85.0	109.7	130.3	148.6
56-57	40	WCMX080412	89.0	112.4	171.4	165.7
58-59	40	WCMX06T308	89.0	112.4	171.4	165.7
60-63	40	WCMX06T308	93.3	123.3	197.9	201.1
64-65	40	WCMX06T308	100.3	137.1	224.0	231.0
66-68	40	WCMX06T308	101.7	151.0	228.6	240.0
69-70	40	WCMX06T308	102.9	160.0	240.0	262.9

SP Insert Type Quick Drill

SP Insert Type Quick Drill



D	d		L=2XD	L=3XD	L=4XD	L=5XD
13-14.5	20	SPMG050204	30.4	35.7	44.7	78.6
15	25	SPMG050204	30.4	35.7	44.7	78.6
15.5-20	25	SPMG060204	30.4	35.7	44.7	78.6
20.5-21.5	25	SPMG060204	41.9	47.6	60.7	83.3
22-24.5	25	SPMG07T308	41.9	47.6	60.7	83.3
25-27.5	32	SPMG07T308	50.3	54.7	65.4	91.4
28-30	32	SPMG090408	50.3	54.7	65.4	91.4
30.5-33.5	32	SPMG090408	66.9	72.9	88.1	108.6
34-40	32	SPMG110408	66.9	72.9	88.1	108.6
41	32	SPMG110408	79.0	88.1	105.4	137.1
42-45	40	SPMG140512	79.0	88.1	105.4	137.1
46-50	40	SPMG140512	88.1	98.9	125.7	148.6
51-55	40	SPMG07T308	94.3	111.0	144.0	171.4
56	40	SPMG07T308	98.9	123.9	208.1	228.6
57-59	40	SPMG090408	98.9	123.9	208.1	228.6
60-63	40	SPMG090408	103.3	136.9	250.0	271.4
64-66	40	SPMG090408	111.0	161.9	280.0	300.0
67-68	40	SPMG110408	111.0	161.9	280.0	300.0
69-70	40	SPMG110408	114.6	173.9	290.0	328.6

Plus WDXT ... / GPMT ... Soort Voorraad Quick Drill Commodity, welkom om navraag te doen!

Plus WDXT.../GPMT... Type Stock Quick Drill Commodity, Welcome To Inquire!

Bogenoemde prys sluit vraag, belasting en fooi in.
Binnelandse USD Dollar Transaksieprys In China.
As jy enige vrae het, stuur asb. E-pos: eva@mzgtool.cn

<http://www.mzg.tw>

Produkprente	Spesifikasie	NO	verskeidenheid	prys
	RBH19C	LBK1	19-25	28.6
	RBH25C	LBK2	25-33	28.6
	RBH32C	LBK3	32-42	31.0
	RBH40C	LBK4	40-55	40.4
	RBH52C	LBK5	52-70	61.9
	RBH68C	LBK6	68-92	83.3
	RBH90C	LBK6	90-122	102.4
	RBH120C	LBK6	120-164	119.0
	RBH160C	BST	160-204	135.7
	RBH200C	BST	200-310	273.9
Insert:CCMT..	RBH300C	BST	300-410	544.0
	RBH400C	BST	400-510	583.3
	RBH500C	BST	500-610	681.0

	CBH20	LBK1	20-26	135.7
	CBH25	LBK2	25-33	154.7
	CBH32	LBK3	32-42	163.1
	CBH40	LBK4	40-55	181.0
	CBH52	LBK5	52-75	204.7
	CBH68	LBK6	68-102	238.1
	CBH100	LBK6	100-152	273.9
	CBH150	LBK6	150-202	323.9
	CBH200	BST	200-310	714.3
	CBH300	BST	300-410	821.4
Fine-Tuning Accuracy 0.01mm	CBH400	BST	400-510	919.0
	CBH500	BST	500-610	1023.9
	EWN20	CK1	20-36	123.9
	EWN25	CK2	25-47	131.0
	EWN32	CK3	32-60	142.9
	EWN41	CK4	41-74	163.1
	EWN53	CK5	53-95	178.6
	EWN68	CK6	68-150	197.6
	EWN100	CK6	100-203	214.3

	EWN1-1		20-25	13.1
	CBH1-2		25-31	13.1
	CBH1-3		30-36	13.1
	CBH2-1		25-33	13.1
	CBH2-2		32-40	13.1
	CBH2-3		39-47	13.1
	CBH3-1		32-42	13.1
	CBH3-2		41-51	13.1
	CBH3-3		50-60	13.1
	CBH4-1		41-54	13.1
	CBH4-2		50-63	13.1
	CBH4-3		61-74	13.1
	CBH5-1		53-70	13.1
	CBH5-2		65-82	13.1
	CBH5-3		78-95	13.1
	CBH6-1		68-100	13.1
			100-153	13.1
	CBH6-2		94-126	13.1
			126-179	13.1
	CBH6-3		118-150	13.1
Insert:TP..			150-203	13.1

	BE09A	M5	16.7	
	BE10. 5A	M5	16.7	
	BE12A	M6	16.7	
	BE14A	M6	16.7	
	BE16A	M6	16.7	
	BE18A	M10	16.7	
	BE20A	M10	16.7	
	BE22A	M10	16.7	
	BE24A	M10	16.7	
	BE26A	M10	16.7	
BE Boring Tool	BE28A	M10	16.7	
	BE30A	M10	16.7	
	BE32A	M10	19.0	
	BE34A	M10	19.0	
	BE36A	M10	23.9	
	BE38A	M10	23.9	
	BE40A	M10	23.9	

	EC1608	-	14.3	
	EC1610	-	14.3	
	EC1612	-	14.3	
	EC1614	-	14.3	

	ST08-W5-100L	M5	59.6	
	ST10-W6-110L	M6	69.0	
	ST12-W6-120L	M6	88.1	
	ST12-W6-150L	M6	107.1	
	ST14-W6-160L	M6	119.0	
	ST16-W10-160L	M10	135.7	
	ST16-W10-180L	M10	150.0	

NBH2084 Boring Tool (Boringreeks:8-280mm)			
			
NBH2084 Boring Tool (Boringreeks: 8-280mm) Fine-Tuning Accuracy 0.01mm			
Spesifikasie	verskeidenheid	prys	

Boor Tool Holder			
SBJ2008-32	8-11	8.6	
SBJ2010-40	10-13	8.6	
SBJ2012-53	12-17	8.6	
SBJ2016-68	16-21	8.6	
SBJ2016-102	16-21	20.4	
SBJ2020-83	20-130	8.6	
SBJ2020-125	20-130	20.4	
SBJ2020-150	20-130	23.9	
SBJ2020-200	20-130	28.6	
SBJ2025-96	25-135	8.6	
SBJ2025-144	25-135	20.4	
SBJ2025-150	25-135	23.9	
SBJ2025-200	25-135	28.6	
SBJ2030-115	30-140	8.6	
SBJ2030-173	30-140	23.9	
SBJ2030-200	30-140	28.6	
SBJ2020-L	120-280	8.6	
SBJ2020-150L	120-400	23.9	

Stel Boring Tool			
NBH2084 Boring head			
R8-NBH2084-8P	8-280	138.1	
NT30-NBH2084-8P	8-280	233.3	
NT40-NBH2084-8P	8-280	233.3	
NT50-NBH2084-8P	8-280	309.6	
BT40-NBH2084-8P	8-280	233.3	
BT50-NBH2084-8P	8-280	273.9	
SK40-NBH2084-8P	8-280	278.6	
SK50-NBH2084-8P	8-280	309.6	

NBJ16 Boring Tool (Boringreeks:8-50mm)			
			
NBJ16 Boring Tool (Boringreeks: 8-50mm) Fine-Tuning Accuracy 0.01mm			
Spesifikasie	verskeidenheid	prys	

Boor Tool Holder			
SBJ1606-24	6-9	8.6	
SBJ1608-32	8-11	8.6	
SBJ1610-40	10-13	8.6	
SBJ1612-53	12-15	8.6	
SBJ1614-60	14-17	8.6	
SBJ1616-68	16-21	8.6	
SBJ1620-83	20-26	8.6	
SBJ1620-150L	20-26	23.9	
SBJ1620-200L	20-26	28.6	
SBJ1625-90	25-31	8.6	
SBJ1625-150L	25-31	23.9	
SBJ1625-200L	25-31	28.6	
SBJ1630-90	30-36	8.6	
SBJ1630-150L	30-36	23.9	
SBJ1630-200L	30-36	28.6	
SBJ1635-90	35-41	8.6	
SBJ1635-150L	35-41	23.9	
SBJ1635-200L	35-41	28.6	
SBJ1640-90	40-46	8.6	
SBJ1640-150L	40-46	23.9	
SBJ1640-200L	40-46	28.6	
SBJ1645-90	45-51	8.6	
SBJ1645-150L	45-51	23.9	
SBJ1645-200L	45-51	28.6	

Stel Boring Tool			
NBJ16 Boring head			
NT40-SBJ16-55-12P	8-50	138.1	
NT50-SBJ16-65-12P	8-50	233.3	
BT30-SBJ16-55-12P	8-50	233.3	
BT40-SBJ16-55-12P	8-50	309.6	
BT50-SBJ16-65-12P	8-50	233.3	
SK30-SBJ16-60-12P	8-50	273.9	
SK40-SBJ16-60-12P	8-50	278.6	
SK50-SBJ16-65-12P	8-50	309.6	

HBOR Fine-Tuning Boring Snyer (Fine-Tuning Akkuraatheid 0.002mm)			
			
HBOR Fine-Tuning Boring Cutter (Fine-Tuning Accuracy 0.002mm)			
Spesifikasie	verskeidenheid	prys	

HBOR25 Boring Cutter			
HBOR25M (29-38) Boring head	29-38	666.7	
HBOR25M (29-38) Back Boring	29-38	666.7	
BT30-HBOR25P ToolHolder		857.1	
BT40-HBOR25P ToolHolder		857.1	
SK30-HBOR25P ToolHolder		857.1	
SK40-HBOR25P ToolHolder		857.1	
HSK63A-HBOR25P ToolHolder		976.1	
CA0602-09T Carbide Boring	2-3.2	59.6	
CA0603-16T Carbide Boring	3-4.2	59.6	
CA0604-22T Carbide Boring	4-5.2	59.6	
CA0605-27T Carbide Boring	5-6.2	59.6	
CA0606-32T Carbide Boring	6-7.2	59.6	
CB06050-21 (CC03)	5-6	123.9	
CB06055-26 (CC03)	5.5-6.5	123.9	
CB06060-26 (CC03)	6-7	123.9	
CB06065-31 (CC03)	6.5-7.5	123.9	
CB06070-31 (CC04)	7-8	123.9	

HBOR32 Boring Cutter			
HBOR32M (36-52) Boring head	36-52	800	
HBOR32M (36-52) Back Boring	36-52	800	

HBOR40 Boring Cutter			
HBOR40M (44-68) Boring head	44-68	833.3	
HBOR40M (44-68) Back Boring	44-68	833.3	

HBOR50 Stel Boring Tool			
HBOR50BM (57-90) Boring head	57-90	742.9	
HBOR50BM (57-90) Back Boring	57-90	742.9	
BT30-HBOR50 (06-90) ToolHolder	6-90	857.1	
BT40-HBOR50 (06-90) ToolHolder	6-90	857.1	
BT50-HBOR50 (06-90) ToolHolder	6-90	1190.4	
BT50-HBOR50 (06-90) -14P	6-90	857.1	
BT50-HBOR50 (06-90) -14P	6-90	1190.4	
BT50-HBOR50 (06-90) -14P	6-90	904.7	
BT50-HBOR50 (06-90) -14P	6-90	1273.9	
BT50-HBOR50 (06-90) -14P	6-90	1273.9	
BT50-HBOR50 (06-90) -14P	6-90	904.7	
BT50-HBOR50 (06-90) -14P	6-90	1273.9	
BT50-HBOR50 (06-90) -14P	6-90	1273.9	
BT50-HBOR50 (06-90) -14P	6-90	1309.6	

HBOR63 Stel Boring Tool			
HBOR63BM (70-110) Boring head	70-110	804.7	
HBOR63BM (110-150) Boring head	110-150	804.7	
HBOR63BM (70-110) Back Boring	70-110	804.7	
HBOR63BM (110-150) Back Boring	110-150	804.7	
NT40-HBOR63 ToolHolder	6-150	1071.4	
NT40-HBOR63 (6-150) -15P	6-150	1381	
NT50-HBOR63 ToolHolder	6-150	1119	
NT50-HBOR63 (6-150) -15P	6-150	1428.6	
BT40-HBOR63 ToolHolder	6-150	1071.4	
BT40-HBOR63 (6-150) 15P	6-150	1381	
BT50-HBOR63 ToolHolder	6-150	1119	
BT50-HBOR63 (6-150) 15P	6-150	1428.6	
SK40-HBOR63 (6-150) 15P	6-150	1381	
SK50-HBOR63 (6-150) 15P	6-150	1428.6	
HSK63A-HBOR63 (6-150) 15P	6-150	1452.4	

Boring Accessories			
Boring Accessories			
BR1606-21 (WBGT0601..L)	6-9	23.9	
BR1608-28 (TBGT0601..L)	8-11	23.9	
BR1610-35 (TBGT0601..L)	10-13	23.9	
BR1612-42 (TP..09..L)	12-15	23.9	
BR1614-50 (TP..09..L)	14-17	23.9	
BR1616-60 (TP..09..L)	16-20	23.9	
BR1620-65 (TP..11..L)	20-24	23.9	
BR1624-68 (TP..11..L)	24-28	23.9	
BM5		35.7	
SRTP2938 (TP..09..L)	28-38	35.7	
SRTP3652 (TP..09..L)	36-52	35.7	
SRTP4468 (TP..09..L)	44-68	41.7	
BM8		9.6	
SRTP70110 (TP..11..L)	70-110	47.6	
SRTP110150 (TP..11..L)	110-150	47.6	

BSA Rough Boring Cutter

BSA Rough Boring Cutter

Spesifikasie	prys
BT40-BSA25-120	47.6
BT40-BSA30-150	47.6
BT40-BSA38-165	50.0
BT40-BSA42-165	50.0
BT40-BSA50-165	53.6
BT40-BSA62-180	63.1
BT40-BSA72-180	71.4
BT40-BSA90-180	89.3
BT50-BSA25-135	81.0
BT50-BSA30-165	81.0
BT50-BSA38-180	83.3
BT50-BSA42-210	83.3
BT50-BSA50-180	86.9
BT50-BSA50-240	92.9
BT50-BSA62-195	95.3
BT50-BSA62-270	107.1
BT50-BSA72-195	95.3
BT50-BSA72-285	131.0
BT50-BSA90-210	164.3
BT50-BSA90-300	208.3
BT50-BSA105-195	297.6
BT50-BSA105-285	381.0

BSA Rough Boring Cutter

BSA Rough Boring Cutter

Spesifikasie	prys
BSA30-42-LBK2	27.4
BSA38-52-LBK3	28.6
BSA50-65-LBK4	33.3
BSA62-90-LBK5	41.7
BSA72-110-LBK6	51.1

BSB Rough Boring Cutter

BSB Rough Boring Cutter

Spesifikasie	prys
BT40-BSB25-120	47.6
BT40-BSB38-150	47.6
BT40-BSB50-165	53.6
BT40-BSB62-180	62.6
BT40-BSB72-165	71.4
BT40-BSB90-180	89.3
BT50-BSB25-135	80.4
BT50-BSB38-180	81.9
BT50-BSB50-180	86.4
BT50-BSB50-240	92.4
BT50-BSB62-195	95.3
BT50-BSB62-270	107.1
BT50-BSB72-195	104.3
BT50-BSB72-285	140.0
BT50-BSB90-210	163.9
BT50-BSB90-300	208.3
BT50-BSB105-195	297.9
BT50-BSB105-285	383.1

BSB-LBK Rough Boring Cutter

BSB-LBK Rough Boring Cutter

Spesifikasie	prys
BSB25-52-LBK2	27.4
BSB38-70-LBK3	28.6
BSB50-90-LBK4	32.9
BSB62-90-LBK5	41.7
BSB72-135-LBK6	59.6

Rough Boring Cutter Holder

Rough Boring Cutter Holder

Spesifikasie	prys
TBS910-36-L	TP09 11.9
TBS910-45-L	TP09 11.9
TBS913-48-L	TP11 11.9
TBS913-65-L	TP11 11.9
TBS916-60-L	TP11 11.9
TBS916-80-L	TP11 11.9
TBS919-70-L	TC16 19.0
TBS919-90-L	TC16 19.0
TBS919-85-L	TC16 19.0
TBS919-105-L	TC16 23.9
TBS925-100-L	TC16 31.0
TBS925-135-L	TC16 38.1

Spesifikasie	prys
TBS910-36-R	TP09 11.9
TBS910-45-R	TP09 11.9
TBS913-48-R	TP11 11.9
TBS913-65-R	TP11 11.9
TBS916-60-R	TP11 11.9
TBS916-80-R	TP11 11.9
TBS919-70-R	TC16 19.0
TBS919-90-R	TC16 19.0
TBS919-85-R	TC16 19.0
TBS919-105-R	TC16 23.9
TBS925-100-R	TC16 31.0
TBS925-135-R	TC16 38.1

Spesifikasie	prys
CBS908-23-L	CC06 11.9
CBS908-30-L	CC06 11.9
CBS910-36-L	CC06 11.9
CBS910-45-L	CC06 11.9
CBS913-48-L	CC09 11.9
CBS913-65-L	CC09 11.9
CBS916-60-L	CC09 11.9
CBS916-80-L	CC09 11.9
CBS919-70-L	CC12 19.0
CBS919-90-L	CC12 19.0
CBS919-85-L	CC12 19.0
CBS919-105-L	CC12 23.9
CBS925-100-L	CC12 31.0
CBS925-135-L	CC12 38.1

Spesifikasie	prys
CBS908-23-R	CC06 11.9
CBS908-30-R	CC06 11.9
CBS910-36-R	CC06 11.9
CBS910-45-R	CC06 11.9
CBS913-48-R	CC09 11.9
CBS913-65-R	CC09 11.9
CBS916-60-R	CC09 11.9
CBS916-80-R	CC09 11.9
CBS919-70-R	CC12 19.0
CBS919-90-R	CC12 19.0
CBS919-85-R	CC12 19.0
CBS919-105-R	CC12 23.9
CBS925-100-R	CC12 31.0
CBS925-135-R	CC12 38.1

Spesifikasie	prys
TBS410-45	TP09 11.9
TBS410-50	TP09 11.9
TBS413-60	TP11 11.9
TBS416-75	TP11 11.9
TBS419-90	TC16 19.0
TBS419-115	TC16 19.0
TBS425-130	TC16 38.1

Spesifikasie	prys
CBS408-30	CC06 11.9
CBS408-35	CC06 11.9
CBS410-45	CC06 11.9
CBS410-50	CC06 11.9
CBS413-60	CC09 11.9
CBS416-75	CC09 11.9
CBS419-115	CC12 19.0
CBS425-130	CC12 38.1

BST / NBH Toolholder

BST / NBH Toolholder

Spesifikasie	prys
BT30-NBH2084	35.7
BT40-NBH2084	28.6
BT50-NBH2084	59.6
NT30-NBH2084	35.7
NT40-NBH2084	35.7
NT50-NBH2084	71.4
SK40-NBH2084	35.7
SK50-NBH2084	71.4
BBT40-NBH2084	154.7
BBT50-NBH2084	214.3
CAT40-NBH2084	46.4
CAT50-NBH2084	92.9
HSK63A-NBH2084	154.7
HSK100A-NBH2084	214.3
ISO40-NBH2084	46.4
ISO50-NBH2084	92.9
C20-NBH2084	61.9
MT3-NBH2084	42.9
MT4-NBH2084	42.9
MT5-NBH2084	52.4
MT6-NBH2084	66.7
MTB3-NBH2084	42.9
MTB4-NBH2084	42.9
MTB5-NBH2084	52.4
MTB6-NBH2084	66.7
RB-NBH2084	35.7
BT40-NBH2084-100L	59.6
BT40-NBH2084-150L	90.4
BT40-NBH2084-200L	119.0
BT50-NBH2084-100L	71.4
BT50-NBH2084-150L	90.4
BT50-NBH2084-200L	119.0
BT50-NBH2084-250L	148.9
BT40-BST-70	66.7
BT40-BST-100	66.7
BT40-BST-150	77.4
BT40-BST-200	85.7
BT50-BST-100	66.7
BT50-BST-150	77.4
BT50-BST-200	83.3
BT50-BST-250	107.1
BT50-BST-300	119.0
BT50-BST-350	134.6
BT50-BST-400	148.9
BT50-BST-450	195.3
BT50-BST-500	238.1
SK40-BST-100	92.9
SK40-BST-150	123.9
SK50-BST-100	92.9
SK50-BST-150	123.9
SK50-BST-200	154.7
SK50-BST-250	185.7

LBK Uitbreidingsstang

LBK Extension Rod

Spesifikasie	prys
LBK1-1-30	11.9
LBK2-2-30	11.9
LBK3-3-30	14.3
LBK4-4-45	14.3
LBK4-4-60	16.7
LBK5-5-60	19.0
LBK5-5-90	21.4
LBK6-6-60	21.4
LBK6-6-100	21.4
LBK6-6-120	29.7

LBK Omskakeling Mou

LBK Conversion Sleeve

Spesifikasie	prys
LBK2-1-36	31.0
LBK3-1-41	31.0
LBK3-2-37	31.0
LBK4-1-58	35.7
LBK4-2-50	35.7
LBK4-3-50	35.7
LBK5-1-60	40.4
LBK5-2-54	40.4
LBK5-2-74	40.4
LBK5-3-47	40.4
LBK5-3-72	40.4
LBK5-4-42	40.4
LBK5-4-67	40.4
LBK6-1-70	46.4
LBK6-2-63	46.4
LBK6-2-93	56.0
LBK6-3-56	46.4
LBK6-3-96	56.0
LBK6-4-51	46.4
LBK6-4-101	56.0
LBK6-5-41	46.4
LBK6-5-91	56.0

LBK Gereedskapphouer

LBK Toolholder

Spesifikasie	prys
BT30-LBK1-55	21.0
BT30-LBK1-70	21.0
BT30-LBK2-80	21.0
BT30-LBK3-80	21.0
BT30-LBK4-70	21.0
BT30-LBK5-70	21.0
BT30-LBK6-60	21.0

Spesifikasie	prys
BT40-LBK1-75	21.0
BT40-LBK1-105	21.0
BT40-LBK1-130	28.3
BT40-LBK1-165	35.7
BT40-LBK1-195	59.6
BT40-LBK2-85	21.0
BT40-LBK2-115	21.0
BT40-LBK2-130	28.3
BT40-LBK2-165	35.7
BT40-LBK2-200	59.6
BT40-LBK3-95	21.0
BT40-LBK3-125	28.3
BT40-LBK3-165	35.7
BT40-LBK3-210	59.6
BT40-LBK4-85	21.0
BT40-LBK4-115	21.0
BT40-LBK4-130	28.3
BT40-LBK4-150	28.3
BT40-LBK4-175	35.7
BT40-LBK4-220	59.6
BT40-LBK5-75	21.0
BT40-LBK5-125	28.3
BT40-LBK5-175	35.7
BT40-LBK5-235	59.6
BT40-LBK6-65	21.0
BT40-LBK6-115	21.0
BT40-LBK6-150	28.3
BT40-LBK6-165	35.7
BT40-LBK6-240	59.6

Spesifikasie	prys
BT50-LBK1-115	53.6
BT50-LBK1-145	59.6
BT50-LBK1-200	80.4
BT50-LBK2-110	53.6
BT50-LBK2-140	59.6
BT50-LBK2-175	65.4
BT50-LBK2-235	108.3
BT50-LBK3-125	53.6
BT50-LBK3-140	59.6
BT50-LBK3-155	59.6
BT50-LBK3-185	65.4
BT50-LBK3-215	75.0
BT50-LBK3-255	91.7
BT50-LBK3-290	108.3
BT50-LBK3-300	108.3
BT50-LBK3-350	148.9
BT50-LBK4-115	53.6
BT50-LBK4-145	59.6
BT50-LBK4-160	65.4
BT50-LBK4-205	75.0
BT50-LBK4-255	91.7
BT50-LBK4-305	108.3
BT50-LBK4-350	148.9
BT50-LBK5-105	53.6
BT50-LBK5-180	65.4
BT50-LBK5-240	75.0
BT50-LBK5-300	108.3
BT50-LBK5-350	148.9
BT50-LBK6-95	53.6
BT50-LBK6-155	65.4
BT50-LBK6-170	65.4
BT50-LBK6-230	75.0
BT50-LBK6-290	108.3
BT50-LBK6-350	148.9

Spesifikasie	prys
HSK63A-LBK1-105	148.9
HSK63A-LBK2-115	148.9
HSK63A-LBK3-125	148.9
HSK63A-LBK4-115	148.9
HSK63A-LBK5-125	148.9
HSK63A-LBK6-115	148.9

CK Gereedskapphouer

CK Toolholder

Spesifikasie	prys
BT30-CK1-55	35.7
BT30-CK1-70	35.7
BT30-CK2-80	35.7
BT30-CK3-80	35.7
BT30-CK4-70	35.7
BT30-CK5-70	35.7
BT30-CK6-60	35.7

Spesifikasie	prys
BT40-CK1-75	35.7
BT40-CK1-105	35.7
BT40-CK1-130	44.7
BT40-CK2-75	35.7
BT40-CK2-115	35.7
BT40-CK2-130	44.7
BT40-CK3-80	35.7
BT40-CK3-100	35.7
BT40-CK3-135	44.7
BT40-CK3-155	44.7
BT40-CK4-75	35.7
BT40-CK4-100	35.7
BT40-CK4-150	44.7
BT40-CK4-170	53.6
BT40-CK5-60	35.7
BT40-CK5-100	35.7
BT40-CK5-150	44.7
BT40-CK6-65	35.7
BT40-CK6-100	35.7
BT40-CK6-150	44.7

Spesifikasie	prys
BT50-CK1-115	75.0
BT50-CK1-145	82.1
BT50-CK1-200	95.3
BT50-CK2-105	75.0
BT50-CK2-135	82.1
BT50-CK2-165	78.6
BT50-CK2-235	95.3
BT50-CK3-110	75.0
BT50-CK3-140	82.1
BT50-CK3-175	78.6
BT50-CK3-290	140.7
BT50-CK3-300	140.7
BT50-CK3-350	189.3
BT50-CK4-100	75.0
BT50-CK4-160	78.6
BT50-CK4-205	101.0
BT50-CK4-270	140.7
BT50-CK4-300	140.7
BT50-CK4-350	189.3
BT50-CK5-90	75.0
BT50-CK5-165	78.6
BT50-CK5-210	101.0
BT50-CK5-270	140.7
BT50-CK5-300	140.7
BT50-CK5-350	189.3
BT50-CK6-95	75.0
BT50-CK6-155	78.6
BT50-CK6-215	101.0
BT50-CK6-250	140.7
BT50-CK6-300	140.7
BT50-CK6-350	189.3


CK Extension Rod

CK Extension Rod

Spesifikasie	prys
CK1-1-30	29.7
CK2-2-30	29.7
CK3-3-30	29.7
CK4-4-45	35.7
CK4-4-60	35.7
CK5-5-60	38.9
CK5-5-90	44.7
CK6-6-60	38.9
CK6-6-100	44.7
CK6-6-120	59.6

ER Collet Tool Holder

ER Collet Toolholder



Spesifikasie NO. xColletxA/MxL	prys USD
BT30-ER11-70	16.0
BT30-ER11-100	16.0
BT30-ER16-70	18.6
BT30-ER16-100	18.6
BT30-ER16-150	19.7
BT30-ER20-70	18.6
BT30-ER20-100	18.6
BT30-ER20-150	19.7
BT30-ER25-70	18.6
BT30-ER25-100	18.6
BT30-ER25-150	19.7
BT30-ER32-70	18.6
BT30-ER32-100	18.6
BT30-ER32-150	19.7
BT30-ER40-80	17.1
BT30-ER40-100	17.1

BT40-ER11-70	21.1
BT40-ER11-100	21.1
BT40-ER16-70	21.1
BT40-ER16-100	21.1
BT40-ER16-150	22.4
BT40-ER16-200	37.1
BT40-ER20-70	21.1
BT40-ER20-100	21.1
BT40-ER20-150	22.4
BT40-ER20-200	37.1
BT40-ER25-70	21.1
BT40-ER25-100	21.1
BT40-ER25-150	22.4
BT40-ER25-200	37.1
BT40-ER32-70	21.1
BT40-ER32-100	21.1
BT40-ER32-150	22.4
BT40-ER32-200	37.1
BT40-ER32-250	50.3
BT40-ER32-300	74.0
BT40-ER40-80	19.7
BT40-ER40-100	19.7
BT40-ER40-150	23.9
BT40-ER40-200	39.7

BT50-ER16-100	39.7
BT50-ER16-150	50.3
BT50-ER16-200	63.6
BT50-ER20-100	39.7
BT50-ER20-150	50.3
BT50-ER20-200	61.0
BT50-ER20-250	81.9
BT50-ER20-300	100.4
BT50-ER25-70	39.7
BT50-ER25-100	39.7
BT50-ER25-150	50.3
BT50-ER25-200	61.0
BT50-ER25-250	84.7
BT50-ER25-300	100.4
BT50-ER32-70	39.7
BT50-ER32-100	39.7
BT50-ER32-150	50.3
BT50-ER32-200	61.0
BT50-ER32-250	81.9
BT50-ER32-300	97.9
BT50-ER32-350	126.9
BT50-ER32-400	158.9
BT50-ER40-100	42.4
BT50-ER40-150	52.9
BT50-ER40-200	63.6
BT50-ER40-250	87.4
BT50-ER40-300	105.7
BT50-ER40-350	129.6
BT50-ER40-400	158.9
BT50-ER50-100	74.0
BT50-ER50-150	81.9
BT50-ER50-200	92.6
BT50-ER50-250	121.7
BT50-ER50-300	158.9

Spesifikasie NO. xColletxA/MxL	prys USD
R8-ER25	17.1
R8-ER32	17.1
R8-ER40	19.7
MTB3-ER20	16.0
MTB3-ER25	16.0
MTB3-ER32	17.1
MTB4-ER25	17.1
MTB4-ER32	18.6
MTB4-ER40	22.4
MTB5-ER40	26.4
NT30-ER25	17.1
NT30-ER32	17.1
NT30-ER40	19.7
NT40-ER25	17.1
NT40-ER32	17.1
NT40-ER40	19.7
ISO20-ER16-35MS	40.4
ISO25-ER20-35MS	40.4
ISO30-ER32-42	27.4
ISO30-ER32-60	27.4
HSK32E-ER16-050MS	82.1
HSK32E-ER20-050MS	82.1
HSK32E-ER20-060MS	82.1
HSK32E-ER25-060MS	82.1
BT30-GER16-70	21.4
BT30-GER16-100	21.4
BT30-GER20-70	21.4
BT30-GER20-100	21.4
BT30-GER25-70	21.4
BT30-GER25-100	21.4
BT40-GER16-70	21.4
BT40-GER16-100	21.4
BT40-GER20-70	23.9
BT40-GER20-100	23.9
BT40-GER25-70	23.9
BT40-GER25-100	23.9
BT40-GER32-70	23.9
BT40-GER32-100	23.9

ER Collet Extension Tool Holder

ER Collet Extension Toolholder



Spesifikasie DxColletxA/MxL	prys USD
C10-ER8-100	9.3
C10-ER8-150	10.4
C12-ER8-100	9.3
C12-ER8-150	10.4
C12-ER11-100	6.7
C12-ER11-150	6.7
C16-ER11-100	6.7
C16-ER11-150	6.7
C16-ER16-100	6.7
C16-ER16-150	6.7
C16-ER16-200	11.9
C16-ER16-250	16.0
C16-ER20-100	6.7
C16-ER20-150	6.7
C16-ER20-200	11.9
C20-ER20-100	6.7
C20-ER20-150	6.7
C20-ER20-200	11.9
C20-ER20-250	16.0
C20-ER16-100	6.7
C20-ER16-150	6.7
C20-ER16-200	11.9
C20-ER16-250	16.0
C20-ER11-100	9.3
C20-ER11-150	9.3
C20-ER25-100	10.4
C20-ER25-150	10.4
C25-ER16-100	6.7
C25-ER16-150	6.7
C25-ER16-200	11.9
C25-ER16-250	17.1
C25-ER20-100	6.7
C25-ER20-150	6.7
C25-ER20-200	11.9
C25-ER25-100	10.4
C25-ER25-150	11.9
C25-ER25-200	17.1
C25-ER25-250	19.7
C25-ER32-100	14.6
C25-ER32-150	17.1
C32-ER32-100	14.6
C32-ER32-150	17.1
C32-ER32-200	18.6
C32-ER32-250	22.4
C40-ER40-100	19.7
C40-ER32-100	17.1
C32-ER40-100	18.6

ER Uitbreiding Collet

ER Extension Collet



Spesifikasie Collet	presisie 0.01mm	presisie 0.008mm	presisie 0.005mm
ER8	3.1	-	-
ER11	1.7	2.2	5.3
ER16	1.7	2.2	5.3
ER20	1.7	2.2	5.3
ER25	1.9	2.2	5.3
ER32	2.6	2.8	6.7
ER40	4.0	-	6.7
ER50	11.9	-	-

ER Wrench / Noten

ER Wrench / Nuts



Spesifikasie Collet	Wrench	Nut
ER8A/M	2.6	4.0
ER11A/M	1.4	1.7
ER16A/M	1.7	1.7
ER20A/M	1.7	1.7
ER25UM	2.6	2.6
ER32UM	3.1	3.1
ER40UM	4.0	4.0
ER50UM	-	15.3

FMB Inch Face Milling Tool Holder

FMB Inch Face Milling Tool Holder



Spesifikasie NO. xdxL	prys USD
R8-FMA25. 4	17.1
R8-FMA31. 75	17.1
C20-FMB25. 4	17.1
NT50-FMA31. 75-75	43.6
NT50-FMA38. 1-75	43.6
NT50-FMA47. 625-75	92.6
NT50-FMA50. 8-75	55.4
BT40-FMA25. 4-60	17.1
BT40-FMA25. 4-100	19.7
BT40-FMA31. 75-60	18.6
BT40-FMA31. 75-100	19.7
BT40-FMA38. 1-60	19.7
BT40-FMA38. 1-100	21.1
BT50-FMA25. 4-60	42.4
BT50-FMA25. 4-100	42.4
BT50-FMA25. 4-150	52.9
BT50-FMA25. 4-200	63.6
BT50-FMA25. 4-250	84.7
BT50-FMA25. 4-300	111.1
BT50-FMA31. 75-60	43.6
BT50-FMA31. 75-100	43.6
BT50-FMA31. 75-150	56.9
BT50-FMA31. 75-200	67.4
BT50-FMA31. 75-250	87.4
BT50-FMA31. 75-300	119.0
BT50-FMA38. 1-60	42.4
BT50-FMA38. 1-100	45.0
BT50-FMA38. 1-150	59.6
BT50-FMA47. 625-75	84.7
BT50-FMA47. 625-150	145.4
BT50-FMA47. 625-200	198.3
BT50-FMA50. 8-75	55.4
BT50-FMA50. 8-100	68.9
BT50-FMA50. 8-150	79.3

FMB Metrieke gesigsmylhulpmiddelhouer

FMB Metric Face Milling Tool Holder

Spesifikasie NO. xdxL	prys USD
BT30-FMB22-45	14.6
BT30-FMB22-60	14.6
BT30-FMB22-100	18.6
BT30-FMB27-45	14.6
BT30-FMB27-60	14.6
BT30-FMB27-100	18.6
BT30-FMB32-45	16.0
BT30-FMB32-60	16.0
BT40-FMB22-45	17.1
BT40-FMB22-60	17.1
BT40-FMB22-100	18.6
BT40-FMB22-150	22.4
BT40-FMB22-200	37.1
BT40-FMB22-250	47.6
BT40-FMB22-300	61.0
BT40-FMB22-350	74.0
BT40-FMB27-45	17.1
BT40-FMB27-60	17.1
BT40-FMB27-100	18.6
BT40-FMB27-150	23.9
BT40-FMB32-60	17.1
BT40-FMB32-100	17.1
BT40-FMB32-150	23.9
BT40-FMB40-60	19.7
BT40-FMB40-100	21.1
BT40-FMB40-150	26.4
BT50-FMB22-60	39.7
BT50-FMB22-100	39.7
BT50-FMB22-150	50.3
BT50-FMB22-200	61.0
BT50-FMB22-250	81.9
BT50-FMB22-300	100.4
BT50-FMB22-350	119.0
BT50-FMB22-400	132.4
BT50-FMB22-450	153.3
BT50-FMB22-500	185.3
BT50-FMB22-550	211.7
BT50-FMB22-600	238.1
BT50-FMB27-60	39.7
BT50-FMB27-100	39.7
BT50-FMB27-150	52.9
BT50-FMB27-200	63.6
BT50-FMB27-250	84.7
BT50-FMB27-300	103.1
BT50-FMB27-350	119.0
BT50-FMB27-400	145.4
BT50-FMB32-60	42.4
BT50-FMB32-100	45.0
BT50-FMB32-150	56.9
BT50-FMB32-200	67.4
BT50-FMB32-250	87.4
BT50-FMB32-300	119.0
BT50-FMB40-60	42.4
BT50-FMB40-100	45.0
BT50-FMB40-150	58.1
BT50-FMB40-200	68.9
BT50-FMB40-250	90.0
BT50-FMB40-300	119.0
BT50-FMB60-75	84.7
BT50-FMB60-150	145.4

R8-FMB22	16.0
R8-FMB27	16.0
R8-FMB32	17.1
R8-FMB40	19.7
C20-FMB22	16.0
C20-FMB27	16.0
C20-FMB32	17.1
C25-FMB22	17.1
C25-FMB27	17.1
C25-FMB32	17.1
C32-FMB22	18.6
C32-FMB27	18.6
C32-FMB32	18.6
MT3-FMB22	17.1
MT3-FMB27	17.1
MT3-FMB32	17.1
MT4-FMB22	19.7
MT4-FMB27	19.7
MT4-FMB32	19.7
NT30-FMB22	18.6
NT30-FMB27	18.6
NT30-FMB32	18.6
NT40-FMB22	18.6
NT40-FMB27	18.6
NT40-FMB32	18.6
NT40-FMB40	21.1
NT50-FMB22	42.4
NT50-FMB27	42.4
NT50-FMB32	42.4
NT50-FMB40-75	43.6
NT50-FMB32-150	52.9
NT50-FMB32-200	63.6
NT50-FMB60-75	92.6

CNC Tool Holder CNC Tool Holder

MaiFix®

**GSK High Speed En
Hoë Presisie Gereedskaphouer**
GSK High Speed And
High presisie Toolholder



Spesifikasie NO. xColletxL	prys USD
BT30-GSK10-60	20.3
BT30-GSK10-90	20.3
BT30-GSK16-60	20.3
BT30-GSK16-90	20.3
BT40-GSK10-60	23.9
BT40-GSK10-100	23.9
BT40-GSK16-60	23.9
BT40-GSK16-100	23.9
Collet SK10	7.1
Collet SK16	9.0
Bearing Spanner	15.4

MTA / B Morse Taper Toolholder
MTA/B Morse Taper Toolholder



Spesifikasie NO. xMT...xL	prys USD
BT30-MTA2-75	16.0
BT30-MTA3-75	16.0
BT30-MTA4-75	16.0
BT40-MTA1-120	26.4
BT40-MTA1-45	18.6
BT40-MTA2-120	25.3
BT40-MTA2-60	16.0
BT40-MTA3-135	25.3
BT40-MTA3-75	16.0
BT40-MTA4-165	31.7
BT40-MTA4-90	17.1
BT50-MTA1-120	55.4
BT50-MTA1-45	43.6
BT50-MTA2-135	52.9
BT50-MTA2-60	39.7
BT50-MTA3-150	52.9
BT50-MTA3-75	39.7
BT50-MTA4-180	66.1
BT50-MTA4-90	39.7
BT50-MTA5-105	43.6
BT50-MTA5-210	90.0
NT40-MTA2	18.6
NT40-MTA3	18.6
NT40-MTA4	18.6
NT50-MTA1-45	43.6
NT50-MTA2-60	42.4
NT50-MTA3-75	42.4
NT50-MTA4-90	42.4
NT50-MTA5-105	43.6
BT40-MTB1-120	26.4
BT40-MTB1-45	18.6
BT40-MTB2-120	25.3
BT40-MTB2-60	16.0
BT40-MTB3-135	25.3
BT40-MTB3-75	16.0
BT40-MTB4-165	31.7
BT40-MTB4-90	17.1
BT50-MTB1-120	55.4
BT50-MTB1-45	43.6
BT50-MTB2-135	52.9
BT50-MTB2-60	39.7
BT50-MTB3-150	52.9
BT50-MTB3-75	39.7
BT50-MTB4-180	66.1
BT50-MTB4-90	39.7
BT50-MTB5-105	43.6
BT50-MTB5-210	90.0
NT40-MTB2	18.6
NT40-MTB3	18.6
NT40-MTB4	18.6
NT50-MTB1-45	43.6
NT50-MTB2-60	42.4
NT50-MTB3-75	42.4
NT50-MTB4-90	42.4
NT50-MTB5-105	43.6

C Kragtige sleutelhelpmiddel

C Powerful Collet Toolholder



Spesifikasie NO. xColletxL	prys USD
R8-C32	63.6
NT30-C25	63.6
NT30-C32	63.6
NT40-C25	63.6
NT40-C32-105	61.0
MT4-C32	74.0
MT5-C32	100.4
MT6-C32	145.4
MT6-C42	180.0
NT50-C32-105	92.6
NT50-C42-115	119.0
BT30-C20-80	61.0
BT30-C25-80	61.0
BT30-C32-105	61.0
BT40-C20-90	61.0
BT40-C25-90	61.0
BT40-C32-105	55.4
BT40-C42-100	105.7
BT50-C20-105	92.6
BT50-C25-105	92.6
BT50-C32-105	92.6
BT50-C32-135	105.7
BT50-C32-165	119.0
BT50-C32-200	145.4
BT50-C32-250	171.9
BT50-C32-300	224.7
BT50-C42-115	119.0
BT50-C42-135	132.4
BT50-C42-165	145.4
BT50-C42-200	171.9
BT50-C42-250	211.7
BT50-C42-300	259.3
SK50-C32-110	171.9
JT50-C32-110	171.9
Collet C20	3.6
Collet C25	3.6
Collet C32	3.6
Collet C42	7.6
Wrench C20/25/32/42	3.9

Tool Shank Of
Self-aansteker Boor Chuck


Tool Shank Of
Self-Tightening
Drill Chuck



Spesifikasie NO. xColletxL	prys USD
APU13 Drill Chuck	23.9
APU16 Drill Chuck	26.4
BT30-APU08-80	37.1
BT30-APU13-100	37.1
BT30-APU16-100	39.7
BT40-APU08-100	37.1
BT40-APU13-100	37.1
BT40-APU16-120	39.7
BT50-APU13-110	58.1
BT50-APU13-180	79.3
BT50-APU16-130	62.1
BT50-APU16-180	84.7
NT30-APU13-100	39.7
NT40-APU13-100	39.7
NT30-APU16-120	42.4
NT40-APU16-120	42.4
Self-aansteker Boor Chuck1-13	19.7
Self-aansteker Boor Chuck1-16	23.9
C20-APU13	31.7
C20-APU16	34.3
C32-APU13	35.7
R8-APU13	31.7
R8-APU16	34.3
MT3-APU13	30.4
MT4-APU13	30.4
MT3-APU16	33.1
MT4-APU16	33.1
APU Wrench (08/13/16)	1.9

SDC Back-pull Collet Tool Holder

SDC Back-Pull Collet Toolholder



Spesifikasie NO. xColletxL	prys USD
BT30-SDC6-90	59.6
BT30-SDC8-90	59.6
BT30-SDC10-90	59.6
BT30-SDC12-90	59.6
BT40-SDC6-90	63.6
BT40-SDC8-90	63.6
BT40-SDC10-90	63.6
BT40-SDC12-90	63.6
BT40-SDC6-120	79.3
BT40-SDC8-120	79.3
BT40-SDC10-120	79.3
BT40-SDC12-120	79.3
COLLET	
Collet SDC06	11.9
Collet SDC08	11.9
Collet SDC10	13.1
Collet SDC12	13.1

Torsion Tapping Protection Tool Holder

Torsional Tapping Protection Toolholder



Spesifikasie NO. xColletxL	prys USD
BT50-J4112	119.0
BT50-J4124	132.4
BT40-J4112	79.3
BT40-J4124	92.6
MT3-J4112	74.0
MT4-J4112	79.3
MT5-J4124	100.4

Tap Collets

Spesifikasie NO. xColletxL	prys USD
GT312 China Standard	16.0
GT312 Japanese Standard	18.6
GT24 China Standard	19.7
GT24 Japanese Standard	22.4

Side Frees Tool Holder of Saw Blade

Side Milling Tool Holder of Saw Blade



Spesifikasie NO. xColletxL	prys USD
BT40-SCA22-90	65.4
BT40-SCA25.4-90	65.4
BT40-SCA25.4-120	83.3
BT40-SCA27-90	65.4
BT40-SCA32-90	65.4

Masjiengereedskap Spindel Toetsstang


Machine Tool Spindle Test Rod



Spesifikasie NO. xL	prys USD
BT30	92.9
BT40	92.9
BT50	131.0

SLN Side Fixed Type Tool Holder

SLN Side Fixed Type Toolholder



Spesifikasie NO. xdxL	prys USD
BT30-SLN12	16.0
BT30-SLN16	16.0
BT30-SLN20	16.0
BT30-SLN25	16.0
BT30-SLN32	16.0
BT40-SLN06-75	21.1
BT40-SLN08-75	21.1
BT40-SLN10-75	21.1
BT40-SLN12-75	17.1
BT40-SLN16-75	17.1
BT40-SLN20-75	17.1
BT40-SLN20-150	25.3
BT40-SLN25-100	17.1
BT40-SLN25-150	25.3
BT40-SLN32-100	17.1
BT40-SLN32-150	25.3
BT40-SLN40-100	19.7
BT50-SLN06-105	46.1
BT50-SLN08-105	46.1
BT50-SLN10-105	46.1
BT50-SLN12-105	39.7
BT50-SLN16-105	39.7
BT50-SLN20-105	39.7
BT50-SLN25-105	39.7
BT50-SLN32-105	39.7
BT50-SLN40-105	42.4
BT50-SLN40-150	52.9
BT50-SLN40-200	63.6
BT50-SLN40-250	92.6
BT50-SLN40-300	105.7
BT50-SLN50.8-120	55.4

Spesifikasie NO. xdxL	prys USD
C10-SLN4-100	22.4
C10-SLN4-150	22.4
C10-SLN6-100	22.4
C10-SLN6-150	22.4
C12-SLN4-100	22.4
C12-SLN4-150	22.4
C12-SLN6-100	22.4
C12-SLN6-150	22.4
C12-SLN8-100	22.4
C12-SLN8-150	22.4
C16-SLN10-100	22.4
C16-SLN10-150	22.4
C16-SLN6-100	22.4
C16-SLN6-150	22.4
C16-SLN8-100	22.4
C16-SLN8-150	22.4
C20-SLN10-100	25.3
C20-SLN10-150	25.3
C20-SLN6-100	25.3
C20-SLN6-150	25.3
C20-SLN8-100	25.3
C20-SLN8-150	25.3

Spesifikasie NO. xdxL	prys USD
NT40-SLN12	19.7
NT40-SLN16	19.7
NT40-SLN25	19.7
NT40-SLN32	19.7
NT50-SLN12	42.4
NT50-SLN16	42.4
NT50-SLN20	42.4
NT50-SLN25	42.4
NT50-SLN32	42.4
NT50-SLN40-105	43.6
NT50-SLN42-105	47.6
NT50-SLN50.8-120	55.4

Spesifikasie NO. xdxL	prys USD
ISO20-11.3-Probe	40.4
ISO25-11.3-Probe	40.4
ISO25-20-Probe	40.4
HSK32E-11.3-Probe	82.1

Bogenoemde prys sluit vraag, belasting en fooi in.
Binnelandse USD Dollar Transaksieprys In China.
As jy enige vrae het, stuur asb. E-pos: eva@mzgtool.cn

<http://www.mzg.tw>

CNC Tool Holder Puller Bolt


CNC Tool Holder Puller Bolt

45°/60°/90°



CNC Tool Holder Lockset

CNC Tool Holder Lockset




CNC Tool Holder Lockset

CNC Tool Holder Lockset



CNC Tool Holder Lockset

CNC Tool Holder Lockset



Spesifikasie	prys USD	Spesifikasie	prys USD	Spesifikasie	prys USD	Spesifikasie	prys USD
BT30-45°	1.4	NBT30	14.3	ISO20	59.6	BT30	17.9
BT30-60°	1.4			ISO25	59.6	BT40	19.0
BT30-90°	1.9			HSK25	59.6	BT50	38.1
BT40-45°	1.4			HSK32	59.6		
BT40-45° Deur gaatjie	1.9			HSK40	71.4		
BT40-60°	1.9			HSK50	71.4		
BT40-90°	1.9			HSK63	83.3		
BT50-45°	3.1			HSK100	119.0		
BT50-45° Deur gaatjie	3.6						
BT50-60°	3.6						
BT50-60° Deur gaatjie	3.9						
BT50-90°	3.6						
DIN69872-30	3.6						
DIN69872-40	3.6						
DIN69872-50	6.0						
ISO7388-30	4.6						
ISO7388-40	4.6						
ISO7388-50	6.0						
JIS6339-30	3.6						
JIS6339-40	3.6						
JIS6339-50	6.0						
MAZAK-BT40	3.6						
MAZAK-BT50	6.0						

Spesifikasie	prys USD	Spesifikasie	prys USD	Spesifikasie	prys USD
fotoelektriese Z-axis Setter	61.9	gewone type	2.4	BT30	3.9
Dial Z-axis Setter	66.7	Antimagnetic type	3.6	BT40	3.9
		Keramiek magneet type	10.7	BT50	5.4
		fotoelektriese type	13.3		

Z-Axis Setter

Z-Axis Setter



fotoelektriese



Dial

CNC Edge Finder

CNC Edge Finder



gewone Antimagnetic Ceramic fotoelektriese

Masjiengereedskap Spoelreinigerstang

Machine Tool Spindle Cleaning Rod



Spesifikasie	1 JAWS	prys	2 JAWS	prys	3 JAWS	prys	4 JAWS	prys
Holle Hydraulic Chuck	4 inch		SBL-204	435.3	SB-204	435.3	SBS-204	-
	5 inch		SBL-205	435.3	SB-205	435.3	SBS-205	482.9
	6 inch		SBL-206	492.9	SB-206	492.9	SBS-206	561.9
	8 inch		SBL-208	544.0	SB-208	544.0	SBS-208	629.7
	10 inch		SBL-210	697.6	SB-210	697.6	SBS-210	800.0
Hollow Hydraulic Chuck	12 inch		SBL-212	1190.4	SB-212	1190.4	SBS-212	1326.1
	15 inch		SBL-215	2642.9	SB-215	2642.9	SBS-215	3000.0
Groot diafragma Holle Hydraulic Chuck	6 inch		2DTK-206	647.6	3DTK-206	647.6	4DTK-206	714.3
	8 inch		2DTK-208	782.1	3DTK-208	782.1	4DTK-208	869.0
Large Aperture Hollow Hydraulic Chuck	10 inch		2DTK-210	935.7	3DTK-210	935.7	4DTK-210	1038.1
Lang slag Holle Hydraulic Chuck	6 inch				3JDB-206	988.1		
	8 inch				3JDB-208	1121.4		
Long Stroke Hollow Hydraulic Chuck	10 inch				3JDB-210	1258.3		
Hollow Half-Through Pneumatische Chuck	5 inch		SBL-205KQ	595.3	SB-205KQ	547.6	SBS-205KQ	666.7
	6 inch		SBL-206KQ	631.0	SB-206KQ	611.9	SBS-206KQ	714.3
	8 inch		SBL-208KQ	714.3	SB-208KQ	681.0	SBS-208KQ	788.1
	10 inch		SBL-210KQ	785.7	SB-210KQ	750.0	SBS-210KQ	908.6
Vaste Hydraulic Chuck	4 inch		JNL-04	428.6	JN-04	401.1		
	5 inch		JNL-05	452.4	JN-05	409.6		
	6 inch		JNL-06	500.0	JN-06	459.6		
	8 inch		JNL-08	547.6	JN-08	511.9		
	10 inch		JNL-10	714.3	JN-10	666.7		
	12 inch		JNL-12	1119.0	JN-12	1088.1		
	15 inch		JNL-15		JN-15	2309.6		
Lang slag Vaste Hydraulic Chuck	5 inch	1L-05	547.6	2L-05	511.9	3L-05	595.3	
	6 inch	1L-06	595.3	2L-06	544.0	3L-06	642.9	
	8 inch	1L-08	619.0	2L-08	542.9	3L-08	666.7	
Long Stroke Solid Hydraulic Chuck	10 inch	1L-10	833.3	2L-10	750.0	3L-10	881.0	
Lang slag Holle Hydraulic Chuck	6 inch				JLS-206	892.9		
	8 inch				JLS-208	940.4		
Long Stroke Hollow Hydraulic Chuck	10 inch				JLS-210	1038.1		

Chuck T Blok

Chuck T Blok



dimensies	prys USD
5 inch	10.7
6 inch	11.9
8 inch	15.4
10 inch	19.0
12 inch	22.1

Chuck Jaw Fixing Plate

Chuck Jaw Fixing Plate



dimensies	prys USD
5 inch	61.9
6 inch	73.9
8 inch	107.1
10 inch	115.4

Vaste Hidrouliese Rotary Cylinder

Solid Hydraulic Rotary Cylinder



dimensies	prys USD
5 inch(0815)	109.6
6 inch(1020)	131.0
8/10inch(1225)	150.0
12 inch(1530)	197.6

Hol hidrouliese roterende silinder

Hollow Hydraulic Rotary Cylinder



dimensies	prys USD
4 inch(428)	261.9
5 inch(1036)	273.9
6 inch(1246)	306.0
8 inch(1552)	357.1
10 inch(1875)	647.6
12 inch(2091)	1309.6

Chuck Connecting Disc

Chuck Connecting Disc



dimensies	prys USD
4 inch	35.7
5 inch	21.4
6 inch	21.4
8 inch	35.7
10 inch	47.6
12 inch	71.4

Harde Kaak Vir Hidrouliese Chucks

Hard Jaw For Hydraulic Chucks



dimensies	prys USD
5 inch	102.4
6 inch	119.0
8 inch	131.0
10 inch	163.1
12 inch	204.7
15 inch	369.0

Fan Sagte Kaak Vir Hidrouliese Chucks

Fan Soft Jaw For Hydraulic Chucks




dimensies	prys USD
5 inch	
6 inch	
8 inch	
10 inch	
12 inch	
15 inch	

Spesifikasie	1 JAWS	prys	2 JAWS	prys	3 JAWS	prys	4 JAWS	prys
vergoeding Vaste Hydraulic Chuck Compensation Solid Hydraulic Chuck	6 inch	3GB-06	720.3					
	8 inch	3GB-08	839.3					
vertikale Holle Hydraulic Chuck	5 inch		JYL-05	738.1	JY-05	714.3	JYS-05	833.3
	6 inch		JYL-06	785.7	JY-06	761.9	JYS-06	904.7
	8 inch		JYL-08	928.6	JY-08	904.7	JYS-08	976.1
	10 inch		JYL-10	1023.9	JY-10	988.1	JYS-10	1107.1
Hollow Half-Through Vertikale Pneumatische Chuck	5 inch		SBL-205KQL	714.3	SB-205KQL	690.4	SBS-205KQL	785.7
	6 inch		SBL-206KQL	773.9	SB-206KQL	750.0	SBS-206KQL	857.1
	8 inch		SBL-208KQL	904.7	SB-208KQL	881.0	SBS-208KQL	952.4
Hollow Half-Through Vertical Pneumatische Chuck	10 inch		SBL-210KQL	976.1	SB-210KQL	952.4	SBS-210KQL	1071.4

Sagte kakebeen vir hidrouliese kuikens

Soft Jaw For Hydraulic Chucks



Standaard Sagte Kaak Vir Hidrouliese Chucks

Standard Soft Jaw For Hydraulic Chucks

dimensies	a°	H	prys USD
4 inch		23	10.3
5 inch		30	10.3
6 inch	60°	36	11.9
8 inch	90°	38	13.9
10 inch	120°	42	16.1
12 inch		50	27.4
15 inch		62	67.9

dimensies	H	prys USD	dimensies	H	prys USD	dimensies	H	prys USD	dimensies	H	prys USD	dimensies	H	prys USD
5H40	40	13.6	6H50	50	17.1	8H40	40	20.4	10H50	50	23.9	12H60	60	34.6
5H50	50	17.1	6H60	60	20.4	8H50	50	20.4	10H60	60	27.4	12H70	70	40.4
5H60	60	20.4	6H70	70	23.9	8H60	60	23.9	10H70	70	31.0	12H80	80	47.6
5H70	70	23.9	6H80	80	28.9	8H70	70	27.4	10H80	80	34.6	12H90	90	59.6
5H80	80	39.3	6H90	90	32.4	8H80	80	31.0	10H90	90	41.7	12H100	100	73.9
5H90	90	45.3	6H100	100	37.6	8H90	90	35.7	10H100	100	50.0	12H120	120	80.0
5H100	100	51.1	6H120	120	51.1	8H100	100	42.9	10H110	110	54.7	12H150	150	94.0
			6H130	130	56.0	8H120	120	51.1	10H120	120	59.6			
			6H150	150	61.9	8H130	130	54.7	10H130	130	68.1			
						8H140	140	65.4	10H150	150	80.0			
						8H150	150	69.0	10H170	170	102.4			
						8H200	200	135.7	10H180	180	109.6			
									10H200	200	146.4			

Bogenoemde prys sluit vraag, belasting en fooi in.

Binnelandse USD Dollar Transaksieprys In China.

As jy enige vrae het, stuur asb. E-pos: eva@mzgtool.cn

<http://www.mzg.tw>

Machine Tools Price



E-mail: eva@mzgtool.cn



WeChat



Twitter



LinkedIn



Facebook



Skandeer, Kontak ons

Dongguan Ming Ze Hardware Machinery Co., Ltd.

Operation Center: No.42-1, # Article, Changrong International Machinery Hardnery Hardware Plaza, No.56, Wusha Zhen'anzhong Road, Changan town, Dongguan city, Guangdong Province, China

TEL: +86-013929492387

([Wechat/Facebook/Twitter/Whatsapp/Linkedin](#))

FAX: +86-769-85359513

Website: <http://www.mzg.tw>

E-mail: eva@mzgtool.cn